



Corporate Finance Department
Materials Management Division

ADDENDUM NO. 1 to TENDER NO. 579-2003

FAIRFIELD PARK LOCAL IMPROVEMENT DISTRICT STORMWATER RETENTION BASIN EXCAVATION, OUTFALLS & ASSOCIATED WORKS

ISSUED: December 29, 2003
BY: Scott Harnish, Wardrop Engineering Inc.
TELEPHONE NO. (204) 956-0980

URGENT

**PLEASE FORWARD THIS DOCUMENT TO WHOEVER
IS IN POSSESSION OF THE TENDER PACKAGE**

**THIS ADDENDUM SHALL BE INCORPORATED
INTO THE TENDER PACKAGE AND SHALL
FORM A PART OF THE CONTRACT
DOCUMENTS**

Please note the following and attached changes, corrections, additions, deletions, information and/or instructions in connection with the Tender Package, and be governed accordingly. Failure to acknowledge receipt of this Addendum in Paragraph 10 of Form A: Tender may render your Tender Submission non-responsive.

PART A – TENDER SUBMISSION

Replace Form B: Prices with Form B (Addendum No. 1): Prices attached.

PART B – BIDDING PROCEDURES

B5. ADDENDA

Revise B5.3 to read:

B5.3 The Bidder shall acknowledge receipt of each addendum in Paragraph 10 of Form A: Tender. Failure to acknowledge receipt of an addendum may render a Bid non-responsive.

PART D – SUPPLEMENTAL CONDITIONS

D3. DEFINITIONS

Add to D3.1:

- (b) "CSP" means corrugated steel pipe.
- (c) "SRB" means stormwater retention basin.

PART E – SPECIFICATIONS

GENERAL

Where the description clause for any Specification within PART E refers to “Special Provision”, substitute “Specification”.

E3. SEWER MANHOLES

Revise E3.2.1 (a) to read:

- (a) The manhole base section shall be bedded on a thoroughly compacted 100 mm thick bed of crushed limestone. This bedding shall be fully compacted and levelled throughout the full trench width to the exact grade specified so that the base section is uniformly and fully supported and the floor level.

E7. CONTROL CHAMBER REINFORCING STEEL

Renumber the following Clauses as follows:

- E7.3.5 Method of Measurement as E7.4 Method of Measurement
- E7.3.6 Supply and Placement of Reinforcing Steel as E7.4.1 Supply and Placement of Reinforcing Steel
- E7.3.7 Basis of Payment as E7.4.2 Basis of Payment

E12. PRECAST TURFSTONE AND MAINTENANCE EQUIPMENT RAMP SECTIONS

Delete E12.3 and E12.3.1

DRAWINGS

DRAWING LD-2975 (C0002)

Add the following Note and apply it to all poles on the north side of Lee Boulevard between Manholes S04 and S06:

CONTRACTOR TO ARRANGE FOR TEMPORARY POLE SUPPORT IF REQUIRED

DRAWING LD-2980 (C0007)

Note the following for Details 1 and 2 (Ditch Inlet Structure):

- Ditch Inlet Structures shall be constructed as part of Manholes S05 and S06.
- The Inlet Elevation shown on the Ditch Inlet Structure Detail shall correspond to the Rim Elevations for Manholes S05 and S06.
- For Manhole S05, the ladder rungs shown on the Ditch Inlet Structure Detail shall be placed on the “front” wall of the manhole, opposite the wall where the 750 mm LDS connects to the manhole base.