PART E SPECIFICATIONS

PART E - SPECIFICATIONS

GENERAL

E1. GENERAL

E1.1 These Specifications shall apply to the Work.

E2. GOODS

- E2.1 The Contractor shall supply and deliver utility trailers in accordance with the requirements hereinafter specified.
- E2.2 The trailer shall comply with all Canadian Motor Vehicle Safety Standards (C.M.V.S.S.) and the Manitoba Highway Traffic Act regulations and requirements.
- E2.3 Item No. 1 24 foot long trailer shall include the following as a minimum:
 - (a) Trailer deck shall not be narrower than 102 inches and it shall be a deck-over style (no fenders protruding above the deck);
 - (b) A front rail, minimum height of 12 inches mounted to the trailer;
 - (c) steel mesh vehicle loading ramps;
 - (d) 12,000 lb jack;
 - (e) Trailer wiring and lighting shall meet all regulations as recommended by Manufacturer. Wiring shall be secured, loomed and protected from wear points;
 - (f) Licence plate bracket c/w light required, c/w preferred LED lamp;
 - (g) 2 6,000 lb axles;
 - (h) electric brakes;
 - (i) 4 − 215-85-R16 tires on 16" 5 bolt wheels;
 - (j) 2 5/16 " ball hitch;
 - (k) 4 leaf spring suspension;
 - (I) galvanized steel construction, primed and power coat painted;
 - (m) treated wood floor;
 - (n) safety chains and hooks;
 - (o) Spare tire mounted on a rim; and
 - (p) Heavy duty winch mounted to the trailer, capable of pulling 2000 lbs up onto the deck.
- E2.4 Item No. 2 16' trailer shall include the following as a minimum:
 - (a) Trailer deck shall not be narrower than 83 inches;
 - (b) A front rail, minimum height of 12 inches mounted to the trailer;
 - (c) steel mesh vehicle loading ramps;
 - (d) 12,000 lb jack;
 - (e) Trailer wiring and lighting shall meet all regulations as recommended by Manufacturer.
 Wiring shall be secured, loomed and protected from wear points;
 - (f) Licence plate bracket c/w light
 - (g) 2 6,000 lb axles;

Template Version: G320040301

- (h) electric brakes;
- (i) 4 215-85-R16 tires on 16" 5 bolt wheels;
- (j) 2 5/16 " ball hitch;
- (k) 4 leaf spring suspension;
- (I) galvanized steel construction, primed and power coat painted;
- (m) treated wood floor;
- (n) safety chains and hooks;
- (o) Spare tire mounted on a rim; and
- (p) Heavy duty winch mounted to the trailer, capable of pulling 2000 lbs up onto the deck.

E3. DELIVERY

- E3.1 Goods shall be delivered F.O.B. destination; freight prepaid within thirty (30) Business Days of the placing of an order, except where otherwise agreed at the time of ordering.
- E3.2 Goods shall be delivered between 8:30 a.m. and 4:30 p.m. on Business Days.