LUMINAIRE SCHEDULE											
SYMBOL	TYPE	VOLTS	INPUT WATTS	DESCRIPTION	QTY	AMPS TYPE	BALLAST	MANUFACTURING/ CATALOG NUMBER	MOUNTING		
(A)	FLUOR	120	64	300mm x 1200mm INDUSTRIAL UNIT, HEAVY DUTY STEEL REFLECTOR WITH 20% UPLIGHT, BAKED WHITE ENAMEL FINISH PAINTED AFTER FABRICATION	2	F32T8/ 32W, RS, 35K	HPF, CBM 265ma FUSED ELECTRONIC	LITHONIA AF SERIES	SURFACE OR PENDANT, SEE PLANS		
⊠ (B)	HALOGEN	12	12W	250mm x 275mm x 160mm DEEP, EMERGENCY STANDBY, NEMA 4X NON METALLIC ENCLOSURE, NICKEL CADMIUM SEALED BATTERY, LAMP DISCONNECT SWITCH, 15 MINUTE TIME DELAY COMPLETE WITH TWO HALOGEN LAMP HEADS	2		N/A	STANPRO SLBIF SERIES	WALL MOUNT		
₩ ©	HALOGEN			REMOTE HEAD FOR TYPE B	2		N/A	STANPRO SLBIF SERIES	WALL MOUNT		
⊠ (D)	LED	120	3.8	EXIT LIGHT, SELF-CONTAINED BATTERY. 300mm(H) x 250mm(W) x 50mm(D) NOM DIM HOUSING WITH BRUSHED ALUM FACEPLATES. 20mm x 150mm(H) RED LETTERS. INTEGRAL LONG LIFE NICAD BATTERY. SELF TESTING WITH BI-COLOR/TRI-LEVEL STATUS INDICATOR LIGHT. DOUBLE FACE AND ARROWS AS SHOWN ON PLANS UNIVERSAL MOUNT	N/A	FURN W/ UNIT	N/A	STANPRO SLEXC SERIES	CLG X END HX WALL HX MOUNT ON RECESSED OUTLET BOX		
ŒΣ	мн	120	476	600mm(DIA) x 700mm DEEP CAST ALUMINIUM BALLAST, HOUSING, GLASS REFLECTOR WITH TEMPERED GLASS BOTTOM CLOSURE	1	400W CLEAR	HPF, CBM	LITHONIA DURA BAY	PENDANT/CEILING		
¤(F)	МН	120	476	SAME AS TYPE E, EXCEPT WITH STANDBY QUARTZ LAMP	1	400W CLEAR	HPF, CBM	LITHONIA DURA BAY	PENDANT		
<u> </u>	FLUOR	120	64	120mm(D) x 120mm(H) x 1200mm(L) WALL UNIT, STEEL HOUSING WITH BAKED WHITE ENAMEL FINISH, 100% VIRGIN ACRYLIC SMOOTH WHITE DIFFUSER	2	F32T8/ 32W, RS, 35K	HPF, CBM 265ma FUSED ELECTRONIC	LITHONIA WC2 32 120 GEB CSA	WALL MOUNT +2300mm AFF AND ABOVE STAIR LANDING		
ÄΦ	мн	120	211	400mm x 410mm WALL UNIT, PRISMATIC POLYCARBONATE REFRACTOR, CAST ALUMINIUM HOUSING	1	175W CLEAR	HPF, CBM	LITHONIA TWP SERIES	WALL MOUNT		
	FLUOR	120	64	1200mm FLUORESCENT LIGHT FIXTURE, 120VAC HIGH P.F. ELECTRONIC BALLAST, 2 x 32W-T8-4100K LAMP, TOTALLY ENCLOSED AND GASKETED HOUSING, SUITABLE FOR WET OR DAMP LOCATION, CEILING PENDANT MOUNTED AND ALL NECESSARY MOUNTING HARDWARE		F032T8/ 32W, RS, 35K	HPF, CBM 265ma FUSED ELECTRONIC	LITHONIA DMW SERIES	CEILING		
<u></u>	MH	208	1000	300mm x 500mm" METAL HALIDE, LUMINAIRE DOWN EMITTING LIGHT THROUGH POLYCARBONATE LENS, POLYESTER POWDER COAT. WHITE FINISH ON LUMINAIRE HOUSING, LIGHT GUIDE SIDE PANELS. 3000mm LIGHT GUIDE WITH WHITE ALUMINIUM SIDE PANELS AND NON EMITTING WHITE ABS UPPER HOUSING.	1	1000W BT MOGUL BASE	REMOTE MOUNT M47 TYPE	TIR ILLUMIWAVE	PENDANT		
ЖK	FLUOR	120	26	420mm(DIA) x 270mm DEEP COMPACT FLUORESCENT DOWN LIGHT. RUGGED ALUMINIUM LAMP HOLDER HOUSING.	1	26DTT	COMPACT	GOTHAM AFV 26DTT	RECESSED T BAR		
	FLUOR	120	64	600mm x 1200mm RECESSED STATIC TROFFER 16 CELLS (2 ROWS OF 8) SEMI— SPECULAR.120mm DEEP PARA—CONTURED HOUSING INTEGRAL GRID LOCK FEATURES.	2	F32T8	CBM/ETL CLASS "P"	COOPER 2P2GAx232	RECESSED T BAR		
M	FLUOR	120	64	300mm x 1200mm PARABOLIC RECESSED STATIC TROFFER, 26 CELL (2 ROW OF 13). 140mm DEEP PARA—CONTURED HOUSING.	2	F32T8	CBM/ETL CLASS "P"	COOPER P2GAx232	RECESSED T BAR		
Äω	МН	120	70	400mm x 410mm WALL UNIT, PRISMATIC POLYCARBONATE REFRACTOR, CAST ALUMINIUM HOUSING	1	70W CLEAR	HPF, CBM	LITHONIA TWP SERIES	WALL MOUNT		
□□□	FLUOR	120	34	120mm(D) x 120mm(H) x 600mm(L) WALL UNIT, STEEL HOUSING WITH BAKED WHITE ENAMEL FINISH, 100% VIRGIN ACRYLIC SMOOTH WHITE DIFFUSER	2	17W T8	HPF, CBM	LITHONIA WC2 17 120 GEB CSA	WALL MOUNT		
	FLUOR	120	64	120mm(D) x 120mm(H) x 1200mm(L) WALL UNIT, STEEL HOUSING WITH BAKED WHITE ENAMEL FINISH, 100% VIRGIN ACRYLIC SMOOTH WHITE DIFFUSER	2	F32T8/ 32W, RS, 35K	HPF, CBM 265ma FUSED ELECTRONIC	LITHONIA WC2 32 120 GEB CSA	WALL MOUNT +2300mm AFF AND ABOVE STAIR LANDING		
¤@	МН	120	211	420mm(DIA) x 500mm DEEP CAST ALUMINIUM BALLAST HOUSING, INJECTION MOLDED ACRYLIC REFRACTOR	1	175W CLEAR	HPF, CBM	LITHONIA TXV SERIES	PENDANT/CEILING		

	LUMINAIRE SCHEDULE										
SYMBOL	TYPE	VOLTS	INPUT WATTS	DESCRIPTION	LAMPS QTY TYPE		BALLAST	MANUFACTURING/ CATALOG NUMBER	MOUNTING		
	FLUOR	120	120	300mm x 1200mm INDUSTRIAL UNIT, HEAVY DUTY STEEL REFLECTOR WITH FULL DEPTH END PLATES, 20% UPLIGHT. BAKED ENAMEL FINISH PAINTED AFTER FABRICATION.	2	F54T5HO/ 54W, RS, 35K	HPF, CBM 265ma FUSED ELECTRONIC	LITHONIA PV	SURFACE OR PENDANT, SEE PLANS		
Д®	HPS	120	90	EXTERIOR WALL UNIT, SHARP CUT OFF ALUMINUM CANOPY, BAKED BRONZE POLYESTER POWDER COAT, SST HARDWARE, TEMPERED GLASS LENS, UL LISTED FOR WET LOCATIONS WITH BUILT—IN PHOTOCELL.	1	70W HPS	HPF	LITHONIA WST SERIES	WALL		
Ϋ́	INC	120	150	HEAVY DUTY CAST ALUMINUM, POLYESTER POWDER COATED HOUSING, ENCLOSED AND GASKETTED, GLASS GLOBE, WALL MOUNTING, WITH CAST ALUMINUM GUARD.	1	150W INC		NRL EXACTA SERIES	WALL		
U	FLUOR	120	64	250x1200 mm DIRECT/INDIRECT, DIE FORMED STEEL HOUSING, SPECULAR ALUMINUM REFLECTOR, WHITE STEEL HOUSING.	2	F32T8/ 32W, RS, 35K	HPF, CBM 265 mA FUSED ELECTRONIC	PEERLITE CERRA SERIES	CEILING		

	B.M ELE					CH2MHILL	-	ENGINEER'S SEAL	THE CITY OF W	INNIPEG	
EAPEGN					Frederickson Cooper		Earth Tech A Tyco International Ltd. Company	ORIGINAL SIGNED BY	Winnipeg WATER AND WASTE DEPARTMENT ENGINEERING DIVISION		
Certificate of Authorization					DESIGNED BY	JT	CHECKED ND	L.D. LLEWELLYN	WATER TREATMENT PLANT	CITY FILE NUMBER	
CH2M HILL Canada Ltd.					DRAWN BY	KJ	APPROVED AHL	2006/03/29	MAIN BUILDING MECHANICAL AND ELECTRICAL	SHEET OF	
No. 1441 Expiry: April 30, 2006	<u> </u>				SCALE:	NTS	RELEASED FOR CONSTRUCTION BY:		ELECTRICAL	CITY DRAWING NUMBER	
	00	ISSUED FOR TENDER	06/03/29	LL			R. SOROKOWSKI	CONSULTANT DRAWING NO.		1-0601B-D-E0501-001-00D	
	NO.	REVISIONS	DATE	BY	DATE	2005/06/29	DATE 2006/03/29	WB-E0501	LUMINAIRE SCHEDULE		