



## 256-2008 ADDENDUM 3

### ELZEAR GOULET MEMORIAL PARK

#### **URGENT**

**PLEASE FORWARD THIS DOCUMENT TO  
WHOEVER IS IN POSSESSION OF THE BID  
OPPORTUNITY**

ISSUED: April 22, 2008  
BY: Prachi Rajguru  
TELEPHONE NO. (204) 956-0396

**THIS ADDENDUM SHALL BE INCORPORATED  
INTO THE BID OPPORTUNITY AND SHALL  
FORM A PART OF THE CONTRACT  
DOCUMENTS**

Template Version: A20070419

---

Please note the following and attached changes, corrections, additions, deletions, information and/or instructions in connection with the Bid Opportunity, and be governed accordingly. Failure to acknowledge receipt of this Addendum in Paragraph 10 of Form A: Bid may render your Bid non-responsive.

---

#### **PART A – BID SUBMISSION**

Replace: 256-2008 Bid Submission with 256-2008 Addendum 3 Bid Submission. The following is a summary of changes incorporated in the replacement Bid Submission:

Form B(R1): Revised Item No. 20 & 21.

#### **PART E – SPECIFICATIONS**

Revise: E23.8 to read: E23.8 Placement and compaction of crushed granular limestone:

- (a) Place crushed granular base course material to a minimum compacted thickness of 127mm. Compact to 98% standard proctor density.
- (b) Place crushed granular levelling course material to a minimum compacted thickness of 38mm. Compact to 98% standard proctor density.
- (c) Crushed Limestone fines to a minimum compacted thickness of 13mm as finishing course. Compact to 95% standard proctor density.
- (d) Add crushed granular material as required to replace unsuitable subgrade material. Place in layers not exceeding 200mm thickness and compact to 98% standard proctor.
- (e) Finished surface to be within 12mm of specified grade, but not uniformly high or low. Ensure positive drainage on paved areas and in adjacent sodded areas.

#### **DRAWINGS**

Replace: 256-2008 \_Drawing\_E1 with 256-2008 \_Addendum\_3 Drawing E1