



270-2008 ADDENDUM No. 1

DESIGN AND CONSTRUCTION – WADING POOL WATERSLIDES AND RESILIENT RUBBER SAFETY SURFACING AT VARIOUS COMMUNITY CENTRES AND PARKS

URGENT

**PLEASE FORWARD THIS DOCUMENT TO
WHOEVER IS IN POSSESSION OF THE BID
OPPORTUNITY**

ISSUED: April 16, 2008
BY: Coleen Groening
TELEPHONE NO. (204) 986-2491

**THIS ADDENDUM SHALL BE INCORPORATED
INTO THE BID OPPORTUNITY AND SHALL
FORM A PART OF THE CONTRACT
DOCUMENTS**

Template Version: A20070419

Please note the following and attached changes, corrections, additions, deletions, information and/or instructions in connection with the Bid Opportunity, and be governed accordingly. Failure to acknowledge receipt of this Addendum in Paragraph 10 of Form A: Bid may render your Bid non-responsive.

PART E – SPECIFICATIONS

- Revise: E3.3 (a) to read: The wading pool and surrounding decks are constructed of 150 mm thick cast-in-place concrete with steel rebar reinforcing and which has a water depth of no more than 60 cm (23.62 inches). The typical wading pool is 15.24 meter (50 feet) in diameter and consists of a minimum width of 1.3 meter (4.2 feet) of unobstructed, hard surface deck surrounding the pool basin. The perimeter concrete curb has a depth of 150 mm (6 inches).
- Add: E3.5.1 (e) Installation of waterslides to also include all mechanical equipment and waterlines required to deliver water supply for slides.