



260-2010 ADDENDUM 1

SUPPLY AND DELIVERY OF TREE TRIMMING AERIAL DEVICE VEHICLES

URGENT

**PLEASE FORWARD THIS DOCUMENT TO
WHOEVER IS IN POSSESSION OF THE BID
OPPORTUNITY**

ISSUED: July 19, 2010
BY: B. Dupuis Smith
TELEPHONE NO. (204) 986-2492

**THIS ADDENDUM SHALL BE INCORPORATED
INTO THE BID OPPORTUNITY AND SHALL
FORM A PART OF THE CONTRACT
DOCUMENTS**

Template Version: A20070419

Please note the following and attached changes, corrections, additions, deletions, information and/or instructions in connection with the Bid Opportunity, and be governed accordingly. Failure to acknowledge receipt of this Addendum in Paragraph 8 of Form A: Bid may render your Bid non-responsive.

PART A – BID SUBMISSION

Replace: 260-2010 Bid Submission with 260-2010 Addendum 1 – Bid Submission. The following is a summary of changes incorporated in the replacement Bid Submission:

FORM N: DETAILED SPECIFICATIONS

- Revise: 7.13 of Detailed Specifications 10022 (Page 6) to read: Aerial device shall be certifiable below 46 KVAC. A factory document to certify that the equipment is designed to withstand 100 KVAC (wet and dry) during testing is to be supplied upon delivery of the aerial device. The leakage during the test shall not exceed 1.5 micro amps per KV/ft.
- Revise: 10.4 of Detailed Specifications 10022 (Page 8) to read: Height of sides – 1.6 m (63 in.) approx., state.
- Revise: 17.8 of Detailed Specifications 10022 (Page 15) to read: Interior of chipper body – finished with coal tar epoxy or equivalent.
- Revise: 15.8 of Detailed Specifications 10024 (Page 34) to read: Automatic greasing system – complete cab & chassis vehicle shall be supplied with a Groeneveld/CPL Systems Inc. automatic greasing system including approx. twenty-six (26) points on cab & chassis. The greasing system shall be equipped with an automatic low level shut-off and an in-cab red light indicator.