



342-2010 ADDENDUM 1

ATTACHE PARK PLAYGROUND RENOVATION

URGENT

**PLEASE FORWARD THIS DOCUMENT TO
WHOEVER IS IN POSSESSION OF THE BID
OPPORTUNITY**

ISSUED: May 6, 2010
BY: Dean Spearman
TELEPHONE NO. (204) 261-4137

**THIS ADDENDUM SHALL BE INCORPORATED
INTO THE BID OPPORTUNITY AND SHALL
FORM A PART OF THE CONTRACT
DOCUMENTS**

Template Version: A20070419

Please note the following and attached changes, corrections, additions, deletions, information and/or instructions in connection with the Bid Opportunity, and be governed accordingly. Failure to acknowledge receipt of this Addendum in Paragraph 8 of Form A: Bid may render your Bid non-responsive.

PART D – SUPPLEMENTAL CONDITIONS

- Revise: E15.1 to read: New Swings shall be 8' high, two bay, 4 place w 90 mm (3.5") O.D. 7 gauge OR 2 3/8" O.D. 5 gauge, RS40 galvanized steel pipe top beam and 60mm (2 3/8") 10 gauge legs all RS 40-galvanized with powder coated end fittings and two slash proof rubber enclosed infant seats, and two belt slash proof belt seats c.w. heavy duty 4/1 straight link galvanized steel chain, double clevis and bolt links or approved substitute in accordance with B6.
- Revise: E15.3 to read: Yoke clamps shall be either one piece construction and fabricated from 8 guage RS40 Galvanized steel or two piece, compression clamping cast aluminum or galvanized metal with baked on polyester powdercoating. They shall be complete with tamper proof hardware. Swings shall be attached to top beam with anti-wrap hardware.