



## 957-2010 ADDENDUM 1

### SUPPLY, FABRICATION, AND DELIVERY OF BEARINGS - OSBORNE STREET BRIDGE

#### **URGENT**

**PLEASE FORWARD THIS DOCUMENT TO  
WHOEVER IS IN POSSESSION OF THE BID  
OPPORTUNITY**

ISSUED: January 7, 2011  
BY: Vaibhav Banthia  
TELEPHONE NO. (204) 954-6800

**THIS ADDENDUM SHALL BE INCORPORATED  
INTO THE BID OPPORTUNITY AND SHALL  
FORM A PART OF THE CONTRACT  
DOCUMENTS**

Template Version: A20070419

---

**Please note the following and attached changes, corrections, additions, deletions, information and/or instructions in connection with the Bid Opportunity, and be governed accordingly. Failure to acknowledge receipt of this Addendum in Paragraph 9 of Form A: Bid may render your Bid non-responsive.**

---

#### **PART E – SPECIFICATIONS**

- Revise: E4.4.1 (d) to read: Elastomer shall be natural rubber, low temperature grade 4 or 5 with a 60 durometer shore A hardness.
- Revise: E4.4.2 (b) to read: The stainless steel sliding surface interface sheet shall conform to ASTM A240/A240M and continuously welded to the top plate. The roughness of the contact surface shall be measured in accordance with CSA B95 and shall not be greater than 0.25  $\mu\text{m}$  arithmetic average.
- Revise: E5.4.1 (c) (ii) to read: Roughness of the contact surface shall be no greater than 0.25  $\mu\text{m}$  arithmetic average.

#### **DRAWINGS**

- Revise: B109-11-002 Drawing Bearing Notes (8) to read:

Stainless steel mating surface shall conform to ASTM Standard A240 and shall have a minimum thickness of 3 mm. The roughness of the contact surface shall be no greater than 0.25 micrometers arithmetic average for plane surfaces