

**Part 1 General**

**1.1 REFERENCES**

- .1 NEMA 250-2003, Enclosures for Electrical Equipment (1000 Volts Maximum).
- .2 Canadian Standards Association (CSA International).
  - .1 CSA-C22.1-2009, Canadian Electrical Code, Part 1, Safety Standard for Electrical Installations.

**1.2 SUBMITTALS**

- .1 Submit product data in accordance with Section 01 33 00 – Submittal Procedures.

**Part 2 Products**

**2.1 GENERAL**

- .1 Control devices of each category to be of same type and manufacturer.
- .2 External trim materials to be corrosion resistant.
- .3 Operating conditions: -40 – 55 degrees C with 5 - 95% RH (non-condensing) unless otherwise specified.

**2.2 PUSHBUTTONS – PUSH-PULL/TWIST TO RELEASE**

- .1 Supply and install two-position maintained emergency stop operator stations for P-F1 and P-F2, per drawings 1-0157L-E0007 and 1-0157L-E0009.
- .2 Requirements:
  - .1 Ingress Protection: NEMA 4X
  - .2 Contact Life: 1,000,000 cycles
  - .3 Mechanical Life: 250,000 cycles
  - .4 Contact Rating: 10 A
  - .5 Contact Configuration: As shown on the drawings
  - .6 Illumination: Not required unless otherwise indicated.
  - .7 Acceptable for hazardous Class I, Zone 2 location.
- .3 Acceptable Products:
  - .1 Allen-Bradley 800R/H series as shown on the drawings or approved equal in accordance with B6.

**2.3 SELECTOR SWITCHES – 3 POSITION MAINTAINED**

- .1 Supply and install a three-position maintained selector switch remote operator station for SF-F1, per drawing 1-0157L-E0011.

- .2 Requirements:
  - .1 Ingress Protection: NEMA 4X
  - .2 Contact Life: 1,000,000 cycles
  - .3 Mechanical Life: 250,000 cycles
  - .4 Contact Rating: 10 A
  - .5 Contact Configuration: As shown on the drawings
  - .6 Illumination: Not required.
- .3 Acceptable Products:
  - .1 Allen-Bradley 800H series or approved equal in accordance with B6.

### **Part 3 Execution**

#### **3.1 INSTALLATION**

- .1 Install field control devices in accordance with manufacturers recommended methods, procedures and instructions.
- .2 Readily accessible to allow for unhindered operation and servicing.
- .3 Wall installation:
  - .1 Located as shown on the drawings.
  - .2 Securely mounted.

#### **3.2 IDENTIFICATION**

- .1 Identify field devices with lamacoids. Install in a conspicuous location.

**END OF SECTION**

**Part 1 General**

**1.1 REFERENCES**

- .1 NEMA 250-2003, Enclosures for Electrical Equipment (1000 Volts Maximum).
- .2 Canadian Standards Association (CSA International).
  - .1 CSA-C22.1-2009, Canadian Electrical Code, Part 1, Safety Standard for Electrical Installations.

**1.2 SUBMITTALS**

- .1 Submit shop drawings and manufacturer's installation instructions in accordance with Section 01 33 00 – Submittal Procedures.
- .2 Manufacturer's Instructions:
  - .1 Include manufacturer's installation instructions for specified equipment and devices in O&M Manuals.

**Part 2 Products**

**2.1 GENERAL**

- .1 Control devices of each category to be of same type and manufacturer.
- .2 External trim materials to be corrosion resistant.
- .3 Operating conditions: 0 – 35 degrees C with 5 - 95% RH (non-condensing) unless otherwise specified.
- .4 Account for hysteresis, relaxation time, maximum and minimum limits in applications of sensors and controls.

**2.2 ROOM TEMPERATURE SWITCHES**

- .1 Requirements:
  - .1 Switch: Dual (high temperature and low temperature)
  - .2 Manually adjustable.
  - .3 Range: -10 – 50 degrees C
  - .4 Mounting: Wall
  - .5 Protection: NEMA 4 or IP65
  - .6 Output Signal: Independent SPDT circuits, rated at 5 A @ 120 VAC
  - .7 Accuracy: < 1 degrees C over range of 0 to 70 degrees C.
  - .8 Approvals: CSA / cUL
  - .9 Acceptable Products:
    - .1 United Electric B402-120
    - .2 Or approved equal in accordance with B6.

**Part 3 Execution**

**3.1 INSTALLATION**

- .1 Install equipment, components so that manufacturer's and CSA labels are visible and legible after commissioning is complete.
- .2 Install field control devices in accordance with manufacturers recommended methods, procedures and instructions.
- .3 Support field-mounted panels, transmitters and sensors on pipe stands or channel brackets.
- .4 Electrical:
  - .1 Complete installation in accordance with Section 26 05 01 - Common Work Results - Electrical.
  - .2 Install communication wiring in conduit or utilizing ACIC cabling if shown on the drawings.
    - .1 Provide complete conduit /cable system to link instrumentation and the control panel(s).
    - .2 Conduit sizes to suit wiring requirements and to allow for future expansion capabilities specified for systems.
    - .3 Maximum conduit fill not to exceed 40%.
    - .4 Design drawings do not show conduit layout.

**3.2 TEMPERATURE SENSORS**

- .1 Stabilize to ensure minimum field adjustments or calibrations.
- .2 Readily accessible and adaptable to each type of application to allow for quick easy replacement and servicing without special tools or skills.
- .3 Duct installations:
  - .1 Do not mount in dead air space.
  - .2 Locate within sensor vibration and velocity limits.
  - .3 Securely mount extended surface sensor used to sense average temperature.
  - .4 Thermally isolate elements from brackets and supports to respond to air temperature only.
  - .5 Support sensor element separately from coils, filter racks.

**3.3 IDENTIFICATION**

- .1 Identify field devices with lamacoids. Install in a conspicuous location.

**END OF SECTION**

**Part 1            General**

**1.1                SUMMARY**

- .1    Section Includes:
  - .1        Process Control Devices including damper actuators.

**1.2                REFERENCES**

- .1    Association (NEMA).
  - .1        NEMA 250-2003, Enclosures for Electrical Equipment (1000 Volts Maximum).
- .2    Canadian Standards Association (CSA International).
  - .1        CSA-C22.1-2009, Canadian Electrical Code, Part 1, Safety Standard for Electrical Installations.

**1.3                SUBMITTALS**

- .1    Submit shop drawings and manufacturer's installation instructions in accordance with Section 01 33 00 – Submittal Procedures.
- .2    Manufacturer's Instructions:
  - .1        Include manufacturer's installation instructions for specified equipment and devices in O&M Manuals.

**Part 2            Products**

**2.1                GENERAL**

- .1    Control devices of each category to be of same type and manufacturer.
- .2    External trim materials to be corrosion resistant. Internal parts to be assembled in watertight assembly.
- .3    Operating conditions: 0 – 32 degrees C with 5 - 95% RH (non-condensing) unless otherwise specified.
- .4    Terminations: use standard conduit box with slot screwdriver compression connector block unless otherwise specified.
- .5    Transmitters and sensors to be unaffected by external transmitters including walkie talkies.
- .6    Account for hysteresis, relaxation time, maximum and minimum limits in applications of sensors and controls.

## **2.2 ELECTRONIC ON-OFF DAMPER ACTUATORS**

- .1 Requirements:
  - .1 Direct mount on-off type.
  - .2 Spring return type for "fail-safe" in Normally Open or Normally Closed position as indicated.
  - .3 Torque: 4 Nm (35 lb-in) minimum.
  - .4 Damper actuator to drive damper from full open to full closed in less than 90 seconds.
  - .5 Spring return to drive damper from full open to full closed in less than 60 seconds at normal room temperature.
  - .6 Angle of Rotation: 90° minimum, adjustable with mechanical stops.
  - .7 Direction of Rotation: Configurable via switch mounted on the actuator.
  - .8 Shaft Diameter: 8.0mm to 16.0mm (3/8" to 1/2").
  - .9 Electrical Connection: 0.9 meter (3 ft), 18 AWG, plenum rated cable.
  - .10 Overload protection: Required.
  - .11 Auxiliary Switches: One SPDT, adjustable operation between 0 and 95°.
  - .12 Power requirements: 7.5 VA maximum at 120 VAC, 60Hz.
  - .13 Operating Temperature: -30 °C to 50 °C.
  - .14 Housing: NEMA 2 or IP54 or better.
  - .15 CSA listing or equivalent.
  - .16 Acceptable Products: Belimo LF120-S or approved equal in accordance with B6

## **Part 3 Execution**

### **3.1 INSTALLATION**

- .1 Install equipment, components so that manufacturer's and CSA labels are visible and legible after commissioning is complete.
- .2 Install field control devices in accordance with manufacturers recommended methods, procedures and instructions.
- .3 Support field-mounted panels, transmitters and sensors on pipe stands or channel brackets.
- .4 Electrical:
  - .1 Complete installation in accordance with Section 26 05 01 - Common Work Results - Electrical.
  - .2 Install communication wiring in conduit or utilizing ACIC cabling.
    - .1 Provide complete conduit /cable system to link instrumentation and the control panel(s).
    - .2 Conduit sizes to suit wiring requirements and to allow for future expansion capabilities specified for systems.
    - .3 Maximum conduit fill not to exceed 40%.
    - .4 Design drawings do not show conduit layout.

.5 Terminate devices with leads in junction boxes with terminals.

.1 Wire nuts are not permitted.

.2 Protect leads in flexible conduit.

### **3.2 IDENTIFICATION**

.1 Identify devices with lamacoids. Mount in a conspicuous location.

### **3.3 TESTING AND COMMISSIONING**

.1 Calibrate and test control devices for accuracy and performance.

**END OF SECTION**