CIRCUIT AND RACEWAY GENERAL CIRCUIT CONDUCTOR AND CONDUIT IDENTIFICATION POWER CIRCUIT CALLOUTS POWER CABLE CIRCUIT CALLOUTS DATA / COMMUNICATION [T2] [1 (2 PAIRS), TELEPHONE] [1/2"FLEX, 2#12,#12G] [1"C,2#6, 1#8G] [3/4°C,1 (3C#12,1#12G) TYPE 2] [D2] [1 (2 PAIRS), CAT6] [P28] [PC2] [3/4"C,2#12,1#12G] [1"C,3#6, 1#8G] [3/4"C,1 (3C#10,1#10G) TYPE 2] [D3] [1 (1 PAIR), BELDEN9841] [3/4"C,3#12,1#12G] [P28a] [1"C,4#6, 1#8G] [PC3] [1"C,1 (3C#8,1#10G) TYPE 2] [P29] [1 1/4"C,2 (3C#12,1#12G) TYPE 2] [D4] [1 (3 PAIRS), BELDEN638AFS] [3/4"C,4#12,1#12G] [PC4] [1"C,3#6, 2#14,1#8G] [1 1/2"C,2 (3C#10,1#10G) TYPE 2]|[D5] [1 (1 PAIR), BELDEN87760] [3/4"C,5#12,1#12G] [P30] [1"C,3#6, 3#14,1#8G] [P31] [3/4"C,6#12,1#12G] [1"C,3#6, 4#14,1#8G] [PC1A] [3/4"C,1 (2C#12,1#12G) TYPE 2] [3/4"C,1 (2C#10,1#10G) TYPE 2] [P32] [1"C,3#6, 5#14,1#8G] [3/4"C,7#12,1#12G] [PC2A] [P8] [P33] [3/4"C,8#12,1#12G] [1"C,3#4,1#8G] [P9] [3/4°C,3#12,2#14,1#12G] [P34] [1 1/4"C,3#4,3#14,1#8G] [P35] [P10] [3/4"C,3#12,3#14,1#12G] [1 1/4"C,3#4,5#14,1#8G] [P36] [3/4"C,3#12,4#14,1#12G] [1 1/4"C,3#3, 1#6G] [P11] [P37] [3/4"C,3#12,5#14,1#12G] [P12] [1 1/4"C,3#3, 3#14,1#6G] EMPTY CONDUIT [P13] [P38] [3/4"C,3#12,6#14,1#12G] [1 1/4"C,3#2, 1#6G] [3/4"C, WITH PULL STRING] [P39] [3/4"C,3#12,7#14,1#12G] [1 1/4"C,3#1, 1#6G] [P14] [EC-2][1"C, WITH PULL STRING] [P39a] [1 1/2"C,4#1, 1#6G] [P15] [3/4"C,2#10,1#10G] [EC-3][1 1/4"C, WITH PULL STRING] [1 1/2"C,3#1, 3#14,1#6G] [P16] [P40] [3/4"C,3#10,1#10G] [EC-4] [1 1/2"C, WITH PULL STRING] [P41] [P17] [3/4"C,3#10,2#14,1#10G] [1 1/2"C,3#2/0, 1#6G] [EC-5] [2"C, WITH PULL STRING] [2"C,4#2/0, 1#6G] [3/4"C,3#10,3#14,1#10G] [P18] [P41a] [EC-6] [3"C, WITH PULL STRING] [3/4"C,3#10,4#14,1#10G] [P42] [2"C,3#3/0, 1#4G] [P19] [EC-7] [4"C, WITH PULL STRING] [P20] [3/4"C,3#10,5#14,1#10G] [P43] [2"C,3#4/0, 1#4G] [EC-8] [5"C, WITH PULL STRING] [P21] [1"C,2#8,1#10G] [P300] [2 1/2"C, 3#300 kcmil, 1#3G] [1"C,3#8,1#10G] [P22] [P350] [3 1/2°C, 3#350 kcmil, 1#4G[P23] [1"C,3#8,2#14,1#10G] [P500] [3"C, 3#500 kcmil, 1#3G] [P24] [1"C,3#8,3#14,1#10G] [P750] [4"c, 3#750 kcmil, 1#2G][P25] [1"C,3#8,4#14,1#10G] [P26] [1"C,3#8,5#14,1#10G] ANALOG CIRCUIT CALLOUTS CONTROL CIRCUIT CALLOUTS CONTROL CABLE CIRCUIT CALLOUTS [CC5] [3/4°C,1 TYPE 3] [3/4°C,1-5C TYPE 1] [3/4°C,MSC] [1"C,2 TYPE 3] [CC7] [3/4"C,1-7C TYPE 1][A2] [C2] [3/4"C,2#14,1#14G] [CC9] [A3] [1"C,3 TYPE 3] [1"C,1-9C TYPE 1] [3/4"C,3#14,1#14G] [CC12] [A4] [1"C,4 TYPE 3] [1"C,1-12C TYPE 1] [C4] [3/4"C,4#14,1#14G] [CC19] $[1 \ 1/2$ °C, 1-19C TYPE 1] $[1 \ 1/4$ "C,5 TYPE 3] [C5] [3/4"C,5#14,1#14G] [CC25] $[1 \ 1/4$ "C,6 TYPE 3] [1 1/2"C,1-25C TYPE 1] [C6] [3/4"C,6#14,1#14G] [CC37] $[1 \ 1/2$ °C,7 TYPE 3] $[2^{\circ}C,1-37C \text{ TYPE } 1]$ [C7] [3/4"C,7#14,1#14G] [8A] $[1 \ 1/2$ °C,8 TYPE 3] [CCC1] [1-7C #12 TYPE 1] [C8] [3/4"C,8#14,1#14G] $[1 \ 1/2$ °C,9 TYPE 3] [C9] [3/4"C,9#14,1#14G] [A10] [2"C,10 TYPE 3] [C10] [3/4"C,10#14,1#14G] [A11] [2"C,11 TYPE 3] [C11] [3/4"C,11#14,1#14G] [A12] [2"C,12 TYPE 3] [C12] [3/4"C,12#14,1#14G] [A13] [2"C,13 TYPE 3] [C13] [3/4"C,13#14,1#14G] [A14] [2"C,14 TYPE 3] [C14] [3/4"C,14#14,1#14G] [A15] $[3/4^{\circ}C,1]$ TYPE 4 [C15] [3/4"C,15#14,1#14G] [3/4"C,2 TYPE 4] [A16] [3/4"C,16#14,1#14G] [C16] [1"C,3 TYPE 4] [A17] [3/4"C,17#14,1#14G] [1 1/4"C,4 TYPE 4] [A18] [3/4"C,18#14,1#14G] [1 1/4"C,5 TYPE 4] [A19] [C19] [3/4"C,19#14,1#14G] [A20] [1 1/4"C,6 TYPE 4] [C20] [1"C,20#14,1#14G] [A21] $[1 \ 1/2\text{"C},7 \ \text{TYPE 4}]$ [1"C,21#14,1#14G] [A22] [1 1/2"C,8 TYPE 4] [C22] [1"C,22#14,1#14G] [A23] [2"C,9 TYPE 4] [C23] [1"C,23#14,1#14G] [A24] [3/4°C,1-4 pr. TYPE 5] [C24] [1"C,24#14,1#14G] [A25] [1"C,2-4 pr. TYPE 5] [C25] [1"C,25#14,1#14G] TYPE 1 - MULTI CONDUCTOR CONTROL CABLE TYPE 2 - MULTI CONDUCTOR POWER CABLE TYPE 3 - No. 16 TWISTED SHIELDED PAIR TYPE 4 - No. 16 TWISTED SHIELDED TRIAD INSTRUMENTATION CABLE TYPE 5 - No. 18 MULTI TWISTED, SHIELDED PAIR WITH A COMMON OVERALL SHIELD TYPE 6 - No. 18 MULTI TWISTED PAIRS WITH A COMMON OVERALL SHIELD USED FOR PROCESS CONTROL AND COMPUTER CABLING NOTES: FOR CABLE TYPES, SEE SPECIFICATIONS. 5. FOR METRIC CONDUIT SIZES USE THE FOLLOWING CONVERSION: $1 \frac{1}{4} = 35 \text{ mm}$ 1/2" = 16 mm 3/4" = 21 mm CONDUIT SIZES ARE BASED ON THE AREA OF RW90 CONDUCTORS. 1 1/2" = 41 mm 2" = 53 mm SIZING OF CONDUCTORS #2AWG AND SMALLER BASED ON AMPACITIES i'' = 27 mmAT 60 DEGREES C, SIZING OF CONDUCTORS #1AWG AND LARGER BASED ON AMPACITIES AT 75 DEGREES C. WHERE CIRCUITS ARE UNDERGROUND, DIRECT BURIED OR CONCRETE ENCASED, MINIMUM CONDUIT SIZE SHALL BE AS INDICATED ON THE DRAWINGS... CONSTRUCTION COMPLETION DATE: YYYY MM DD

ENGINEER'S SEAL THE CITY OF WINNIPEG CH2MHILL® WATER AND WASTE DEPARTMENT Winnipeg ORIGINAL ENGINEERING DIVISION SIGNED BY DESIGNED L.D. LLEWELLYN BRADY ROAD RESOURCE MANAGEMENT FACILITY SHEET **38** OF **45** 13/01/25 LEAF AND YARD WASTE AND CITY DRAWING NUMBER PILOT BIOSOLIDS COMPOSTING RELEASED FOR NTS | CONSTRUCTION 13/02/26 JBC ELECTRICAL - LEGEND ISSUED FOR ADDENDUM 2 HORIZONTAL CONSULTANT DRAWING NUMBER 1-0400B-E0001-003-01 13/01/25 JBC VERTICAL 0 ISSUED FOR CONSTRUCTION E - 003SHEET 3 OF 3 DATE 2013 01 25 BY FILE PATH: C:\pw_workdir\ch2mhill_wbg\jcortez1\d0198672\ FILE NAME: $E-003_438634.dwg$ PLOT DATE: 2013 02 26 BID OPPORTUNITY: 839-2012