


EXISTING CROSS SECTION

SCALE: 1:100



REVISIONS TO OPERATOR FLOOR

SCALE: 1:50

WORK ITEMS:

- CUT 1219x1524 OPENING AND INSTALL LAPEYRE STAIRS WITH SAFETY GATE.
- 2 CUT OPENING TO INSTALL THE 914x1524 BILCO J-AL FLOOR HATCH RATED AT 300 PSF
- 3) INSTALL GALVANIZED STEEL FLOOR BEAMS
- 4 INSTALL HANDRAILS. SEE D-13050 AND D-13051 FOR HANDRAIL PLAN AND DETAILS
- (5) REMOVE EXISTING LADDER. INSTALL 6 mm GALVANIZED STEEL LID ON ACCESS EXISTING OPENING
- 6 REMOVE EXISTING STYROFOAM INSULATION LOCATED AT FLOOR SOFFIT.

DESIGN FLOOR LOADS:


- DESIGN LOAD = 7.2 kPa
- LIFT LOAD SUPPORTED BY A MINIMUM OF TWO (2) POINTS = 22.3 kN (5000 lbs)

NOTE:

- SEE D-13048 AND D-13049 FOR STRUCTURAL STEEL BEAM CONNECTION DETAILS.
- SEE D-13052 AND D-13053 FOR HANDRAIL PLAN AND DETAILS.
- EXISTING STRUCTURE DIMENSIONS ARE APPROXIMATE ONLY. CONTRACTOR TO VERIFY PRIOR TO CONSTRUCTION.



B.M. ELEV. LOCATION APPROVED UNDERGROUND STRUCTURES COSTRUCTION COMPLETION DATE: YYYY MM DD SUPV. U/G STRUCTURES COMMITTEE DESIGNED CHECKED FAK FAK APPROVED BY LOCATION OF UNDERGROUND STRUCTURES AS SHOWN ARE BASED ON THE BEST INFORMATION AVAILABLE BUT NO QUARANTEE IS GIVEN THAT ALL EXISTING UTILITIES ARE SHOWN OR THAT THE GIVEN LOCATIONS ARE EXACT. CONFIRMATION OF EXISTENCE AND EXACT LOCATION OF ALL SERVICES MUST BE OBTAINED FROM THE INDIVIDUAL UTILITIES BEFORE PROCEEDING WITH CONSTRUCTION. DRAWN FAK BH RELEASED FOR CONSTRUCTION SCALE: HORIZONTAL AS NOTED VERTICAL DATE REVISIONS DATE 2012 10 15



Winnipeg

THE CITY OF WINNIPEG WATER AND WASTE DEPARTMENT ENGINEERING DIVISION

WILKES AVE RESERVOIR
WILKES RESERVOIR VALVE PIT B

ACCESS FLOOR MODIFICATIONS

SHEET 3 OF 7

D-13047

D OPPORTUNITY: XXX-20XX FILE PAT

CONSULTANT DRAWING NUMBER

FILE PATH: C:\2CURRENT_PROJECTS\Kemp Engineering\Wilkes Reservoir