

FORM A: BID
(See B8)

1. Contract Title SUPPLY AND DELIVERY OF A WALK-IN VAN

2. Bidder

Name of Bidder

Usual Business Name of Bidder as it appears on Invoice (if different from above)

Street

City

Province

Postal Code

(Mailing address if different)

Email Address of Bidder

Facsimile Number

Street or P.O. Box

City

Province

Postal Code

(Choose one)

GST Registration Number (if applicable)

The Bidder is:

a sole proprietor

a partnership

a corporation

carrying on business under the above name.

3. Contact Person

The Bidder hereby authorizes the following contact person to represent the Bidder for purposes of the Bid.

Contact Person

Title

Telephone Number

Facsimile Number

Email Address

4. Definitions

All capitalized terms used in the Contract shall have the meanings ascribed to them in the General Conditions and D3.

5. Offer The Bidder hereby offers to perform the Work in accordance with the Contract for the price(s), in Canadian funds, set out on Form B: Prices, appended hereto.

6. Commencement of the Work The Bidder agrees that no Work shall commence until he/she is in receipt of a notice of award from the Award Authority authorizing the commencement of the Work.

7. Contract The Bidder agrees that the Bid Opportunity in its entirety shall be deemed to be incorporated in and to form a part of this offer notwithstanding that not all parts thereof are necessarily attached to or accompany this Bid.

8. Addenda The Bidder certifies that the following addenda have been received and agrees that they shall be deemed to form a part of the Contract:

No.	Dated
_____	_____
_____	_____
_____	_____

9. Time This offer shall be open for acceptance, binding and irrevocable for a period of sixty (60) Calendar Days following the Submission Deadline.

10. Signatures The Bidder or the Bidder's authorized official or officials have signed this _____ day of _____, 20____.

Signature of Bidder or
Bidder's Authorized Official or Officials

(Print here name and official capacity of individual whose signature appears above)

(Print here name and official capacity of individual whose signature appears above)

FORM B: PRICES
(See B9)

SUPPLY AND DELIVERY OF A WALK-IN VAN

UNIT PRICES

ITEM NO.	DESCRIPTION	SPEC. REF.	UNIT	QUANTITY	UNIT PRICE
1.	Walk-in Van	13029	Each	1	

Name of Bidder

FORM N: DETAILED SPECIFICATIONS 13029

SUPPLY AND DELIVERY OF A WALK-IN VAN

1.0 DESCRIPTION OF EQUIPMENT-

- 1.1 These specifications describe a **Walk-in Van** and other equipment and features as specified herein.
- 1.2 The **Walk-in Van** shall be a new 2014 model year or newer.
- 1.3 The **Walk-in Van** and all other items/components shall be the manufacturer's latest model. The equipment shall be furnished complete and ready for operation. Any parts or accessories not specifically mentioned, but which are required to complete and place the equipment and associated attachments in successful operation shall be furnished as though specifically mentioned in these specifications. The equipment and associated attachments, and all parts thereof, shall conform in strength and quality of material and workmanship, to the best standards and engineering practice of the industry.

2.0 OTHER SPECIFICATIONS AND STANDARDS-

- 2.1 All applicable SAE standards form an integral part of these specifications and shall have precedence in any conflict concerning minimum acceptable standards.

- 2.2 The **Walk-in Van** shall comply with the applicable regulations:

Highway Traffic Act = <http://web2.gov.mb.ca/laws/statutes/ccsm/h060e.pHP>

Manitoba Motor Vehicle Act = <http://www.tc.gc.ca/acts-regulations/GENERAL/M/mvsa/menu.htm>

Canadian Motor Vehicle Safety Standards, CMVSS = <http://www.gnb.ca/0062/regs/83-163.htm>

Transport Canada = <http://laws.justice.gc.ca/en/notice/index.html?redirect=%2Fen%2FM-10.01%2F250448.html>

National Safety Mark, NSM = <http://www.tc.gc.ca/actsregulations/GENERAL/M/mvsa/regulations/mvsrg/001/mvsr3-5.html>

Manitoba/Winnipeg Safety and Health Act, Parts 12, 22 = <http://web2.gov.mb.ca/laws/statutes/ccsm/w210e.pHP> and <http://www.gov.mb.ca/labour/safety/>

Canadian Standards Association, CSA = <http://www.csa.ca/about/Default.asp?language=english>

Under Writers of Canada, U/L = <http://www.ulc.ca/>

Society of Automotive Engineers, SAE = http://en.wikipedia.org/wiki/Society_of_Automotive_Engineers

- 2.3 It will be the responsibility of the Bidder to inform the City of any deficiencies in these specifications, for under this Contract the Contractor shall be held responsible for the design, performance, reliability and satisfactory operational function of the units.

3.0 PREFORMANCE-

- 3.1 Shall be capable of consistent top performance for hauling and transporting various Winnipeg Transit related equipment during the climatic conditions which are normal to the City of Winnipeg.

4.0 SERVICE FACILITY-

- 4.1 For the purpose of warranty repairs, the Bidder shall have an authorized service facility located within 10 km of the boundaries of the City of Winnipeg. The facility, or a portion thereof, shall be dedicated to the service and maintenance of the type equipment being offered. Bidders shall provide a description of the service facility including, but not limited to, number of qualified service staff, years of service experience, and general service capabilities within three (3) Business Days upon request of the Contract Administrator.

5.0 REFERENCES-

- 5.1 Provide five (5) Canadian references where this equipment is used in a working environment where climatic conditions are similar to the City of Winnipeg

6.0 INSTRUCTIONS FOR COMPLETION OF SPECIFICATIONS-

- 6.1 Each bid will be evaluated based on adherence to all terms, conditions and requirements outlined in the Bid Opportunity package.
- 6.2 All items in these specifications must be answered indicating compliance or non-compliance. BIDDERS SHALL STATE "YES" FOR COMPLIANCE OR STATE DEVIATION, or give reply where requested to do so. Deviations shall be clearly stated and fully detailed. Alternatives will be considered subject to evaluation.
- 6.3 EACH BIDDER IS REQUIRED TO FILL IN EVERY BLANK. FAILURE TO DO SO MAY BE USED AS A BASIS FOR REJECTION OF BID

7.0 PERFORMANCE RELIABILITY-

- 7.1 The responsibility for the design of the walk-in van and associated, its performance and reliability shall rest upon the Contractor.
- 7.2 The term "repeated failures" as used herein is defined to mean that the same component, subassembly, or assembly develops repeated defects, breakdowns and/or malfunctions rendering the vehicle inoperative, or requiring repeated shop correction, service and/or replacement during the warranty period applicable for said component, subassembly, or assembly. Minor items or ordinary service adjustments are not included, or considered under the scope of "repeated failures", as well as other factors, such as operational damage due to accidents, misuse or lack of proper maintenance, service and lubrication attention by not following the manufacturer's preventative maintenance schedule.
- 7.3 Where the walk-in van and associated develops "repeated failures" in service, the Contractor shall make any necessary engineering changes, repairs, alterations or modifications in order to guarantee reliability of performance.
- 7.4 The equipment shall be capable of consistent top performance in City of Winnipeg Environment. Note: The City of Winnipeg has four seasons with ambient temperatures ranging from approximately 90°F (32°C) to -40°F (-40°C)

8.0 FUEL-

- 8.1 Where applicable, all equipment must be fully fuelled upon delivery (no exceptions).

9.0 QUALIFICATIONS OF MANUFACTURER & CONTRACTOR-

- 9.1 The manufacturer of the walk-in van and associated shall have demonstrated experience manufacturing walk-in vans and associated.
- 9.2 The manufacturer shall have in effect a documented quality control program ensuring that the quality of materials and workmanship, including welding, conforms to the best standards and engineering practice of the industry.
- 9.3 The Contractor shall have demonstrated experience servicing, repairing and maintaining walk-in vans and associated of the type being offered.

10.0 NATIONAL SAFETY MARK- (IF APPLICABLE)

- 10.1 In Canada, modification to new vehicles can only be done at facilities that are recognized by Transport Canada. All of these facilities must have a National Safety Mark from Transport Canada. Transport Canada National Safety Mark is a label that indicates that the modifications are compliant with all current Canadian Motor Vehicle Safety Standards (CMVSS)

STATE (NSM) #- _____

11.0 MANITOBA SAFETY INSPECTION- (IF APPLICABLE)

- 11.1 The vehicles shall be complete with a current Manitoba Safety Sticker affixed to the driver's side vent window.

12.0 STRIPPED CHASSIS

- 12.1 GVWR - 26,000 lbs. _____
- 12.1.1 Front GAWR - 8000 lbs. _____
- 12.1.2 Rear GAWR - 18,000 lbs. _____
- 12.2 Wheelbase - 178 in.. _____
- 12.3 Engine - Cummins ISB 6.7-240 diesel, 240 hp, 560 lb-ft torque. _____
- 12.4 Engine shut-down - low oil pressure / high water temperature. _____
- 12.5 Block heater - 1000 watt, with covered, recess mounted male plug. _____
- 12.6 Coolant - Extended Life coolant, antifreeze to -35°C. _____
- 12.7 Coolant hoses - silicone type, Gates Blue Stripe or Premium type hoses. _____
- 12.8 Alternator - Leece Neville, 200 Amp. _____
- 12.9 Batteries - three (3) 600 CCA batteries, 1800 CCA total, easily accessible, state mounting location. _____
- 12.10 Exhaust - horizontal exhaust. _____
- 12.11 Transmission - Allison automatic, 2200 RDS with park pawl and PTO provision. _____
- 12.12 Front axle and suspension - 8000 lbs. capacity. _____

- 12.13 Rear axle and suspension - 18,000 lbs. capacity with air-ride suspension, manual dump switch and auto fill override valve. _____
- 12.13.1 Rear suspension stabilizer - rear swaybar. _____
- 12.13.2 Rear axle ratio – 4.30, **state** ratio. _____
- 12.14 Shock absorbers - heavy duty, front and rear. _____
- 12.15 Oil seals - required front and rear. _____
- 12.16 Front tires - 255/70R22.5, BSW, radial ply, all season or rib tread, load rating and width to match GVWR. **State** make, model, size and load rating. _____
-
- 12.16.1 Rear tires - 255/70R22.5, BSW, radial ply, on/off road grip tread, load rating and width to match GVWR. **State** make, model, size and load rating being bid _____
-
- 12.16.2 Front and rear rims - polished aluminium, rated for GVWR. _____
- 12.17 Brakes – hydraulic disk, ABS, power, with air supply. _____
- 12.17.1 Air drier – Haldex cartridge type. _____
- 12.17.2 Moisture ejector - Bendix DV-2, heated, required in wet tank. _____
- 12.17.3 Drain valves - manual, chain or cable operated, required on each tank. _____
- 12.17.4 Parking brake - dash mounted air operated parking brake knob. _____
- 12.18 Steering – power with tilt and telescopic wheel. _____
- 12.19 Fuel tank - rectangular steel or aluminium, 246L capacity, passenger's side fill. _____
- 12.20 Fuel filter - fuel filter shall be complete with heated fuel/water separator. _____
- 12.21 Front bumper - full width, chrome bumper, min. 10 in. height with integral tow hooks. _____
- 13.0 ACCESSORIES & GAUGES**
- 13.1 Starter control - ignition switch with integral start and accessory position. _____
- 13.2 Front heater/defroster - high output, 40,000 BTU. _____
- 13.3 Air conditioning - required. _____
- 13.4 12-Volt power point - two (2) required. _____
- 13.5 Radio - AM/FM CD with two (2) speakers, wired through ignition. _____

- 13.6 Bluetooth® technology - required for use with cellular phones, “hands-free” capable, voice command activated through vehicle’s radio circuit. _____
- 13.7 Horn - dual electric. _____
- 13.8 Warning flashers - required with switch mounted on steering column. _____
- 13.9 Circuit breakers - automatic self-reset circuit breakers. _____
- 13.10 Wipers/washers - intermittent with electric washers, wired through ignition, capable of providing clear field of vision for 95th percentile operator. _____
- 13.10.1 Wiper motors - dual, top-mounted, enclosed, accessible with a bolted cover. _____
- 13.11 Gauges:
- i) Fuel level. _____
 - ii) Engine coolant temperature. _____
 - iii) Engine oil pressure. _____
 - iv) Voltmeter. _____
 - v) Air restriction indicator - dash mounted or intake mounted. _____
 - vi) Tachometer. _____
 - vii) Engine hourmeter. _____
 - viii) Diesel exhaust fluid (DEF). _____
- 13.12 Window fans - two (2) auxiliary defroster fans with metal blade guards and individual switches, located for driver and passenger side of front windshield. Each fan to be complete with a switch, wired through ignition. _____
- 13.13 Drink holders - two (2) required with rubber inserts for adjustable drink sizes. _____
- 14.0 DIMENSIONS AND WEIGHTS**
- 14.1 Cargo length, interior (measured to bulkhead) - 16 ft., **state**. _____
- 14.2 Overall length - 310 in., **state**. _____
- 14.3 Overall height - 125 in., **state**. _____
- 14.4 Body width, exterior - 94 in., **state** outside body width. _____
- 14.5 Interior height - 85 in., **state**. _____
- 14.6 Floor height - 38 in., **state**. _____
- 14.7 Unit weight including chassis, van body, shelving etc. - **state**. _____

15.0 INTERFACES

15.1 All interfaces between aluminium and steel are to be separated by a minimum of $\frac{1}{16}$ in. thick rubber or neoprene sheet and shall be bolted through with stainless steel bolts and non-conductive bushings.

16.0 VAN BODY, EXTERIOR

16.1 Engine hood - aluminium or fibreglass, tilt type, **state** material.

16.2 Side view mirrors - dual stainless steel or black carbonate, power, heated, 6"x 16" with convex.

16.3 Back-up camera - required, complete with sound and in-cab monitor.

16.4 Driver's side door - sliding type with sliding window, **state** door and window dimensions.

16.5 Passenger side door - hinged sedan type with roll-down or sliding window, **state** door and window dimensions.

16.6 Door actuators, exterior – power locks for both front and rear doors with keyless entry, locking exterior handle and matching non-locking interior handle.

16.7 All exterior side and rear doors shall be keyed alike.

16.8 Keys and remote entry – the unit shall be equipped with four (4) sets of keys and four (4) remote entry (FOBS).

16.9 Walls - smooth aluminium construction panels, 0.100 in. thick on 12 in. centres. **State** construction method.

16.10 Roof - smooth aluminium stressed-skin, 0.040 in. thickness, 1-piece design.

16.10.1 Roof bows - hat type on 24 in. centres.

16.10.2 Roof vent - Fan-Tastic, model 4000 power vent with 3-speed reversible fan, installed in roof of cargo area, switch panel actuated.

16.11 Floor, cross sills - full width 2" x 2" x 0.125" hollow structural steel tubing or equivalent on 16 in. centres. **State** material.

16.11.1 Floor, long sills - structural C-channels or equivalent. **State** material.

16.12 Floor insulation - 2-3 in. of spray foam insulation on underside of floor.

16.13 Mudflaps - aluminium or no-name black rubber type with steel bar anti-sail brackets, installed behind rear tires.

16.14 Rear bumper - full width, heavy-duty step bumper, 12-14 in. deep, 10,000 lbs. towing capacity, c/w a grip strut step surface. Bumper shall be designed with a recess for a pintle hitch mount.

- 16.14.1 Bumper shall be bolted to chassis frame and to van body, reinforced as required. Mounting height shall provide a 18-20 in. step height from ground level. _____
- 16.14.2 Hitch reinforcement - "A" frame, bolted to chassis frame web. _____
- 16.14.3 Combination hitch - Buyers Products BH8-2000, secured with grade-8 fasteners. Mounting height to be determined at time of installation. _____
- 16.14.4 Hitch mount to be recessed such as to provide minimum intrusion into access area. _____
- 16.14.5 Lunette eyes for trailer safety chains - two (2) required, one on each side of hitch, located so as not to intrude in step area. Each lunette eye shall be rated at full capacity of hitch, Buyers Products B56729 or equal. _____
- 16.15 Side exterior storage compartment 1 - 88"W x 54"H x 10"D compartment located on passenger side aft of bulkhead and ahead of rear wheels with a Gortite (or equivalent) roll-up door. Bottom edge of compartment shall be 36 in. from ground level. Compartment capacity shall be 1500 lbs. Compartment shall be c/w a rubber mat on floor, finished with Zolotone paint or equal. _____
- 16.16 Rear access door - located at the curbside rear of the vehicle beside rear, passenger-side door, 14"W x 36"H. Door to be double skin aluminium design, right-side stainless steel hinges, c/w a stainless steel lockable paddle handle. Bottom edge of access door shall be 1 in. higher than the top of the passenger side interior rear wheel well tub. The access door is to be centered between the curbside 85"H x 20"W rear door's outside frame edge and the curbside rear interior corner wall panel of the vehicle. _____

Note: The intent of the rear access door is to outfit the inside of the van with a future, City supplied and installed storage compartment.

17.0 REAR DOORS

- 17.1 Rear doors - two (2), hinged type, aluminium double skin, approx. 85" H x 20" W approx. complete with safety glass top and bottom. _____
- 17.2 Safety glass - one (1) per door, 20" H x 14" W each with appropriate safety markings. _____
- 17.3 Hinges - three (3) per door, heavy-duty, stainless steel. _____
- 17.4 Latch, right side door - locking exterior handle and matching non-locking interior handle. _____
- 17.5 Latches, left and right side doors - **state** details of door latches including, but not limited to, slam-action, rod actuation, slide bolts, striker plates, accessibility for servicing, etc. _____
- _____
- _____
- _____

17.6 Grab handles - two (2) required mounted vertically on interior of rear doors, located for ergonomic entry and egress. _____

17.7 Door stays - designed to hold rear doors in fully open position, "Grabber" U-style (Cast Products Inc.) or equivalent. _____

18.0 INTERIOR, GENERAL

18.1 Front seats - two (2) high back bucket type, cloth captain's chairs with flip-up arm rests, back height shall be 26 in., seat belts with shoulder restraints. _____

18.1.1 Seats shall be ergonomically positioned for proper seat travel, comfortable rear incline angles and sufficient hip and elbow room. _____

18.2 Side door actuators, interior - easily accessible from a normal seated position. _____

18.3 Interior side door arm rests - required with sufficient padding for driver and front passenger. _____

18.4 Grab handles, interior - supplied as required at front and rear doors for ergonomic entry and egress of vehicle. _____

18.5 Sun visors - required for driver and passenger. _____

18.6 Interior rear view mirror - 2"x 9" approx. _____

18.7 Walls and ceiling, cargo area - aluminium skin lined, securely fastened, removable for future City supplied and installed, aftermarket wiring. _____

18.8 Floor - ribbed extruded aluminium flooring. _____

18.9 Insulation - urethane spray-on foam, 1-2 in. thick in walls, ceiling and firewall, 2 in. thick in floor. Side and rear doors shall be insulated as much as practicable. _____

18.10 Bulkhead - 12 ga. aluminium with sufficient soundproofing, located directly behind driver's and passenger's seats. _____

18.10.1 Bulkhead shall be located to allow full seat travel for driver and passenger. _____

18.10.2 Bulkhead door - centre sliding door, latchable with min. 18 in. x 18 in. Lexan window. _____

18.10.3 Fire extinguisher - ABC type, 5 lb. c/w storage bracket. Mounting location to be determined at time of installation. _____

18.11 Flare kit - three (3) triangular reflectors, CVSA approved. _____

18.12 First aid kit - required, Provincial 1 approved kit, supplied loose. _____

19.0 AUXILIARY POWER UNIT

19.1 Rigmaster T2 - required for 6000 watts of power, 120 V electrical, heat and air conditioning, installed under floor, outside of frame rails on

driver's side. Exact location of APU, Cabin Controller and ducting to be discussed with the Successful Bidder at time of installation.

20.0 ELECTRICAL & LIGHTING

20.1 All vehicle lighting shall conform to C.M.V.S.S. and Manitoba Highway Traffic Act requirements.

20.2 Body mounted vehicle lighting shall be LED Truck-Lite components (except otherwise noted) and shall include the following:

20.2.1 Stop, turn and tail lamps - two (2) P/N 44302R lights with P/N 40700 mounting grommets, flush or recess mounted.

20.2.1.1 High mounted stop, turn and tail lamps - two (2) P/N 44302R lights with P/N 40700 mounting grommets, flush or recess mounted.

20.2.2 Back-up lights - P/N 44244, one (1) per side with 40700 mounting grommets.

20.2.3 Light cluster - three (3) only P/N 10250R with P/N 10700 mounting grommets.

20.2.4 Clearance lights - P/N 10250R and 10250Y with P/N 10700 mounting grommets.

20.2.5 License plate lamp - part # 704816.

20.2.6 Lighting harnesses - Truck-Lite 50 Series Harness system, properly routed and secured.

20.2.7 Junction box - P/N 50400, complete with necessary compression fittings, required for all vehicle lighting harness connections, located inside rear of truck frame.

20.3 All plug-in connectors shall be coated with Truck-Lite NYK Compound prior to assembly.

20.4 Trailer connector - 6-pole, Grote 82-1016, wired to code, installed in rear bumper.

20.5 Back-up alarm - Preco Model 240 or Truck-Lite 92900, 97 dB(A) rating, installed at the rear of the unit, located to be protected from damage.

20.6 Interior Lighting

i) Driver's area - two (2) Truck-Lite P/N 80250 interior dome lights w/switches, mounted directly above driver's and passenger's seats. Dome lights shall maintain continuous power even when the vehicle is turned-off. Activation shall also be through driver's, passenger's and rear door switches and through a main switch panel on the dash.

ii) Cargo area - three (3) Truck-Lite 80250 interior dome lights mounted above centre isle, evenly spaced. Activation shall also be through driver's, passenger's and rear door switches and through a main switch panel on the dash.

20.7 Door-open indicator - a red light indicator shall be installed, visible to the driver, to indicate door open or ajar for front doors, rear doors, and compartment doors.

20.8 All wiring for body manufacturer installed accessories and trailer plug shall be colour coded, loomed and properly secured.

20.8.1 All electrical connectors shall be crimped and soldered, then sealed using heat shrink tubing.

20.8.2 All joining of wires for the back-up alarm, warning lights, rear work-lights and trailer plug shall be soldered and sealed using heat shrink tubing (crimp on electrical connectors for joining wires are not acceptable).

20.8.3 Any holes required to run wires through shall be drilled (not punched), grommeted and sealed as necessary.

21.0 INSTALLATION

21.1 Mounting brackets shall be bolted to chassis frame using Grade-8 fasteners.

21.2 Any holes required in the chassis frame web must be drilled and reamed to fit bolts, no exceptions.

21.3 Welding or drilling on chassis frame flanges and welding on chassis frame web is not permitted.

21.4 Mounting of the van body shall be in accordance with the chassis manufacturer's guidelines for body mounting, including, but not limited to, guidelines for tire and suspension clearance and fuel filler installation.

21.5 Tire clearance - bumper pad clearance plus 3 in.

21.6 The van body shall be mounted as low as practicable and shall incorporate wheel wells.

21.7 All holes for latches etc. shall be neatly cut and de-burred.

21.8 All edges and corners shall be rounded to prevent accidental injury.

22.0 FINISH

22.1 The complete van body shall be properly cleaned, primed with a suitable primer, and finished as follows:

i) Exterior - entire unit (including roof) shall be painted white with two (2) coats of polyurethane enamel, Dupont Imron, Akzo Sikkens or Endura paint process.

ii) Interior - ceiling and walls shall be painted white with two (2) coats of polyurethane enamel, Dupont Imron, Akzo Sikkens or Endura paint process.

iii) Rear bumper - painted argent or grey with two (2) coats of

polyurethane enamel, Dupont Imron, Akzo Sikkens or Endura paint process or Powder Coated or Galvanized. **State.**

23.0 MANUALS

23.1 Operator's manuals – two (2) required for chassis, body, and APU.

23.2 Parts/Repair/Service – required, including preventative maintenance Schedules for life of unit, CDs or online manuals preferred.

24.0 WARRANTY

24.1 The warranty for the walk-in van shall cover the complete equipment and all parts thereof against any defects of workmanship, construction and materials for a period of **not less than 2-years**. Any article that has become defective during said warranty period and has not proven to have been caused by negligence on the part of the user shall be repaired or replaced at no cost to the City. The warranty shall be effective from the date the equipment is put into service by the City of Winnipeg.

24.1.1 A new two (2) year warranty period shall be provided for any article that is repaired or replaced under the terms of the "repeat failures" clause (Section **7.0 Performance Reliability**). The new warranty period shall be effective from the date of acceptance of the repaired or replaced article.

24.2 Additional warranties shall include the following:

- i) Basic vehicle - two (2) years, unlimited km.
 - ii) Batteries - one (1) year or 100 000 km.
 - iii) Drivetrain - two (2) years, unlimited km.
 - iv) Cab structure/corrosion - five (5) years, unlimited km.
 - v) Frame and crossmembers - five (5) years, unlimited km.
 - vi) Exterior cab and body paint - two (2) years or 100 000 km.
 - vii) Engine - four (4) years or 320 000 km including engine electronics and injectors.
 - viii) Towing coverage - four (4) years or 320 000 km.
 - ix) Transmission - five (5) years, unlimited km.
 - x) Axles, front and rear - two (2) years or 240 000 km.
 - xi) Exhaust system - four (4) years or 160 000 km.
-

25.0 LITERATURE AND DRAWINGS

25.1 Bidders shall submit current, descriptive, detailed literature of the equipment with their bid.

25.2 Drawings - the City will require detailed layout drawings of the interior and exterior of the walk-in van prior to the award of the Contract. Drawings must include accurate measurements and representations of the location and dimensions of major components, compartments, compartment doors, windows and mounting locations of equipment/accessories installed on the proposed vehicle. The Bidder shall provide the drawings within three (3) Business Days upon request of the Contract Administrator.

26.0 TRAINING

26.1 The Contractor shall be required to provide training (at the Contractor's expense) for the City of Winnipeg maintenance and operating personnel. The training shall be divided into two separate sessions, one for maintenance personnel and one for operating personnel. The training shall be conducted in separate or combined sessions for each group of personnel.

The duration of the sessions shall be as long as required for adequate familiarization and orientation of the equipment to the satisfaction of the Contract Administrator.

The training shall be conducted within two (2) calendar weeks from the date of delivery and shall be coordinated through the Contract Administrator.

The training shall be conducted in Winnipeg at a time and location designated by the Contract Administrator.

Pricing should be based on one (1) business day for maintenance personnel and one (1) business day for operating personnel.

Note: The first payment of the contract on the equipment will not be issued until successful completion of training has been conducted to the satisfaction of the Contract Administrator.

Training Aides:

a) On the type of equipment being offered, state if CD Rom training aides or on-line training are available-

What is the recommended minimum training duration for:

Primary unit:

For major attachments (if Applicable):

State what other training aids are available (videos, CDs).

For the primary unit:

For major attachments (if applicable):

Training Materials and applicable manuals or on-line training material information must be provided to the Operator Training Branch of Public Works at the earliest possible opportunity, no later than (4) weeks prior to delivery, when supplying vehicles, equipment and related attachments. Send these materials, preferably in both electronic format and hard copy (training videos are to be supplied on either CD or DVD) to:

Public Works Department, Human Resources Division
Equipment Operator Training Branch

102-1155 Pacific Avenue
Winnipeg, MB
R3E 3P1

Attn:
Leanne Guertin
Equipment Operator Training Consultant

Cell: 204-451-3793
Contact e-mail: lguertin@winnipeg.ca

27.0 DELIVERY

27.1 Delivery Point- The complete unit shall be serviced, ready for operation and delivered F.O.B. with the freight prepaid, including invoice and N.I.V.S. (if applicable) to the WFMA 195 Tecumseh Street, Winnipeg MB. _____

27.2 Delivery Time- Within forty (40) calendar weeks from the date of official notification of award of contract. Equipment shall be delivered between 8:00 am and 3:00 pm on Business Days. _____

27.3 Delivery Contact- The Contractor shall contact the Contract Administrator prior to delivery of the equipment. _____

27.4 P.D.I- A pre-delivery inspection shall be performed by the Contractor on the equipment. Proof upon inspection including completed check list. _____

FORM Q-SUSTAINABILITY QUESTIONNAIRE

Product Information

(Yes/No)

Product Sustainability: High Quality, Small Ecological Footprint

1. Have you employed environmentally innovative best practices and/or technologies in the goods you are supplying in this Bid Opportunity as compared to similar goods? If yes, please describe them below.

Describe:

2. Have you obtained 3rd party environmental certifications for any of the products that you are supplying in this Bid Opportunity?

Describe:

3. Have you performed a life cycle assessment of the goods you are supplying in this Bid Opportunity? If yes, please describe below.

Describe:

4. Are there any other environmentally innovative best practices and/or technologies in the goods you are supplying in this Bid Opportunity that we could have specified in this tender, but have not? If yes, please describe them below.

Describe:

Company Information

Energy and Climate: Reducing Energy Costs and Greenhouse Gas Emissions

1. Have you measured your corporate greenhouse gas emissions? If yes, please report your total annual greenhouse gas emissions reported in the most recent year measured?

Describe:

2. Have you set publicly available greenhouse gas reduction targets? If yes, what are those targets?

Describe:

Material Efficiency: Reducing Waste and Enhancing Quality

1. Do you measure the total amount of solid waste generated from the facilities that produce your product(s) for this Bid Opportunity? If yes, please report for the most recent year measured.

Describe:

2. Have you set publicly available solid waste reduction targets? If yes, what are those targets?

Describe:

3. Do you measure the total water use from facilities that produce your product(s) for this Bid Opportunity? If yes, please report for the most recent year measured.

Describe:

4. Have you set publicly available water use reduction targets? If yes, what are those targets?

Describe:

Natural Resources: Responsibly Sourced Raw Materials

1. Have you established publicly available sustainability purchasing guidelines for your direct suppliers that address issues such as environmental compliance, employment practices and product safety?

Describe:

Social Responsibility: Ensuring Responsible and Ethical Production

1. Do you have a process for managing social compliance at the manufacturing level?

Describe:

2. Do you work with your supply base to resolve issues found during social compliance evaluations and also document specific corrections and improvements?

Describe:

3. Do you invest in community development activities in the markets you source from and/or operate within? _____

Describe:
