



**THE CITY OF WINNIPEG**

# **BID OPPORTUNITY**

**BID OPPORTUNITY NO. 533-2015**

**CAMPION TOT LOT PLAYGROUND REDEVELOPMENT**

## TABLE OF CONTENTS

### PART A - BID SUBMISSION

Form A: Bid	1
Form B: Prices	3

### PART B - BIDDING PROCEDURES

B4. Contract Title	1
B5. Submission Deadline	1
B6. Site Investigation	1
B7. Enquiries	1
B8. Confidentiality	1
B9. Addenda	2
B10. Substitutes	2
B11. Bid Components	3
B12. Bid	4
B13. Prices	4
B14. Disclosure	5
B15. Qualification	5
B16. Design Drawings	6
B17. Component Descriptions	6
B18. Opening of Bids and Release of Information	6
B19. Irrevocable Bid	6
B20. Withdrawal of Bids	6
B21. Evaluation of Bids	7
B22. Award of Contract	8

### PART C - GENERAL CONDITIONS

C0. General Conditions	1
------------------------	---

### PART D - SUPPLEMENTAL CONDITIONS

#### General

D1. General Conditions	1
D2. Scope of Work	1
D3. Contract Administrator	1
D4. Contractor's Supervisor	1
D5. Ownership of Information, Confidentiality and Non Disclosure	1
D6. Notices	2

#### Submissions

D7. Authority to Carry on Business	2
D8. Safe Work Plan	2
D9. Insurance	3
D10. Performance Security	3
D11. Subcontractor List	3
D12. Detailed Work Schedule	4

#### Schedule of Work

D13. Commencement	4
D14. Substantial Performance	4
D15. Total Performance	5
D16. Liquidated Damages	5
D17. Scheduled Maintenance	5

#### Control of Work

D18. Job Meetings	5
D19. Prime Contractor – The Workplace Safety and Health Act (Manitoba)	6
D20. The Workplace Safety and Health Act (Manitoba) – Qualifications	6

**Measurement and Payment**

D21. Payment	6
--------------	---

**Warranty**

D22. Warranty	6
---------------	---

Form H1: Performance Bond	7
---------------------------	---

Form H2: Irrevocable Standby Letter of Credit	9
---	---

Form J: Subcontractor List	11
----------------------------	----

Form L: Detailed Work Schedule	12
--------------------------------	----

**PART E - SPECIFICATIONS**

**General**

E4. Applicable Specifications and Drawings	1
--	---

GENERAL	1
---------	---

E5. Existing Services and Utilities	1
-------------------------------------	---

E6. Access To Site	1
--------------------	---

E7. Permits, Notices, Licenses, Certificates, Laws and Rules	2
--	---

E8. Damage to Existing Structures, Trees and Property	2
---	---

E9. Pedestrian Safety And Traffic Management	3
--	---

E10. Protection Of The Survey Infrastructure	3
--	---

E11. Site Restoration	3
-----------------------	---

E12. Site Enclosures	3
----------------------	---

E13. Removals	4
---------------	---

E14. Excavation and Grading	4
-----------------------------	---

E15. Sub-Surface Drainage	6
---------------------------	---

E16. Protective Surfacing	8
---------------------------	---

E17. Poured in Place Concrete Edging	10
--------------------------------------	----

E18. Asphalt Path	11
-------------------	----

E19. Site Furniture	14
---------------------	----

E20. Log Stepping Posts	15
-------------------------	----

E21. Climbing Boulders	16
------------------------	----

E22. Post Fencing	17
-------------------	----

E23. Soil and Sod	18
-------------------	----

E24. Play Equipment	19
---------------------	----

E25. Swing Set	22
----------------	----

E26. Bowl Swing	23
-----------------	----

E27. Foundations	24
------------------	----

E28. Maintenance Kits	24
-----------------------	----

## **PART B - BIDDING PROCEDURES**

### **B4. CONTRACT TITLE**

B4.1 CAMPION TOT LOT PLAYGROUND REDEVELOPMENT

### **B5. SUBMISSION DEADLINE**

B5.1 The Submission Deadline is 4:00 p.m. Winnipeg time, July 6, 2015.

B5.2 Bids determined by the Manager of Materials to have been received later than the Submission Deadline will not be accepted and will be returned upon request.

B5.3 The Contract Administrator or the Manager of Materials may extend the Submission Deadline by issuing an addendum at any time prior to the time and date specified in B5.1.

### **B6. SITE INVESTIGATION**

B6.1 Further to C3.1, the Bidder may view the Site without making an appointment.

### **B7. ENQUIRIES**

B7.1 All enquiries shall be directed to the Contract Administrator identified in D3.1.

B7.2 If the Bidder finds errors, discrepancies or omissions in the Bid Opportunity, or is unsure of the meaning or intent of any provision therein, the Bidder shall notify the Contract Administrator of the error, discrepancy or omission, or request a clarification as to the meaning or intent of the provision at least five (5) Business Days prior to the Submission Deadline.

B7.3 Responses to enquiries which, in the sole judgment of the Contract Administrator, require a correction to or a clarification of the Bid Opportunity will be provided by the Contract Administrator to all Bidders by issuing an addendum.

B7.4 Responses to enquiries which, in the sole judgment of the Contract Administrator, do not require a correction to or a clarification of the Bid Opportunity will be provided by the Contract Administrator only to the Bidder who made the enquiry.

B7.5 The Bidder shall not be entitled to rely on any response or interpretation received pursuant to B7 unless that response or interpretation is provided by the Contract Administrator in writing.

### **B8. CONFIDENTIALITY**

B8.1 Information provided to a Bidder by the City or acquired by a Bidder by way of further enquiries or through investigation is confidential. Such information shall not be used or disclosed in any way without the prior written authorization of the Contract Administrator. The use and disclosure of the confidential information shall not apply to information which:

- (a) was known to the Bidder before receipt hereof; or
- (b) becomes publicly known other than through the Bidder; or
- (c) is disclosed pursuant to the requirements of a governmental authority or judicial order.

B8.2 The Bidder shall not make any statement of fact or opinion regarding any aspect of the Bid Opportunity to the media or any member of the public without the prior written authorization of the Contract Administrator.

## **B9. ADDENDA**

- B9.1 The Contract Administrator may, at any time prior to the Submission Deadline, issue addenda correcting errors, discrepancies or omissions in the Bid Opportunity, or clarifying the meaning or intent of any provision therein.
- B9.2 The Contract Administrator will issue each addendum at least two (2) Business Days prior to the Submission Deadline, or provide at least two (2) Business Days by extending the Submission Deadline.
- B9.2.1 Addenda will be available on the Bid Opportunities page at The City of Winnipeg, Corporate Finance, Materials Management Division website at <http://www.winnipeg.ca/matmgt/>
- B9.2.2 The Bidder is responsible for ensuring that he/she has received all addenda and is advised to check the Materials Management Division website for addenda regularly and shortly before the Submission Deadline, as may be amended by addendum.
- B9.2.3 The Bidder shall acknowledge receipt of each addendum in Paragraph 8 of Form A: Bid. Failure to acknowledge receipt of an addendum may render a Bid non-responsive.

## **B10. SUBSTITUTES**

- B10.1 The Work is based on the Plant, Materials and methods specified in the Bid Opportunity.
- B10.2 Substitutions shall not be allowed unless application has been made to and prior approval has been granted by the Contract Administrator in writing.
- B10.3 Requests for approval of a substitute will not be considered unless received in writing by the Contract Administrator at least five (5) Business Days prior to the Submission Deadline.
- B10.4 The Bidder shall ensure that any and all requests for approval of a substitute:
- (a) provide sufficient information and details to enable the Contract Administrator to determine the acceptability of the Plant, Material or method as either an approved equal or alternative;
  - (b) identify any and all changes required in the applicable Work, and all changes to any other Work, which would become necessary to accommodate the substitute;
  - (c) identify any anticipated cost or time savings that may be associated with the substitute;
  - (d) certify that, in the case of a request for approval as an approved equal, the substitute will fully perform the functions called for by the general design, be of equal or superior substance to that specified, is suited to the same use and capable of performing the same function as that specified and can be incorporated into the Work, strictly in accordance with the proposed work schedule and the dates specified in the Supplemental Conditions for Substantial Performance and Total Performance;
  - (e) certify that, in the case of a request for approval as an approved alternative, the substitute will adequately perform the functions called for by the general design, be similar in substance to that specified, is suited to the same use and capable of performing the same function as that specified and can be incorporated into the Work, strictly in accordance with the proposed work schedule and the dates specified in the Supplemental Conditions for Substantial Performance and Total Performance.
- B10.5 The Contract Administrator, after assessing the request for approval of a substitute, may in his/her sole discretion grant approval for the use of a substitute as an "approved equal" or as an "approved alternative", or may refuse to grant approval of the substitute.
- B10.6 The Contract Administrator will provide a response in writing, at least two (2) Business Days prior to the Submission Deadline, to the Bidder who requested approval of the substitute.

- B10.6.1 The Contract Administrator will issue an Addendum, disclosing the approved materials, equipment, methods and products to all potential Bidders. The Bidder requesting and obtaining the approval of a substitute shall be responsible for disseminating information regarding the approval to any person or persons he/she wishes to inform.
- B10.7 If the Contract Administrator approves a substitute as an “approved equal”, any Bidder may use the approved equal in place of the specified item.
- B10.8 If the Contract Administrator approves a substitute as an “approved alternative”, any Bidder bidding that approved alternative may base his/her Total Bid Price upon the specified item but may also indicate an alternative price based upon the approved alternative. Such alternatives will be evaluated in accordance with B21.
- B10.9 No later claim by the Contractor for an addition to the Total Bid Price because of any other changes in the Work necessitated by the use of an approved equal or an approved alternative will be considered.
- B10.10 Notwithstanding B10.2 to B10.9, and in accordance with B11.7, deviations inconsistent with the Bid Opportunity document shall be evaluated in accordance with B21.1(a).

## **B11. BID COMPONENTS**

- B11.1 The Bid shall consist of the following components:
- (a) Form A: Bid;
  - (b) Form B: Prices;
  - (c) Design Drawings as per B16, and;
  - (d) Component Descriptions as per B17.
- B11.2 Further to B11.1, the Bidder should include the written correspondence from the Contract Administrator approving a substitute in accordance with B10.
- B11.3 All components of the Bid shall be fully completed or provided, and submitted by the Bidder no later than the Submission Deadline, with all required entries made clearly and completely, to constitute a responsive Bid.
- B11.4 The Bid Submission may be submitted by mail, courier or personal delivery, or by facsimile transmission.
- B11.5 If the Bid Submission is submitted by mail, courier or personal delivery, it shall be enclosed and sealed in an envelope clearly marked with the Bid Opportunity number and the Bidder's name and address, and shall be submitted to:
- The City of Winnipeg  
Corporate Finance Department  
Materials Management Division  
185 King Street, Main Floor  
Winnipeg, MB R3B 1J1
- B11.5.1 Samples or other components of the Bid Submission which cannot reasonably be enclosed in the envelope may be packaged separately, but shall be clearly marked with the Bid Opportunity number, the Bidder's name and address, and an indication that the contents are part of the Bidder's Bid Submission.
- B11.6 Bidders are advised not to include any information/literature except as requested in accordance with B11.1.
- B11.7 Bidders are advised that inclusion of terms and conditions inconsistent with the Bid Opportunity document, including the General Conditions, will be evaluated in accordance with B21.1(a).

B11.8 If the Bid Submission is submitted by facsimile transmission, it shall be submitted to 204 949-1178.

B11.8.1 The Bidder is advised that the City cannot take responsibility for the availability of the facsimile machine at any time.

B11.8.2 Bids submitted by internet electronic mail (e-mail) will not be accepted.

## **B12. BID**

B12.1 The Bidder shall complete Form A: Bid, making all required entries.

B12.2 Paragraph 2 of Form A: Bid shall be completed in accordance with the following requirements:

- (a) if the Bidder is a sole proprietor carrying on business in his/her own name, his/her name shall be inserted;
- (b) if the Bidder is a partnership, the full name of the partnership shall be inserted;
- (c) if the Bidder is a corporation, the full name of the corporation shall be inserted;
- (d) if the Bidder is carrying on business under a name other than his/her own, the business name and the name of every partner or corporation who is the owner of such business name shall be inserted.

B12.2.1 If a Bid is submitted jointly by two or more persons, each and all such persons shall identify themselves in accordance with B12.2.

B12.3 In Paragraph 3 of Form A: Bid, the Bidder shall identify a contact person who is authorized to represent the Bidder for purposes of the Bid.

B12.4 Paragraph 10 of Form A: Bid shall be signed in accordance with the following requirements:

- (a) if the Bidder is a sole proprietor carrying on business in his/her own name, it shall be signed by the Bidder;
- (b) if the Bidder is a partnership, it shall be signed by the partner or partners who have authority to sign for the partnership;
- (c) if the Bidder is a corporation, it shall be signed by its duly authorized officer or officers;
- (d) if the Bidder is carrying on business under a name other than his/her own, it shall be signed by the registered owner of the business name, or by the registered owner's authorized officials if the owner is a partnership or a corporation.

B12.4.1 The name and official capacity of all individuals signing Form A: Bid should be printed below such signatures.

B12.4.2 All signatures shall be original.

B12.5 If a Bid is submitted jointly by two or more persons, the word "Bidder" shall mean each and all such persons, and the undertakings, covenants and obligations of such joint Bidders in the Bid and the Contract, when awarded, shall be both joint and several.

## **B13. PRICES**

B13.1 The Bidder shall state a price in Canadian funds for each item of the Work identified on Form B: Prices.

B13.2 The quantities listed on Form B: Prices are to be considered approximate only. The City will use said quantities for the purpose of comparing Bids.

**B13.3 The Bidder must complete the Approximate Quantity column for Items 4 and 5 on Form B: Prices. These quantities are dependent on the proposed design as submitted.**

- B13.4 The quantities for which payment will be made to the Contractor are to be determined by the Work actually performed and completed by the Contractor, to be measured as specified in the applicable Specifications.
- B13.5 Payments to Non-Resident Contractors are subject to Non-Resident Withholding Tax pursuant to the Income Tax Act (Canada).

**B14. DISCLOSURE**

B14.1 Various Persons provided information or services with respect to this Work. In the City's opinion, this relationship or association does not create a conflict of interest because of this full disclosure. Where applicable, additional material available as a result of contact with these Persons is listed below.

B14.2 The Persons are:

- (a) Playgrounds R Us;
- (b) Questic Contracting;
- (c) Colcat

**B15. QUALIFICATION**

B15.1 The Bidder shall:

- (a) undertake to be in good standing under The Corporations Act (Manitoba), or properly registered under The Business Names Registration Act (Manitoba), or otherwise properly registered, licensed or permitted by law to carry on business in Manitoba; and
- (b) be financially capable of carrying out the terms of the Contract; and
- (c) have all the necessary experience, capital, organization, and equipment to perform the Work in strict accordance with the terms and provisions of the Contract.

B15.2 The Bidder and any proposed Subcontractor (for the portion of the Work proposed to be subcontracted to them) shall:

- (a) be responsible and not be suspended, debarred or in default of any obligations to the City. A list of suspended or debarred individuals and companies is available on the Information Connection page at The City of Winnipeg, Corporate Finance, Materials Management Division website at <http://www.winnipeg.ca/matmgt/debar.stm>

B15.3 The Bidder and/or any proposed Subcontractor (for the portion of the Work proposed to be subcontracted to them) shall:

- (a) have successfully carried out work similar in nature, scope and value to the Work; and
- (b) be fully capable of performing the Work required to be in strict accordance with the terms and provisions of the Contract; and
- (c) have a written workplace safety and health program if required pursuant to The Workplace Safety and Health Act (Manitoba);

B15.4 Further to B15.3(c), if the Bid Price is over \$100,000, the Bidder shall, within five (5) Business Days of a request by the Contract Administrator, provide proof satisfactory to the Contract Administrator that the Bidder/Subcontractors has a workplace safety and health program meeting the requirements of The Workplace Safety and Health Act (Manitoba), by providing:

- (a) a valid COR certification number under the Certificate of Recognition (COR) Program administered by the Construction Safety Association of Manitoba or by the Manitoba Heavy Construction Association's WORKSAFELY™ COR™ Program; or
- (b) a report or letter to that effect from an independent reviewer acceptable to the City. (A list of acceptable reviewers and the review template are available on the Information

Connection page at The City of Winnipeg, Corporate Finance, Materials Management Division website at <http://www.winnipeg.ca/matmgt/>.

B15.5 The Bidder shall submit, within three (3) Business Days of a request by the Contract Administrator, proof satisfactory to the Contract Administrator of the qualifications of the Bidder and of any proposed Subcontractor.

B15.6 The Bidder shall provide, on the request of the Contract Administrator, full access to any of the Bidder's equipment and facilities to confirm, to the Contract Administrator's satisfaction, that the Bidder's equipment and facilities are adequate to perform the Work.

## **B16. DESIGN DRAWINGS**

B16.1 The Bidder shall submit drawings that illustrate the proposed design and play equipment, such as plan, perspective and any other submissions to illustrate the design intent. **Included in this shall be a plan showing the proposed play equipment and associated safety zones within the proposed play area and site, drawn to scale.** Additional drawings may be requested prior to award for more detailed information.

## **B17. COMPONENT DESCRIPTIONS**

B17.1 The Bidder shall submit component description and / or graphic or catalogue reference outlining specifications of play equipment components

## **B18. OPENING OF BIDS AND RELEASE OF INFORMATION**

B18.1 Bids will not be opened publicly.

B18.2 Following the submission deadline, the names of the Bidders and their Total Bid Prices (unevaluated, and pending review and verification of conformance with requirements) will be available on the Closed Bid Opportunities (or Public/Posted Opening & Award Results) page at The City of Winnipeg, Corporate Finance, Materials Management Division website at <http://www.winnipeg.ca/matmgt/bidopp.asp>

B18.3 After award of Contract, the name(s) of the successful Bidder(s) and the Contract amount(s) will be available on the Closed Bid Opportunities (or Public/Posted Opening & Award Results) page at The City of Winnipeg, Corporate Finance, Materials Management Division website at <http://www.winnipeg.ca/matmgt/>

B18.4 The Bidder is advised that any information contained in any Bid may be released if required by City policy or procedures, by The Freedom of Information and Protection of Privacy Act (Manitoba), by other authorities having jurisdiction, or by law.

## **B19. IRREVOCABLE BID**

B19.1 The Bid(s) submitted by the Bidder shall be irrevocable for the time period specified in Paragraph 9 of Form A: Bid.

B19.2 The acceptance by the City of any Bid shall not release the Bids of the next two lowest evaluated responsive Bidders and these Bidders shall be bound by their Bids on such Work for the time period specified in Paragraph 9 of Form A: Bid.

## **B20. WITHDRAWAL OF BIDS**

B20.1 A Bidder may withdraw his/her Bid without penalty by giving written notice to the Manager of Materials at any time prior to the Submission Deadline.

B20.1.1 Notwithstanding C23.3, the time and date of receipt of any notice withdrawing a Bid shall be the time and date of receipt as determined by the Manager of Materials.

- B20.1.2 The City will assume that any one of the contact persons named in Paragraph 3 of Form A: Bid or the Bidder's authorized representatives named in Paragraph 10 of Form A: Bid, and only such person, has authority to give notice of withdrawal.
- B20.1.3 If a Bidder gives notice of withdrawal prior to the Submission Deadline, the Manager of Materials will:
- (a) retain the Bid until after the Submission Deadline has elapsed;
  - (b) open the Bid to identify the contact person named in Paragraph 3 of Form A: Bid and the Bidder's authorized representatives named in Paragraph 10 of Form A: Bid; and
  - (c) if the notice has been given by any one of the persons specified in B20.1.3(b), declare the Bid withdrawn.
- B20.2 A Bidder who withdraws his/her Bid after the Submission Deadline but before his/her Bid has been released or has lapsed as provided for in B19.2 shall be liable for such damages as are imposed upon the Bidder by law and subject to such sanctions as the Chief Administrative Officer considers appropriate in the circumstances. The City, in such event, shall be entitled to all rights and remedies available to it at law.

## **B21. EVALUATION OF BIDS**

- B21.1 Award of the Contract shall be based on the following bid evaluation criteria:
- (a) compliance by the Bidder with the requirements of the Bid Opportunity or acceptable deviation there from (pass/fail);
  - (b) qualifications of the Bidder and the Subcontractors, if any, pursuant to B15 (pass/fail);
  - (c) Total Bid Price (10 points);
  - (d) Design Drawings/Component Descriptions (90 points);
  - (e) economic analysis of any approved alternative pursuant to B10.
- B21.2 Further to B21.1(a), the Award Authority may reject a Bid as being non-responsive if the Bid is incomplete, obscure or conditional, or contains additions, deletions, alterations or other irregularities. The Award Authority may reject all or any part of any Bid, or waive technical requirements or minor informalities or irregularities, if the interests of the City so require.
- B21.3 Further to B21.1(b), the Award Authority shall reject any Bid submitted by a Bidder who does not demonstrate, in his/her Bid or in other information required to be submitted, that he/she is responsible and qualified.
- B21.4 Further to B21.1(c), the Total Bid Price shall be the sum of the quantities multiplied by the unit prices for each item shown on Form B: Prices.
- B21.4.1 Further to B21.1(a), in the event that a unit price is not provided on Form B: Prices, the City will determine the unit price by dividing the Amount (extended price) by the approximate quantity, for the purposes of evaluation and payment.
- B21.4.2 Further to B21.1(c), the Award Authority may reject a Bid as being non-responsive if it exceeds the budget as shown on Form B: Prices.
- B21.4.3 The Total Bid Price shall be evaluated with a weighting of 10 points out of a total of 100 possible points. As such, the lowest Bidder shall receive the full 10 points, and the second lowest Bidder and subsequent Bidders shall be pro-rated accordingly.
- B21.5 Further to B21.1(d) Design Drawings/Component Descriptions shall be evaluated with a weighting of 90 points out of a total of 100 possible points as per B16 and B17.
- B21.5.1 The Design shall be evaluated on the following criteria:
- (a) compliance with CSA Standards (pass/fail);
  - (b) play value (maximum 41 points):

- (i) 7 points – Gross Motor Play Experience(s) (Climbing, overhead components, balancing, etc.);
  - (ii) 7 points – Imaginative/ Cognitive Play Component(s), including fine motor skills;
  - (iii) 7 points - Provides opportunities for appropriate social / interpersonal interaction and co-operative play;
  - (iv) 6 points – Motion Component(s) – to include at minimum one (1) teeter totter, and spinner seat(s);
  - (v) 6 points – Sliding Component(s) - min. one for each age group: 2-5 year old and 5-12 year old (all slides must be metal);
  - (vi) 3 points - Play Equipment Firehall/ Firefighter Theme;
  - (vii) 5 points - Variety of play Components.
- (c) Designed for inclusive play using Universal Design principles – Accessible Play Area only (maximum 15 points):
- (i) Complies with section 2.3.5 of the 2010 City of Winnipeg Accessibility Design Standards ( [www.winnipeg.ca/ppd/Universal\\_Design.stm](http://www.winnipeg.ca/ppd/Universal_Design.stm) )(pass/fail);
  - (ii) 3 points - Layout of the play area for integration of the wheelchair accessible components to promote inclusive play;
  - (iii) 3 points – Playstructure ramp leads to wheelchair accessible components that are fun for all;
  - (iv) 6 points – Provision of tactile and auditory play experiences.
  - (v) 3 points – Layout of the play area for persons with visual impairment
- (d) Layout/circulation (maximum 24 points):
- (i) 3 points - Connection to platform with ramp starting at 0.3m above top of safety surfacing;
  - (ii) 5 points - Flow and relationship between play area activities;
  - (iii) 4 points - Layout / orientation of components on Site and in relation to park entrances and seating areas;
  - (iv) 6 points – minimal amount of plastic components and moving parts to minimize vandalism
  - (v) 3 points – Orientation to provide good visibility to play area from adjacent roads;
  - (vi) 3 points - Slide orientation – metal must face north or east, plastic should face north or east.
- (e) Durability and performance (maximum 10 points):
- (i) Use of durable / tamper-resistant materials, low maintenance finishes and connector systems & ease of repair / replacement of the products used with the playground area & past performance.

B21.6 Further to B21.5.1, if Contractor states play equipment components are compliant with CSA Standards which are not, liquidated damages shall be charged as per D16 should this result in additional design and/or meeting time on the part of the Contract Administrator.

## **B22. AWARD OF CONTRACT**

B22.1 The City will give notice of the award of the Contract or will give notice that no award will be made.

B22.2 The City will have no obligation to award a Contract to a Bidder, even though one or all of the Bidders are determined to be responsible and qualified, and the Bids are determined to be responsive.

B22.2.1 Without limiting the generality of B22.2, the City will have no obligation to award a Contract where:

- (a) the prices exceed the available City funds for the Work;
- (b) the prices are materially in excess of the prices received for similar work in the past;
- (c) the prices are materially in excess of the City's cost to perform the Work, or a significant portion thereof, with its own forces;
- (d) only one Bid is received; or
- (e) in the judgment of the Award Authority, the interests of the City would best be served by not awarding a Contract.

B22.3 Where an award of Contract is made by the City, the award shall be made to the responsible and qualified Bidder submitting the lowest evaluated responsive Bid, in accordance with B21.

B22.3.1 Following the award of contract, a Bidder will be provided with information related to the evaluation of his/her Bid upon written request to the Contract Administrator.

B22.4 Notwithstanding C4, the City may issue a Purchase Order to the successful Bidder in lieu of the execution of a Contract.

B22.5 The Contract, as defined in C1.1, in its entirety shall be deemed to be incorporated in and to form a part of the Purchase Order notwithstanding that it is not necessarily attached to or accompany said Purchase Order.

## **PART C - GENERAL CONDITIONS**

### **C0. GENERAL CONDITIONS**

- C0.1 The *General Conditions for Construction* (Revision 2006 12 15) are applicable to the Work of the Contract.
- C0.1.1 The *General Conditions for Construction* are available on the Information Connection page at The City of Winnipeg, Corporate Finance, Materials Management Division website at [http://www.winnipeg.ca/matmgt/gen\\_cond.stm](http://www.winnipeg.ca/matmgt/gen_cond.stm)
- C0.2 A reference in the Bid Opportunity to a section, clause or subclause with the prefix “**C**” designates a section, clause or subclause in the *General Conditions for Construction*.

## **PART D - SUPPLEMENTAL CONDITIONS**

### **GENERAL**

#### **D1. GENERAL CONDITIONS**

D1.1 In addition to the *General Conditions for Construction*, these Supplemental Conditions are applicable to the Work of the Contract.

#### **D2. SCOPE OF WORK**

D2.1 The Work to be done under the Contract shall consist of supply and installation of play equipment, edging, surfacing, asphalt pathway and sodding.

D2.2 The major components of the Work are as follows:

- (a) Play equipment;
- (b) Engineered wood fibre safety surfacing;
- (c) Sand safety surfacing;
- (d) Concrete edging;
- (e) Asphalt pathway;
- (f) Site furniture; and
- (g) Sodding.

#### **D3. CONTRACT ADMINISTRATOR**

D3.1 The Contract Administrator is:

Shauna Prociuk  
Landscape Architect  
Telephone No. 204-986-3938  
Email: [shaunaprociuk@winnipeg.ca](mailto:shaunaprociuk@winnipeg.ca)

D3.2 At the pre-construction meeting, the Contract Administrator will identify additional personnel representing the Contract Administrator and their respective roles and responsibilities for the Work.

D3.3 Bids Submissions must be submitted to the address in B11.5.

#### **D4. CONTRACTOR'S SUPERVISOR**

D4.1 At the pre-construction meeting, the Contractor shall identify his/her designated supervisor and any additional personnel representing the Contractor and their respective roles and responsibilities for the Work.

#### **D5. OWNERSHIP OF INFORMATION, CONFIDENTIALITY AND NON DISCLOSURE**

D5.1 The Contract, all deliverables produced or developed, and information provided to or acquired by the Contractor are the property of the City and shall not be appropriated for the Contractors own use, or for the use of any third party.

D5.2 The Contractor shall not make any public announcements or press releases regarding the Contract, without the prior written authorization of the Contract Administrator.

D5.3 The following shall be confidential and shall not be disclosed by the Contractor to the media or any member of the public without the prior written authorization of the Contract Administrator;

- (a) information provided to the Contractor by the City or acquired by the Contractor during the course of the Work;
- (b) the Contract, all deliverables produced or developed; and
- (c) any statement of fact or opinion regarding any aspect of the Contract.

D5.4 A Contractor who violates any provision of D5 may be determined to be in breach of Contract.

## **D6. NOTICES**

D6.1 Except as provided for in C23.2.2, all notices, requests, nominations, proposals, consents, approvals, statements, authorizations, documents or other communications to the Contractor shall be sent to the address or facsimile number identified by the Contractor in Paragraph 2 of Form A: Bid.

D6.2 All notices, requests, nominations, proposals, consents, approvals, statements, authorizations, documents or other communications to the City, except as expressly otherwise required in D6.3, D6.4 or elsewhere in the Contract, shall be sent to the attention of the Contract Administrator at the facsimile number identified in D3.1.

D6.3 Notwithstanding C21., all notices of appeal to the Chief Administrative Officer shall be sent to the attention of the Chief Financial Officer at the following facsimile number:

The City of Winnipeg  
Chief Financial Officer

Facsimile No.: 204 949-1174

D6.4 All notices, requests, nominations, proposals, consents, approvals, statements, authorizations, documents or other communications required to be submitted or returned to the City Solicitor shall be sent to the following facsimile number:

The City of Winnipeg  
Legal Services Department  
Attn: Director of Legal Services

Facsimile No.: 204 947-9155

D6.5 **Bids Submissions** must be submitted to the address in B11.5.

## **SUBMISSIONS**

### **D7. AUTHORITY TO CARRY ON BUSINESS**

D7.1 The Contractor shall be in good standing under The Corporations Act (Manitoba), or properly registered under The Business Names Registration Act (Manitoba), or otherwise properly registered, licensed or permitted by law to carry on business in Manitoba, or if the Contractor does not carry on business in Manitoba, in the jurisdiction where the Contractor does carry on business, throughout the term of the Contract, and shall provide the Contract Administrator with evidence thereof upon request.

### **D8. SAFE WORK PLAN**

D8.1 The Contractor shall provide the Contract Administrator with a Safe Work Plan at least five (5) Business Days prior to the commencement of any Work on the Site but in no event later than the date specified in C4.1 for the return of the executed Contract.

D8.2 The Safe Work Plan should be prepared and submitted in the format shown in the City's template which is available on the Information Connection page at The City of Winnipeg, Corporate Finance, Materials Management Division website at <http://www.winnipeg.ca/matmgt/Safety/default.stm>

## **D9. INSURANCE**

- D9.1 The Contractor shall provide and maintain the following insurance coverage:
- (a) commercial general liability insurance, in the amount of at least two million dollars (\$2,000,000.00) inclusive, with The City of Winnipeg added as an additional insured, with a cross-liability clause, such liability policy to also contain contractual liability, unlicensed motor vehicle liability, non-owned automobile liability and products and completed operations, to remain in place at all times during the performance of the Work and throughout the warranty period;
  - (b) if applicable, Automobile Liability Insurance covering all motor vehicles, owned and operated and used or to be used by the Contractor directly or indirectly in the performance of the Work. The Limit of Liability shall not be less than \$2,000,000 inclusive for loss or damage including personal injuries and death resulting from any one accident or occurrence;
  - (c) all risks installation floater, carrying adequate limits to cover all machinery, equipment, supplies and/or materials intended to enter into and form part of any installation.
- D9.2 Deductibles shall be borne by the Contractor.
- D9.3 The Contractor shall provide the Contract Administrator with a certificate(s) of insurance, **referencing the bid number or the specific operations to be performed**, in a form satisfactory to the City Solicitor, at least two (2) Business Days prior to the commencement of any Work but in no event later than seven (7) Calendar Days from notification of the award of Contract by Purchase Order.
- D9.4 The Contractor shall not cancel, materially alter, or cause each policy to lapse without providing at least thirty (30) Calendar Days prior written notice to the Contract Administrator.

## **D10. PERFORMANCE SECURITY**

- D10.1 If the Contract Price exceeds one hundred thousand dollars (\$100,000.00), the Contractor shall provide and maintain performance security until the expiration of the warranty period in the form of:
- (a) a performance bond of a company registered to conduct the business of a surety in Manitoba, in the form attached to these Supplemental Conditions (Form H1: Performance Bond), in the amount of fifty percent (50%) of the Contract Price; or
  - (b) an irrevocable standby letter of credit issued by a bank or other financial institution registered to conduct business in Manitoba and drawn on a branch located in Winnipeg, in the form attached to these Supplemental Conditions (Form H2: Irrevocable Standby Letter of Credit), in the amount of fifty percent (50%) of the Contract Price; or
  - (c) a certified cheque or draft payable to "The City of Winnipeg", drawn on a bank or other financial institution registered to conduct business in Manitoba, in the amount of fifty percent (50%) of the Contract Price.
- D10.1.1 Where the performance security is in the form of a certified cheque or draft, it will be deposited by the City. The City will not pay any interest on certified cheques or drafts furnished as performance security.
- D10.2 The Contractor shall provide the City Solicitor with the required performance security within seven (7) Calendar Days of notification of the award of the Contract by way of Purchase Order and prior to the commencement of any Work on the Site.

## **D11. SUBCONTRACTOR LIST**

- D11.1 The Contractor shall provide the Contract Administrator with a complete list of the Subcontractors whom the Contractor proposes to engage (Form J: Subcontractor List) at least

two (2) Business Days prior to the commencement of any Work on the Site but in no event later than seven (7) Calendar Days from notification of the award of Contract.

## **D12. DETAILED WORK SCHEDULE**

D12.1 The Contractor shall provide the Contract Administrator with a detailed work schedule at least two (2) Business Days prior to the commencement of any Work on the Site but in no event later than the date specified in C4.1 for the return of the executed Contract.

D12.2 Detailed Work Schedule shall consist of the following dates:

- (a) Start date;
- (b) Removals, excavation and grading;
- (c) Installation of concrete play edging and curbing;
- (d) Installation of play equipment;
- (e) Installation of safety surfacing and associated drainage;
- (f) Installation of asphalt path;
- (g) Installation of site furniture;
- (h) Installation of soil and sod, and;
- (i) Expected completion.

D12.3 Other milestone dates appropriate to this project should also be included to make the Contract Administrator Aware of them.

## **SCHEDULE OF WORK**

### **D13. COMMENCEMENT**

D13.1 The Contractor shall not commence any Work until he/she is in receipt of a Purchase Order from the Award Authority authorizing the commencement of the Work.

D13.2 The Contractor shall not commence any Work on the Site until:

- (a) the Contract Administrator has confirmed receipt and approval of:
  - (i) evidence of authority to carry on business specified in D7;
  - (ii) evidence of the workers compensation coverage specified in C6.15;
  - (iii) the Safe Work Plan specified in D8;
  - (iv) evidence of the insurance specified in D9;
  - (v) the Subcontractor list specified in D11; and
  - (vi) the detailed work schedule specified in D12.
- (b) the Contractor has attended a pre-construction meeting with the Contract Administrator, or the Contract Administrator has waived the requirement for a pre-construction meeting.

**D13.3 The Contractor shall order play equipment and submit this information to the Contract Administrator within seven (7) Calendar Days of receipt of the Purchase Order.**

**D13.4 The Contractor shall commence the Work on the Site within forty two (42) Calendar Days of receipt of the Purchase Order.**

### **D14. SUBSTANTIAL PERFORMANCE**

D14.1 The Contractor shall achieve Substantial Performance within twenty (20) consecutive Working Days of the commencement of the Work as specified in D13.

D14.2 When the Contractor considers the Work to be substantially performed, the Contractor shall arrange, attend and assist in the inspection of the Work with the Contract Administrator for purposes of verifying Substantial Performance. Any defects or deficiencies in the Work noted during that inspection shall be remedied by the Contractor at the earliest possible instance and the Contract Administrator notified so that the Work can be reinspected.

D14.3 The date on which the Work has been certified by the Contract Administrator as being substantially performed to the requirements of the Contract through the issue of a certificate of Substantial Performance is the date on which Substantial Performance has been achieved.

#### **D15. TOTAL PERFORMANCE**

D15.1 The Contractor shall achieve Total Performance within twenty five (25) consecutive Working Days of the commencement of the Work as specified in D13.

D15.2 When the Contractor or the Contract Administrator considers the Work to be totally performed, the Contractor shall arrange, attend and assist in the inspection of the Work with the Contract Administrator for purposes of verifying Total Performance. Any defects or deficiencies in the Work noted during that inspection shall be remedied by the Contractor at the earliest possible instance and the Contract Administrator notified so that the Work can be reinspected.

D15.3 The date on which the Work has been certified by the Contract Administrator as being totally performed to the requirements of the Contract through the issue of a certificate of Total Performance is the date on which Total Performance has been achieved.

#### **D16. LIQUIDATED DAMAGES**

D16.1 If the Contractor fails to achieve Total Performance in accordance with the Contract by the day fixed herein for Total Performance, the Contractor shall pay the City five hundred dollars (\$500.00) per Working Day for each and every Working Day following the day fixed herein for Total Performance during which such failure continues.

D16.2 The amount specified for liquidated damages in D16.1 is based on a genuine pre-estimate of the City's damages in the event that the Contractor does not achieve Total Performance by the day fixed herein for same.

D16.3 The City may reduce any payment to the Contractor by the amount of any liquidated damages assessed.

#### **D17. SCHEDULED MAINTENANCE**

D17.1 The Contractor shall perform the following scheduled maintenance in the manner and within the time periods required by the Specifications:

(a) Topsoil and sod as specified in E23.

D17.2 Determination of Substantial Performance and Total Performance shall be exclusive of scheduled maintenance identified herein. All scheduled maintenance shall be completed prior to the expiration of the warranty period. Where the scheduled maintenance cannot be completed during the warranty period, the warranty period shall be extended for such period of time as it takes the Contractor to complete the scheduled maintenance.

#### **CONTROL OF WORK**

##### **D18. JOB MEETINGS**

D18.1 Regular weekly job meetings will be held at the Site. These meetings shall be attended by a minimum of one representative of the Contract Administrator, one representative of the City and one representative of the Contractor. Each representative shall be a responsible person capable of expressing the position of the Contract Administrator, the City and the Contractor

respectively on any matter discussed at the meeting including the Work schedule and the need to make any revisions to the Work schedule. The progress of the Work will be reviewed at each of these meetings.

D18.2 The Contract Administrator reserves the right to cancel any job meeting or call additional job meetings whenever he/she deems it necessary.

**D19. PRIME CONTRACTOR – THE WORKPLACE SAFETY AND HEALTH ACT (MANITOBA)**

D19.1 Further to C6.24, the Contractor shall be the Prime Contractor and shall serve as, and have the duties of the Prime Contractor in accordance with The Workplace Safety and Health Act (Manitoba).

**D20. THE WORKPLACE SAFETY AND HEALTH ACT (MANITOBA) – QUALIFICATIONS**

D20.1 Further to B15.4, the Contractor/Subcontractor must, throughout the term of the Contract, have a Workplace Safety and Health Program meeting the requirements of The Workplace Safety and Health Act (Manitoba). At any time during the term of the Contract, the City may, at its sole discretion and acting reasonably, require updated proof of compliance, as set out in B15.4.

**MEASUREMENT AND PAYMENT**

**D21. PAYMENT**

D21.1 Further to C12, the City may at its option pay the Contractor by direct deposit to the Contractor's banking institution.

**WARRANTY**

**D22. WARRANTY**

D22.1 Warranty is as stated in C13.

**FORM H1: PERFORMANCE BOND**  
(See D10)

KNOW ALL MEN BY THESE PRESENTS THAT

\_\_\_\_\_ ,  
(hereinafter called the "Principal"), and

\_\_\_\_\_ ,  
(hereinafter called the "Surety"), are held and firmly bound unto **THE CITY OF WINNIPEG** (hereinafter called the "Obligee"), in the sum of

\_\_\_\_\_ dollars (\$\_\_\_\_\_)

of lawful money of Canada to be paid to the Obligee, or its successors or assigns, for the payment of which sum the Principal and the Surety bind themselves, their heirs, executors, administrators, successors and assigns, jointly and severally, firmly by these presents.

WHEREAS the Principal has entered into a written contract with the Obligee for

BID OPPORTUNITY NO. 533-2015

CAMPION TOT LOT PLAYGROUND REDEVELOPMENT

which is by reference made part hereof and is hereinafter referred to as the "Contract".

NOW THEREFORE the condition of the above obligation is such that if the Principal shall:

- (a) carry out and perform the Contract and every part thereof in the manner and within the times set forth in the Contract and in accordance with the terms and conditions specified in the Contract;
- (b) perform the Work in a good, proper, workmanlike manner;
- (c) make all the payments whether to the Obligee or to others as therein provided;
- (d) in every other respect comply with the conditions and perform the covenants contained in the Contract; and
- (e) indemnify and save harmless the Obligee against and from all loss, costs, damages, claims, and demands of every description as set forth in the Contract, and from all penalties, assessments, claims, actions for loss, damages or compensation whether arising under "The Workers Compensation Act", or any other Act or otherwise arising out of or in any way connected with the performance or non-performance of the Contract or any part thereof during the term of the Contract and the warranty period provided for therein;

THEN THIS OBLIGATION SHALL BE VOID, but otherwise shall remain in full force and effect. The Surety shall not, however, be liable for a greater sum than the sum specified above.

AND IT IS HEREBY DECLARED AND AGREED that the Surety shall be liable as Principal, and that nothing of any kind or matter whatsoever that will not discharge the Principal shall operate as a discharge or release of liability of the Surety, any law or usage relating to the liability of Sureties to the contrary notwithstanding.

IN WITNESS WHEREOF the Principal and Surety have signed and sealed this bond the

\_\_\_\_\_ day of \_\_\_\_\_, 20\_\_\_\_.

**SIGNED AND SEALED**  
in the presence of:

\_\_\_\_\_  
(Witness as to Principal if no seal)

\_\_\_\_\_  
(Name of Principal)

Per: \_\_\_\_\_ (Seal)

Per: \_\_\_\_\_

\_\_\_\_\_  
(Name of Surety)

By: \_\_\_\_\_ (Seal)  
(Attorney-in-Fact)

**FORM H2: IRREVOCABLE STANDBY LETTER OF CREDIT  
(PERFORMANCE SECURITY)**  
(See D10)

\_\_\_\_\_  
(Date)

The City of Winnipeg  
Legal Services Department  
185 King Street, 3rd Floor  
Winnipeg MB R3B 1J1

RE: PERFORMANCE SECURITY - BID OPPORTUNITY NO. 533-2015  
CAMPION TOT LOT PLAYGROUND REDEVELOPMENT

Pursuant to the request of and for the account of our customer,

\_\_\_\_\_  
(Name of Contractor)

\_\_\_\_\_  
(Address of Contractor)

WE HEREBY ESTABLISH in your favour our irrevocable Standby Letter of Credit for a sum not exceeding in the aggregate

\_\_\_\_\_ Canadian dollars.

This Standby Letter of Credit may be drawn on by you at any time and from time to time upon written demand for payment made upon us by you. It is understood that we are obligated under this Standby Letter of Credit for the payment of monies only and we hereby agree that we shall honour your demand for payment without inquiring whether you have a right as between yourself and our customer to make such demand and without recognizing any claim of our customer or objection by the customer to payment by us.

The amount of this Standby Letter of Credit may be reduced from time to time only by amounts drawn upon it by you or by formal notice in writing given to us by you if you desire such reduction or are willing that it be made.

Partial drawings are permitted.

We engage with you that all demands for payment made within the terms and currency of this Standby Letter of Credit will be duly honoured if presented to us at:

\_\_\_\_\_  
(Address)

and we confirm and hereby undertake to ensure that all demands for payment will be duly honoured by us.

All demands for payment shall specifically state that they are drawn under this Standby Letter of Credit.

Subject to the condition hereinafter set forth, this Standby Letter of Credit will expire on

\_\_\_\_\_  
(Date)

It is a condition of this Standby Letter of Credit that it shall be deemed to be automatically extended from year to year without amendment from the present or any future expiry date, unless at least 30 days prior to the present or any future expiry date, we notify you in writing that we elect not to consider this Standby Letter of Credit to be renewable for any additional period.

This Standby Letter of Credit may not be revoked or amended without your prior written approval.

This credit is subject to the Uniform Customs and Practice for Documentary Credit (2007 Revision), International Chamber of Commerce Publication Number 600.

\_\_\_\_\_  
(Name of bank or financial institution)

Per: \_\_\_\_\_  
(Authorized Signing Officer)

Per: \_\_\_\_\_  
(Authorized Signing Officer)





## PART E - SPECIFICATIONS

### GENERAL

#### E4. APPLICABLE SPECIFICATIONS AND DRAWINGS

- E4.1 These Specifications shall apply to the Work.
- E4.2 *The City of Winnipeg Standard Construction Specifications* in its entirety, whether or not specifically listed on Form B: Prices, shall apply to the Work.
- E4.2.1 *The City of Winnipeg Standard Construction Specifications* is available on the Information Connection page at The City of Winnipeg, Corporate Finance, Materials Management Division website at <http://www.winnipeg.ca/matmgt/Spec/Default.stm>
- E4.2.2 The version in effect three (3) Business Days before the Submission Deadline shall apply.
- E4.2.3 Further to C2.4(d), Specifications included in the Bid Opportunity shall govern over *The City of Winnipeg Standard Construction Specifications*.
- E4.3 The following are applicable to the Work:

<u>Drawing No.</u>	<u>Drawing Name/Title</u>
C.29-C1-R0	Campion Tot Lot Playground Renovation - Existing Conditions and Removals
C.29-C2-R0	Campion Tot Lot Playground Renovation - Proposed
C.29-C3-R0	Campion Tot Lot Playground Renovation - Grading
C.29-C4-R0	Campion Tot Lot Playground Renovation - Layout
C.29-C5-R0	Campion Tot Lot Playground Renovation – Details 1
C.29-C6-R0	Campion Tot Lot Playground Renovation – Details 2
SCD-105A-R2	Post and Chain Fencing
SCD-119-R2	Waste Receptacle Side Opening Metal Slat Type
SCD-121C-R2	Tache Backless Bench Composite With Arms
SCD-121A-R2	Tache Bench Composite With Arms
SCD-122A-R1	Tache Style Wheelchair Metal Frame Picnic Table
SCD-122-R1	Tache Style Metal Frame Picnic Table
SCD-650-R1	Engineered Wood Fibre Safety Surfacing Drainage Diagram
SCD-659-R2	Multi-Flow Drainage

### GENERAL

#### E5. EXISTING SERVICES AND UTILITIES

- E5.1 No responsibility will be assumed by the City for correctness or completeness of the Drawings, when provided, with respect to the existing utilities, pipes or other objects either underground or on the surface; the City shall not be liable for the incorrectness and inadequacy thereof. It shall be the responsibility of the Contractor to determine the location of all such utilities, pipes and other objects and to make good any damage done to them.

#### E6. ACCESS TO SITE

- E6.1 Access to the Site as required by the Contractor shall be provided and maintained by the Contractor at his own expense and approved by the Contract Administrator.
- E6.2 The Contractor's operations shall be limited to the minimum area necessary for undertaking the Work and he shall be responsible for all damage resulting from his Work on private property.

## **E7. PERMITS, NOTICES, LICENSES, CERTIFICATES, LAWS AND RULES**

- E7.1 Further to C6.12, the Contractor shall give all necessary notices, obtain all necessary permits and pay all fees in order that the Work may be carried out. The Contractor shall submit all plans required by any inspection authority and obtain approval of same before proceeding with the Work, and pay any cost attached to the inspection of such plans.
- E7.2 The Contractor shall comply with all laws, ordinances, rules and regulations that would relate to the Work.
- E7.3 All notices, consents, approvals, statements, authorizations, documents or other communications to the City shall be submitted to the Contract Administrator.
- E7.4 All Work shall be performed in compliance with the Manitoba Workplace Health and Safety Act.
- E7.5 All Work shall be performed in compliance with the Manitoba Workplace Health and Safety Fall Protection guidelines.
- E7.6 The Contractor and Sub-contractors must be fully aware of all Work involving hazardous materials. All Work must be performed in compliance with the Manitoba Department of Labour Workplace Health and Safety Guidelines and all other applicable codes. The Contractor is responsible for the immediate notification to the Contract Administrator of his/her encountering of suspected hazardous material during their course of Work.

## **E8. DAMAGE TO EXISTING STRUCTURES, TREES AND PROPERTY**

- E8.1 All necessary precautions shall be exercised by the Contractor so as not to remove, disturb, or damage any existing trees, shrubs, sod, pavements, streets, roads, boulevards, poles, hydrants, water pipes, gas pipes, electrical wires, cables, conduits, sewers or other existing facilities and equipment at the Site of the Work. For all damage incurred in the performance of the Work (either directly or indirectly), the Contractor shall either replace and repair such damage, whichever may be deemed necessary in the opinion of, and acceptable to City of Winnipeg Contract Administrator, and the cost of which shall be borne entirely by the Contractor. The Contractor shall also indemnify and save harmless the City from all claims made directly or indirectly against it in respect to any such damage.
- E8.2 The Contractor shall take the following precautionary steps to prevent damage from construction activities to existing park trees within the limits of the construction area:
- (a) The Contractor shall not stockpile materials and soil or park vehicles and equipment within 2 metres of trees.
  - (b) Trees identified to be at risk by the Contract Administrator are to be strapped with 25x100x2400 wood planks, or suitable protection as approved by the Contract Administrator.
  - (c) Excavation shall be performed in a manner that minimizes damage to the existing root systems. Where possible, excavation shall be carried out such that the edge of the excavation shall be a minimum of 1.5 times the diameter (measured in inches), with the outcome read in feet, from the closest edge of the trunk. Where roots must be cut to facilitate excavation, they shall be pruned neatly at the face of excavation.
  - (d) Operation of equipment within the drip line of the trees shall be kept to a minimum required to perform the Work required. Equipment shall not be parked, repaired, refuelled; construction materials shall not be stored, and earth materials shall not be stockpiled within the drip lines of trees. The drip line of a tree shall be considered to be the ground surface directly beneath the tips of its outermost branches. The Contractor shall ensure that the operations do not cause flooding or sediment deposition on areas where trees are located.
- E8.3 All damage to existing trees caused by the Contractor's activities shall be repaired to the requirements and satisfaction of the Contract Administrator and the City Forester or his/her designate.

E8.4 No separate measurement or payment will be made for the protection of trees.

**E9. PEDESTRIAN SAFETY AND TRAFFIC MANAGEMENT**

E9.1 Further to CW 1130-R1, the Contractor shall take such measures as are necessary to ensure safe and convenient pedestrian ingress and egress is maintained to private properties while he is Working near them. Any damage caused by the negligence of the Contractor or his Sub-Contractors to the adjacent Works or properties, shall be promptly repaired by him at his own expense, to the satisfaction of the Contract Administrator.

E9.2 Ambulance/ Emergency vehicle access must be maintained at all times.

**E10. PROTECTION OF THE SURVEY INFRASTRUCTURE**

E10.1 Notwithstanding clause 4 "Protection of Survey Bars" of the Standard Provisions; Current legislation, The Surveys Act, places the onus on those undertaking construction to protect the Survey Infrastructure from damage as a result of their activity.

E10.2 Further to C:6.26 (g), at least 72 hours prior to the commencement of the On-Site Work the Contractor shall contact the City of Winnipeg, Geomatics Services Branch at 918-1360 (8:00 am to 4:00 pm Monday to Friday excluding holidays) to obtain underground clearance. Geomatics Services will locate and mark all known outline survey monuments and geodetic control monuments and confirm the physical condition of those monuments upon completion of construction, at no cost to the Contractor.

E10.3 Where a survey post, bar or control monument lies in the line of the proposed Work and must be disturbed, the Contractor shall provide the Contract Administrator with 48 hours notice to permit referencing for future replacement, at no cost to the Contractor. Failure to provide the specified notice shall result in the Contractor paying for all costs associated with replacing or relocating the disturbed outline survey monuments and geodetic control monuments.

E10.4 Survey monuments and geodetic control monuments at or adjacent to the Site, not in the line of the proposed construction that are damaged or disturbed by the Contractor shall be replaced or relocated by the City or its agent and all associated costs shall be paid for by the Contractor. An approximate estimate of the costs involved to restore a legal survey monument is \$1,000 per bar and \$3,000 per control monument. Contractors must ensure their landscaping and other subcontractors are aware of this clearance procedure and the potential restoration costs.

E10.5 Where possible, amounts owed to the City in accordance with the above will be deducted from any payments to be made by the City to the Contractor.

**E11. SITE RESTORATION**

E11.1 Total Performance of the Work shall not be attained until the Contractor has cleaned up the Site and has removed all tools, equipment, waste, debris and surplus foundation earth to the satisfaction of the Contract Administrator. Unless otherwise specified, the Contractor shall restore all areas of the Site beyond the established limit of Work, which have been disturbed by the Contractor's operations to as good as or better than the original condition to the satisfaction of the Contract Administrator. The Contractor shall pay all costs associated with this Work.

**E12. SITE ENCLOSURES**

E12.1 Temporary Site enclosures, as determined necessary at the pre-construction meeting, shall be erected and maintained as required for the duration of the construction period.

E12.2 Site enclosures shall be considered incidental to the Contract Work.

## Site Development

### E13. REMOVALS

#### E13.1.1 General Description

- (a) This specification is supplemental to the latest version of CW 3010 and CW 3110.
- (b) The Work to be done by the Contractor under this specification shall include the furnishing of all superintendence, overhead, labour, materials, equipment, tools, supplies and all other things necessary for and incidental to satisfactory performance and completion of all Work as shown on the drawings as herein specified.

#### E13.2 Work shall include the following:

##### E13.2.1 Remove and legally dispose of:

- (a) Existing vegetation as shown on Drawings:
  - (i) Existing vegetation to be removed includes one (1) dead tree and approximately 20 sq.m of scrub trees and shrubs.

#### E13.3 Construction Methods

E13.3.1 Disposal of material shall be understood to mean hauling of all unsuitable material from the Site and the unloading in a legal manner acceptable to the Contract Administrator.

E13.3.2 Backfill and tamp down holes with compacted sand to a depth of 0.6m. Top with 0.3m of topsoil and sod to as per E23. Match existing grade.

E13.3.3 Existing vegetation as indicated on Drawings shall be removed as per CW 3010. Contractor must ensure the stump from the dead tree be removed in order to allow for asphalt path construction in its place.

#### E13.4 Method of Measurement and Basis of Payment

##### E13.4.1 Method of Measurement shall be as follows:

- (a) Removals shall be measured on a lump sum basis for: "Removals".

##### E13.4.2 Basis of Payment shall be as follows:

- (a) Removals will be paid for at the Contract Unit Prices on Form B: Prices. The amount to be paid shall be for full payment for supplying all labour, equipment and materials, and performing all operations herein described and all other items incidental to the Work and as accepted by the Contract Administrator.

### E14. EXCAVATION AND GRADING

#### E14.1 General Description

E14.1.1 This specification shall amend and supplement CW 3110 and CW 3170. It shall cover the excavation and legal disposal of sand safety surfacing; excavation for new pathways and new play areas; and required site grading as per Drawings.

E14.1.2 All extraneous materials are to be removed from the Site and disposed of in a safe and legal manner.

- (a) The Work to be done by the Contractor under this specification shall include all labour, equipment and material necessary for and incidental to the satisfactory performance and completion of the Work herein specified.

#### E14.1.3 Work shall include but not be limited to the following:

- (a) Excavate, add clean fill if necessary, and grade to the limits shown on Drawings to the depths necessary to achieve finish grade for:

- (i) New Play Area Protective Surfacing and Drainage;
  - ◆ Old sand safety surfacing only has to be excavated as deep as required to install new safety surface and drainage. Leave remaining sand in place below new play area;
- (ii) New topsoil and sod over excavated play areas; and
- (iii) New asphalt paths and seating areas.

## E14.2 Construction Methods

- E14.2.1 Excavation includes the removal of items (i.e., sand, earth) as indicated on the Drawings and as directed by the Contract Administrator. Work includes the satisfactory disposal of unsuitable Site material such as clays susceptible to frost-heaving, silts, rock, rubble, rubbish and any surplus suitable Site material.
- (a) Stockpile suitable, approved material on Site for reuse (clean topsoil, clean earth fill,) in a secure location. Remove and dispose of unsuitable material.
  - (b) Disposal of material shall be understood to mean the hauling of all unsuitable material from the Site and the unloading in a legal manner acceptable to the Contract Administrator. If arrangements are made in advance excavated material may be disposed of on Site at a location designated by the Contract Administrator.
  - (c) Contractor must coordinate with the Contract Administrator to ensure all removals have occurred.
  - (d) Excavation should be coordinated with the installation of play equipment and safety surfacing so as not to leave an open excavation area subject to ponding water.
  - (e) The depth of excavation in the play area shall directly relate to the requirements of the play equipment proposed in the Bid Submission.
  - (f) Excavate to the limits shown and as necessary to achieve finish grades as indicated on the Drawings:
    - (i) New Play Areas – depth to accommodate required safety surfacing based on proposed play equipment, in accordance with Drawings and per E16;
    - (ii) New Asphalt Path and Seating Area – 275 mm depth, in accordance with Drawings and per E18; and
    - (iii) New topsoil and sod – in accordance with Drawings and per E23.

## E14.2.2 Site grading

- (a) Site grading shall be as per Drawings and CW 3170 and shall be integral to all components of Work. Ensure finished grades match proposed grades shown on Drawings. All areas without proposed grades shown shall be graded smoothly to match up with existing edges of the site that remain untouched.
- (b) The Contractor must ensure that the rough grading does not create tripping hazards and no areas of standing water remain. The mud grade of all excavated play areas must drain towards the subsurface drainage piping.

## E14.2.3 Do not disturb adjacent items designated to remain in place.

## E14.3 Method of Measurement and Basis of Payment

### E14.3.1 Method of Measurement shall be as follows:

- (a) Excavation and Grading shall be measured on a cubic metre basis for:
  - (i) "Excavation" on Form B: Prices.
- (b) No measurement will be made for Excavation and Grading of the new asphalt path and seating area as these items are incidental to E18.

### E14.3.2 Basis of Payment shall be as follows:

- (a) Excavation and Grading will be paid for at the Contract Unit Prices on Form B: Prices. The amount to be paid for shall be the total number of units, measured as specified herein, which price shall be for full payment for supplying all labour, equipment and materials, and performing all operations herein described and all other items incidental to the Work and as accepted by the Contract Administrator.
- (b) No payment will be made for the Excavation and Grading for the new asphalt path and seating area as these items are incidental to E18.

**E15. SUB-SURFACE DRAINAGE**

**E15.1 Description**

E15.1.1 This Work shall consist of providing and placing a geocomposite prefabricated drain system to drain the play area, and connection to an emitter, as shown on Drawings.

E15.1.2 This Work shall include:

- (a) Subsurface drainage to drain new playground surfacing, as described in the plans as per SCD-650 and SCD-659.

**E15.2 Material**

E15.2.1 Drainage pipe will be Multi-Flow or approved substitute in accordance with B10. Drainage pipe will 150 mm (6"). The manufacturer will size and approve all fittings for use with Multi-Flow or approved substitute drainage pipe.

E15.2.2 The drain conduit shall be of flexible, prefabricated, rounded rectangular shaped, composite product. The drain conduit will be wrapped with a non-woven geotextile and will be a non-woven needle-punched construction and consist of long-chain polymeric fibres composed of polypropylene, polyethylene or polyamide. The fibres will be oriented into a multi-directional stable network whereby they retain their positions relative with each other and allow the passage of water as specified. The fabric will be free of any chemical treatment or coating, which reduces permeability and will be inert to chemical commonly found in soil. The geotextile will conform to the following minimum average roll values.

Weight	ASTM D-3776	3.0 - 4.0
Tensile Strength	ASTM D-4632	100 - 130
Elongation %	ASTM D-4632	50 - 70
Puncture, lb	ASTM D-751	35 - 60
Mullen Burst, psi	ASTM D-3786	110 - 215
Trapezoidal Tear, lb	ASTM D-4533	40 - 42
Coefficient of Permeability	ASTM D-4491	.2 - .4 cm/sec
Flow Rate, gpm/ft <sup>2</sup>	ASTM D-4491	100 - 140
Permittivity, 1/sec	ASTM D-4491	1.3 - 2.0
Apparent Opening Size	ASTM D-4751	60/70 Max. US Std Sieve Opening
Seam Strength, lb/ft	ASTM D-4595	100
Fungus	ASTM G-21	No Growth

E15.2.3 The drainage core shall be made of a high-density polyethylene. The core shall be constructed using interconnected corrugated pipes that define and provide the flow channels and structural integrity of the drain. The geotextile shall function only as a filter. The core of the edge drain shall conform to the following physical property requirements.

Thickness, inches	ASTM D-1777	1.0
Flow Rate, gpm/ft*	ASTM D-4716	29

Compressive Strength, psf	ASTM D-1621 (modified sand method)	6000
Pipe Stiffness, pii	ASTM D-2412	100

\* At gradient = 0.1, pressure = 10 psi for 100 hours.

E15.2.4 Fittings

- (a) The fittings used with the edge drain shall be of a snap together design. In no case shall any drainage product be joined without the use of the manufacturers connector designed specifically for the purpose. Cleanouts will be provided as indicated on the drawing.

E15.2.5 Pipe

- (a) Pipe for drain outlet laterals will be either 75 mm (3") PVC pipe meeting the requirements of ASTM D-2729 or ASTM F-949, or high-density polyethylene pipe meeting the requirements of AASHTO M252.
- (b) A rodent screen made of 0.3 inch by 0.3-inch square opening size, 0.063-inch gauge, stainless steel or galvanized, welded wire mesh shall be installed in each outlet lateral line. When using galvanized welded wire mesh, the rodent screen shall be galvanized after it has been formed to the shape and dimensions shown on the plans or specified by the Contract Administrator.

E15.2.6 Emitter

- (a) Shall be a 3" polyolefin pop-up drainage emitter with elbow joint, product reference no. NDS# 620 or approved substitute in accordance with B6. Multiflow shall be connected to emitter by using manufacturer's adaptor for connecting drainage pipe to 75mm or 100mm round orifice on appropriate hardware.
  - (i) Contact for Emitter:
    - Consolidated Turf
    - 986 Powell Avenue
    - Winnipeg, Manitoba
    - R3H 0H6
    - Tel: 1-204-633-7276
    - Fax: 1-204-633-3447

E15.3 Backfill for Trenches

- (a) As per SCD-659

E15.4 Methods

E15.4.1 Installation of Subdrain is not to proceed until after the excavation/grading has been approved by the Contract Administrator.

E15.4.2 The layout of the subdrain is to be marked on Site and approved by the Contract Administrator prior to trenching.

E15.4.3 Subdrain within the play area is to be laid on the prepared surface to facilitate cross movement of water. Subdrain shall be installed below geotextile and in conformance with details provided.

- (a) Play area to be graded to drain towards subdrain. This subdrain is to be used in conjunction with the appropriate wood fibre drainage layer to bring excess water out of the play area.

E15.4.4 Trenches are to be inspected by the Contract Administrator prior to backfilling.

- E15.4.5 Pipe is to be placed in the trench and the trench is to be backfilled according to detail Drawings. Backfill is to be lightly tamped into place to eliminate any voids.
- E15.4.6 Fittings for the drain shall be installed in accordance with manufacturer's recommendations.
- E15.4.7 The Contractor shall be responsible for restoration of any surfaces damaged during the Work under this section.
- E15.4.8 Contractor is to protect subdrain from excessive weight during the duration of construction and to repair and make good any pipe collapsed prior to acceptance.
- E15.4.9 Any damaged edge drain or outlet lateral will be replaced or repaired by splicing in an undamaged section of drain at the Contractor's expense. The repair must be in accordance with the manufacturer's specification and to the satisfaction of the Contract Administrator.

**E15.5 Measurement and Payment**

- E15.5.1 Method of Measurement shall be as follows:
- (a) No measurement shall be made for subsurface drainage as it is incidental to E16.
- E15.5.2 Basis of Payment Shall be as follows:
- (a) No payment shall be made for subsurface drainage as it is incidental to E16.

**E16. PROTECTIVE SURFACING**

**E16.1 General Description**

- E16.1.1 This specification shall cover the supply and install of playsand and wood fibre safety surfacing and associated sub-surface drainage.

**E16.2 Playsand Safety Surfacing**

**E16.2.1 Materials**

- (a) Playsand Safety Surfacing shall be course sand of the following Sieve breakdown:

Sieve Size	Cumulative % passing
10mm stone	99
5mm	88
1.25	69
315 um	11
80 m	1.75

**E16.2.2 Construction Methods**

- (a) Playsand Safety Surfacing shall be installed within the boulder and wood stepping post play area, as defined by the concrete edging, to a minimum depth of 250mm.
- (b) The installation of the Playsand Safety Surfacing shall be done immediately after the boulders and stepping posts have been installed.
- (c) Do not compact the material during installation.
- (d) Installation shall be done by equipment sized to suit the Work being done and the sand shall be spread by hand as necessary in the immediate vicinity of the boulders and stepping posts so as not to damage same.

**E16.3 Wood Fibre Safety Surfacing**

**E16.3.1 Description**

- (a) This specification shall cover the supply and installation of Wood Fibre Surfacing within the Play Equipment Area.

- (b) This specification shall cover the drain out of the play area and the connection of the subsurface drainage to an emitter as shown on Drawings and E15.

#### E16.3.2 Materials

- (a) Wood Fibre product shall be Zeager Woodcarpet or substitute in accordance with B10.
- (b) Wood Fibre surfacing shall be supplied by an authorized distributor and delivery slips and/or a warranty certificate from an authorized supplier are to be submitted to the Contract Administrator prior to installation.**

- (i) Contact for Woodcarpet:

Zeagar Bros. Inc.  
4000 East Harrisburg Pike ·  
Middletown, PA 17057  
USA  
Ph: (1-888) 346-8524 or (717) 944-7481 ·  
Fax (717) 944-7681  
[sales@zeager.com](mailto:sales@zeager.com)

- (c) If substitute to Zeager Woodcarpet is proposed, it must meet the following conditions:
  - (i) materials must be IPEMA certified Engineered Wood Fiber
  - (ii) material must consist of random-sized, clean, engineered hardwood chips. Standard wood chips or bark mulch are not acceptable.
  - (iii) materials must meet or exceed ASTM F1292 standards for impact attenuation
  - (iv) materials must be certified by the CSA and approved for playground use
  - (v) materials must comply with ASTM F1951 for accessibility under the Canadians with Disabilities Act
  - (vi) materials must be covered by \$10,000,000.00 product liability insurance as well as provide a minimum 10 year warranty against loss of resiliency
- (d) Wood Fibre surfacing shall include wood fibre, filter cloth, subsurface drainage system and mats under swings and ends of slides.
- (e) Mats are to be installed directly on top of the geotextile fabric and secured in place with two (2) duckbill anchors per mat.

#### E16.3.3 Construction Methods

- (a) Wood Fibre shall be installed within the play areas, as defined by the timber edging to a minimum depth of 200 mm (after compaction). In the case where proposed play equipment includes a maximum fall height greater than 1.8m (6'), depth of material to directly correspond to maximum fall height of play equipment in accordance with manufacturer's specifications.
- (b) The installation of the Wood Fibre shall be done immediately after the play equipment has been installed.
- (c) Installation of entire system, including fibre, filter cloth, subsurface drainage and mats under swings and slide ends shall be done according manufacturer's instructions. Adequate drainage within play equipment area must be ensured as per same.
- (d) Mud grade of play area shall be graded to drain to one edge of the play area, and area cleared of any debris which inhibit proper drainage or installation of products. Drainage pipe shall be installed from the subsurface drainage system within the play area to run outside of the play area perimeter to drain into an existing catch basin. The cost of this shall be included in the price for the wood fibre supply and installation.

- (e) Filter fabric must be cut and fit around playground equipment footings and overlap seams by 300mm.
- (f) Installation shall be done by equipment sized to suit the Work being done and the Wood Fibre shall be spread by hand as necessary in the immediate vicinity of the play equipment so as not to damage same. The play equipment shall be swept clean to the satisfaction of the Contract Administrator after installation of the Wood Fibre.

#### E16.4 Method of Measurement and Basis of Payment

##### E16.4.1 Method of Measurement shall be as follows:

- (a) Protective Surfacing will be measured on a square metre basis for:
  - (i) "Playsand surfacing (275 mm depth)"; and
  - (ii) "Engineered Wood Fibre Safety Surfacing, including Drainage" on Form B: Prices.

◆ **The Bidder must indicate for Item # 4 on Form B: Prices the required quantity of units, dependant on the submission.**

##### E16.4.2 Basis of Payment shall be as follows:

- (a) Protective Surfacing will be paid for at the Contract Unit Prices. The amount to be paid for shall be the total number of units, as indicated on Form B: Prices. This price shall be full payment for supplying all labour, equipment and materials, and performing all operations herein described and all other items incidental to the Work and as accepted by the Contract Administrator.

### E17. POURED IN PLACE CONCRETE EDGING

#### E17.1 General Description

- E17.1.1 This section shall cover the supply and installation of the poured in place concrete playground curb per SCD-643 and Drawings. It shall be read as supplementing City of Winnipeg Standard Construction Specifications CW 3310 and CW 3110.
- E17.1.2 The Work to be done by the Contractor under this Specification shall include the furnishing of all superintendence, overhead, labour, materials, equipment, tools, supplies and all other things necessary for and incidental to the satisfactory performance and completion of all Work as shown on the Drawings and as hereinafter specified, including, but not necessarily confined to the following:
  - (a) Supply and installation of Concrete Play Edging; and
  - (b) Supply and installation of Concrete Edging for Ramp

#### E17.2 Materials

- E17.2.1 Portland Cement to CAN3-A5-M 1983 and CW 3310;
- E17.2.2 Sub Base and Base Course as per CW 3110 and Drawings;
- E17.2.3 Geotextile fabric shall be non-woven and in accordance with CW 3130.

#### E17.3 Construction Methods

- E17.3.1 Layout is to be established on Site, after excavation and grading operations and reviewed by Contract Administrator prior to formwork being completed.
  - (a) Contractor shall visit the Site and verify all data and dimensions and report any errors, omissions or discrepancies to the Contract Administrator prior to any installation.
  - (b) Contractor to layout all concrete work. Contractor shall be responsible for interpretation of grades and protection of stakes. Layout to be approved by Contract Administrator prior to construction.

- E17.3.2 General Contractor is to confirm and warrant that play equipment complete with required safety surfacing zones will fit within curbs as laid out on Site.
- E17.3.3 Granular base, formwork and reinforcing are to be reviewed on Site by the Contract Administrator prior to pouring of concrete.
- E17.3.4 Concrete is to be light broom finished. All exposed edges are to be bull nose as shown on the Drawings. Front, top and back of curb are to be finished, as per CW 3310.
- E17.3.5 Concrete Play Edging and Edging for Ramp shall have saw cut control joints at 1.5m intervals.
- E17.4 Method of Measurement and Basis of Payment
- E17.4.1 Method of Measurement shall be as follows:
- (a) Poured in Place Concrete Edging will be measured on a Linear Metre basis for:
- (i) "Concrete Play Edging"
- ◆ **The Bidder must indicate for Item # 5 on Form B: Prices the required quantity of units, dependant on the submission.**
- (ii) "Concrete Edging for Ramp" on Form B: Prices.
- E17.5 Basis of Payment Shall be as follows:
- E17.5.1 Poured in Place Concrete Edging will be paid for at the Contract Unit Prices. The amount to be paid for shall be the total number of units, as indicated on Form B: Prices. This price shall be full payment for supplying all labour, equipment and materials, and performing all operations herein described and all other items incidental to the Work and as accepted by the Contract Administrator.
- E17.5.2 This payment shall be understood to include all concrete, excavation, base, reinforcing, compaction, placement and finishing.

## **E18. ASPHALT PATH**

- E18.1 This specification shall cover the renovation of an existing asphalt path as well as the supply and installation of a new asphalt path.
- (a) The renovation of the existing asphalt path includes the removal of the asphalt layer (approximately 50mm), the compaction of the existing base, the addition of 19mm crushed limestone down, compacted, and 75mm asphalt layer to match grades indicating on Grading Drawing.
- (b) The supply and installation of a new asphalt path shall include the Excavation, Sub-base Compaction, Geotextile Fabric, Crushed Limestone Sub-Base, Crushed Limestone Base, and Asphaltic Pavement Layer as per Drawings and as indicated below.
- E18.2 Excavation
- E18.2.1 Description
- (a) This specification shall be done in accordance the City of Winnipeg's Standard Construction Specification CW 3110 – "Sub-Grade, Sub-Base and Base Course Construction" and as per SCD-648.
- (b) Excavation shall be understood to include all removal of existing insitu material necessary to achieve finished grade and as indicated on Drawings, all in accordance with E13.
- E18.2.2 Construction Methods
- (a) Excavation shall be performed as outlined in CW 3310 – Item 3.2 – "Excavation".
- (b) If any pavement exists at the limits of the designated area of removal, these shall be saw cut for the full depth of the pavement prior to the demolition and removal

operations. All costs in connection with saw cutting are incidental and shall be included in the unit price bid for excavation.

- (c) All excavated material shall be removed, hauled and disposed of off-site to the satisfaction of the Contract Administrator.

### E18.3 Sub-base Compaction

#### E18.3.1 Description

- (a) Sub grade compaction shall be done in accordance with City of Winnipeg's Standard Construction Specification CW 3110 – "Sub-Grade, Sub-Base and Base Course Construction".

#### E18.3.2 Construction Methods

- (a) Sub-grade compaction shall be performed as outlined in CW 3110 item 3.3 "Preparation of Sub-Grade and Placement of Sub-Base Material".
- (b) Sub-grade shall be free of any fibrous organics, softened and disturbed soil. The prepared sub-grade shall be proof rolled with a heavy sheep's foot roller (min 25 passes) and inspected by the Contract Administrator to detect for any soft spots prior to the placement of overlying granular fills.

### E18.4 Geotextile Fabric

#### E18.4.1 Description

- (a) Geotextile Fabric shall be placed in accordance with City of Winnipeg's Standard Construction Specification CW 3130 "Supply and Installation of Geotextile Fabrics".

#### E18.4.2 Materials

- (a) The separation/ reinforcement geotextile fabric shall be **Non-Woven** and conform to the Products Approved as listed in City of Winnipeg Specification for Approved Products for Surface Works.

#### E18.4.3 Construction Methods

- (a) Separation/ Reinforcement geotextile fabric shall be installed as outlined in CW 3110 item 3.1 "Separation/Reinforcement Geotextile Fabric".

### E18.5 Crushed limestone sub-base course material

#### E18.5.1 Description

- (a) Crushed limestone sub-base material shall be supplied and installed in accordance with City of Winnipeg's Standard Construction Specification CW 3110 "Sub-Grade, Sub-Base and Base Course Construction".

#### E18.5.2 Materials

- (a) Sub Base: 50mm (2") down crushed limestone as per Drawing SCD-648.

#### E18.5.3 Construction Methods

- (a) Crushed limestone sub-base material shall be supplied and installed as outlined in CW 3110 item 3.4 "Placement of Sub-Base Material with Geotextile Fabric".
- (b) All limestone sub-base material shall be placed and compacted as specified to a finished thickness as shown on the drawings.

### E18.6 Crushed Limestone Base Course Material

#### E18.6.1 Description

- (a) Crushed limestone base material shall be supplied and installed in accordance with City of Winnipeg's Standard Construction Specification CW 3110 "Sub-Grade, Sub-Base and Base Course Construction".

E18.6.2 Materials

- (a) Base course material shall be 20mm (3/4") down crushed limestone.

E18.6.3 Construction Methods

- (a) Crushed limestone base material shall be supplied and installed as outlined in CW 3110 item 3.4 "Placement of Sub-Base Material with Geotextile Fabric".
- (b) All limestone base course material shall be placed and compacted as specified to finished thickness as shown on the drawings.

E18.7 Asphaltic Pavement

E18.7.1 Description

- (a) Asphaltic Concrete shall be supplied and installed in accordance with City of Winnipeg Standard Construction Specification CW 3410 "Asphaltic Concrete Pavement Works".

E18.7.2 Materials

- (a) Asphaltic Concrete shall be Type II as specified and to a thickness of 75mm (3") as shown on the Drawings.

E18.7.3 Construction Methods

- (a) Asphaltic Concrete shall be supplied and installed in accordance with the lines, grades and thickness shown on the Drawings and to City of Winnipeg Construction Specification CW 3410. Asphalt shall be placed in one lift.

E18.8 Crack Sealing

- (a) As a warranty requirement, the Contractor shall rout and seal any and all cracks which may appear during the one-year warranty period. Crack sealing shall conform to the requirements of City of Winnipeg Standard Construction CW 3250.
- (b) No separate payment will be made for this item as it is considered a warranty issue and shall fall under G.C.13- Warranty.

E18.9 Quality Control for Hard Surfaced Areas

- (a) Further to Section 10, Quality Control, of CW 3110 and CW 3410, the Contract Administrator may obtain a qualified independent testing lab to conduct tests on materials to determine the acceptability of the sub-grade, sub-base, base course and asphaltic concrete as placed by the Contractor in accordance with the requirements of this Specification.
- (b) The Contractor shall not proceed with each granular fill placement or asphalt installation until test results have been reviewed and approval to proceed is granted by the Contract Administrator.
- (c) The Contract Administrator will conduct a survey of the operation to verify installation of specified layer thickness.
- (d) Non-conformity with the specified test requirements or compacted layer thickness will constitute sufficient grounds for rejection of the Work.

E18.10 Method of Measurement and Basis of Payment

E18.10.1 Method of Measurement shall be as follows:

- (a) Asphalt Path will be measured on a square metre basis for:
  - (i) "Renovated Asphalt Path", and
  - (ii) "New Asphalt Path" on Form B: Prices.

E18.10.2 Basis of Payment shall be as follows:

- (a) Asphalt Path will be paid for at the Contract Unit Prices. The amount to be paid for shall be the total number of units, as indicated on Form B: Prices. This price shall be

full payment for supplying all labour, equipment and materials, and performing all operations herein described and all other items incidental to the Work and as accepted by the Contract Administrator.

## E19. SITE FURNITURE

### E19.1 Description

E19.1.1 This specification shall cover the **pick-up** and installation of one (1) waste receptacle, three (3) benches (2 with backs, one backless), and two (2) picnic tables (1 accessible, 1 standard).

E19.1.2 The Contractor shall furnish all labour, materials, equipment and services necessary to complete the Work as shown on Drawings and specified herein.

### E19.2 Materials

E19.2.1 All materials supplied under this specification shall be of a type approved by the Contract Administrator, and shall be subject to inspection and testing by the Contract Administrator.

E19.2.2 Site Furniture shall be:

- (a) Waste Receptacle – Metal Slat Type - black, as per SCD-119, **Product # 52501063** (metal slat WR) and **Product # 52501058** (Wire Basket) or substitute approved in accordance with B10.
- (b) Bench with Back – Tache Style Composite Bench with Arm Rests – black metal, as per SCD-121A, **Product # 52501085**, or substitute approved in accordance with B10.
- (c) Backless Bench – Tache Backless Bench Composite With Arms – black metal, as per SCD-121C, **Product # 52501086**, or substitute approved in accordance with B10.
- (d) Accessible Picnic Table – Tache Style Wheelchair Metal Frame Picnic Table, as per SCD-122A, with wood slats and cedar tone painted finish and black frame, or substitute approved in accordance with B10.
- (e) Standard Picnic Table – Tache Style Metal Frame Picnic Table, as per SCD-122, with wood slats and cedar tone painted finish and black frame, or substitute approved in accordance with B10.

- (i) Contact for Waste Receptacles and Benches, and Park Sign:

Aaron Lennon @ 986-5505  
Supervisor of Central Repair/Manufacturing Facility  
City of Winnipeg  
Fleet Management Agency Division  
Public Works Department  
215 Tecumseh St  
Winnipeg. MB R3E 3S4  
Email: [ALennon@winnipeg.ca](mailto:ALennon@winnipeg.ca)

- (ii) Contact for Picnic Table:

Todd Hendry @ 204-470-4834 or Brian Mayer @ 204-470-7747 or Marc Laurin @ 204-479-5489  
Centralized Park Services  
City of Winnipeg  
960 Thomas Ave.  
Winnipeg MB R2L 2E1  
Email: [THendry@winnipeg.ca](mailto:THendry@winnipeg.ca), [BMayer@winnipeg.ca](mailto:BMayer@winnipeg.ca),  
[MLaurin@winnipeg.ca](mailto:MLaurin@winnipeg.ca)

### E19.3 Construction Methods

- (a) All Work is to be located and installed in accordance with the Drawings, SCDs, and following manufacturer's instructions, using approved non-rusting, vandal resistant fasteners to ensure solid, durable, finished work suitable for the purpose intended. Fasteners and assembly hardware shall be incidental to the Work;
- (b) All furnishings and fixtures to be installed plumb and true to correct elevations and location, as directed by the Contract Administrator. The Contractor shall confirm proposed locations of all site furnishings with Contract Administrator prior to installation;
- (c) All furnishings and fixtures to be carefully handled so that no parts will be bent, broken or otherwise damaged. Hammering is prohibited;
- (d) Install as per manufacturer's instructions and the attached drawings.
- (e) Picnic Tables shall be installed with two (2) duckbill anchors each.

### E19.4 Method of Measurement and Basis of Payment

#### E19.4.1 Method of Measurement shall be as follows:

- (a) Site Furniture will be measured on a per unit basis for the following items:
  - (i) "Pick up and install Benches",
  - (ii) "Pick up and install Picnic Tables", and
  - (iii) "Pick up and install Waste Receptacle", on Form B: Prices.

#### E19.4.2 Basis of Payment shall be as follows:

- (a) Site Furniture will be paid for at the Contract Unit Prices. The amount to be paid for shall be the total number of units, as indicated on Form B: Prices. This price shall be full payment for supplying all labour, equipment and materials, and performing all operations herein described and all other items incidental to the Work and as accepted by the Contract Administrator.

## **E20. LOG STEPPING POSTS**

### E20.1 Description

E20.1.1 This specification shall cover the pickup and installation of log stepping posts to be located in Playsand safety surfacing within play area as indicated on the Drawings.

### E20.2 Materials

#### E20.2.1 Logs

- (a) Logs shall be reviewed and approved by Contract Administrator prior to delivery to site.
- (b) They shall be between the sizes of 230mm and 350mm diameter, by 1.2m to 1.6m lengths.
- (c) Heights of logs above grade shall vary between 300mm and 600mm.
- (d) Logs shall have a minimum 1.8 offset from concrete edging.
- (e) Acceptable species include oak, elm or ash.
- (f) Debarked, sanded smooth and chamfered top as show on Drawings.
- (g) All ends and cuts shall be treated with preservation before being secured.
- (h) Cutting of treated materials will be done by the supplier before treatment. However, field cutting, fitting, and matching may be required as indicated on the drawings. The contractor shall make the necessary cuts and holes in a true and workmanlike manner. The contractor shall seal all cuts with an approved preservative to match lumber.

- (i) Name and type of preservative shall be reviewed and approved by Contract Administrator prior to applying to logs.

E20.2.2 Granular Base Course

- (a) Granular base course material shall consist of 20mm down crushed limestone and shall conform to CW3110 for crushed limestone base course material.

E20.3 Construction Methods

E20.3.1 Lumber brought to the site shall be carefully handled to avoid damaging the outer fibres. Dropping of the timber from the back of the truck to the ground will not be allowed.

E20.3.2 Special tools and slings shall be employed to prevent the penetration of bruising of the treated surfaces. The use of tongs, chains, or sharp tools for handling purposes will not be allowed.

E20.3.3 The lumber shall be stored in an orderly fashion and must be stacked in neat regular piles. The bottom pieces in each pile shall be placed on blocks to prevent bending of the timber.

E20.3.4 Stake and layout logs as coordinate with Contract Administrator on site and as indicated in Drawings. Layout shall be checked and approved by Contract Administrator prior to construction.

E20.3.5 Subgrade to be compacted to 95% Standard Proctor Density.

E20.3.6 Backfill trench with granular base material as per Drawing. Position the post and hold securely in place in the hole, place granular base course backfill material and compact around the post to within 75mm of the finished grade. After the granular material has been satisfactorily compacted, 75mm of compacted limestone base course is to be placed on top.

E20.3.7 All steppers thoroughly tamped and granular mounded for future settling and drainage way from steppers.

E20.3.8 Log Steppers to be set plumb with no gap between steppers. Contractor shall support features while sufficient compacted granular fill is installed to level the features.

E20.3.9 Ensure logs are stable and unmovable once placed.

E20.3.10 All posts thoroughly tamped and granular mounded for future settling and drainage away from post.

E20.3.11 Edge of logs to be min. 1.8m from concrete edging.

E20.4 Method of Measurement and Basis of Payment

E20.4.1 Method of Measurement shall be as follows:

- (a) Log Stepping Posts will be measured on a per unit basis for the following item: "Log Stepping Posts" on Form B: Prices.

E20.4.2 Basis of Payment shall be as follows:

- (a) Log Stepping Posts will be paid for at the Contract Unit Prices. The amount to be paid for shall be the total number of units, as indicated on Form B: Prices. This price shall be full payment for supplying all labour, equipment and materials, and performing all operations herein described and all other items incidental to the Work and as accepted by the Contract Administrator.

**E21. CLIMBING BOULDERS**

E21.1 Description

E21.1.1 This specification shall cover the installation of climbing boulders as indicated on Drawings.

E21.2 Materials

- E21.2.1 Geotextile Fabric shall be as per Drawing.
- E21.2.2 Granular shall be as per Drawing.
- E21.2.3 Climbing Boulders:
- (a) Rock shall have a smooth edges and corners and a minimum size range of 600mm (2') x 900mm (3') x 900mm (3').
- E21.3 Construction Methods
- E21.3.1 Excavate and backfill with compacted granular base around boulders. Tamper down in 150mm lifts and compact to 95% SPD. Supply and Installation of granular base is incidental to the Work in this section.
- E21.3.2 Boulders shall have a minimum of 1.8m clear area from concrete edging.
- E21.3.3 Safety surfacing shall be installed by play equipment contractor soon afterwards. If the safety surfacing cannot be installed immediately orange safety fencing shall be installed around the boulder play area until such time as it can be installed.
- E21.4 Method of Measurement and Basis of Payment
- E21.4.1 Method of Measurement shall be as follows:
- (a) Climbing Boulders shall be measured on a per unit basis for: "Boulders", on Form B: Prices.
- E21.4.2 Basis of Payment shall be as follows:
- (a) Climbing Boulders will be paid for at the Contract Unit Prices. The amount to be paid for shall be the total number of units, as indicated on Form B: Prices. This price shall be full payment for supplying all labour, equipment and materials, and performing all operations herein described and all other items incidental to the Work and as accepted by the Contract Administrator.
- E22. POST FENCING**
- E22.1 Description
- E22.1.1 This Specification shall cover the supply and installation of post and chain fencing as shown on drawings and SCD-105A. One existing post as well as one new post shall create a construction entry point. In this location, the posts shall be placed 3m apart with a chain connection in between that is lockable.
- E22.2 Materials
- E22.2.1 Materials required for the supply / installation of the wooden bollards include
- (a) Granular backfill shall be 19mm diameter crushed limestone.
  - (b) Wood posts shall be green pressure treated ACQ pine, size shown on drawings.
- E22.3 Construction Methods
- E22.3.1 Install bollard in 300mm diameter holes, minimum 900mm below grade, and backfill with compacted earth material in 150 mm lifts, installed completely up to finish grade. Surplus earth to be legally disposed of.
- E22.3.2 All posts thoroughly tamped and earth mounded approximately 100mm at each post for future settling.
- E22.3.3 Fence posts are to follow the natural contour of the land except for small undulations which would tend to reduce the aesthetic appearance of the finished product

E22.3.4 Installation of wood bollards along the City public lanes can be installed with a Skid-Steer mounted type of auger, only if the Skid-Steer wheels remain on City concrete lane. Plumb top of posts level.

E22.4 Method of Measurement and Basis of Payment.

E22.4.1 Method of Measurement shall be as follows:

- (a) Post and Chain fencing will be measured on a per unit basis for:
  - (i) "Post Fencing" on Form B: Prices

E22.4.2 Basis of Payment shall be as follows:

- (a) Cost for bollards is to be included in the Unit Price Forms and will be paid for on a per unit basis and shall include all costs for the wood bollard, excavation, backfill and removal of excavated materials. Payment for Work specified under this section shall be paid for at the Unit Price, measured on a per unit basis for the Items of Work listed below, which price shall include all costs for the wood bollard,

## **E23. SOIL AND SOD**

E23.1 Description

E23.1.1 This Specification shall amend and supplement the most up to date revisions of City of Winnipeg Specifications CW 3510, CW 3520 and CW 3540. The Contractor shall install mineral sod and a minimum 75mm compacted thickness of topsoil, as required.

E23.1.2 The Contractor shall install topsoil and sod over all graded areas including; around the perimeter of new play area, as well as over old play areas.

E23.1.3 Areas to be Sodded are to be laid out on Site and approved by the Contract Administrator before commencing Work. Work outside the limit approved by the Contract Administrator will not be measured and will not be paid for under this section but considered incidental to the Work. Such incidental items that will not be measured include but are not limited to topsoil and sod placed at the edge of new paving. Incidental Site restoration shall conform to the same Specifications.

E23.1.4 Where edges of excavation abut existing turf those edges are to be cut with a sod cutter prior to excavation.

E23.1.5 Restoration shall be achieved using topsoil and sod unless otherwise directed by the Contract Administrator.

E23.1.6 Thirty (30) day maintenance period on sod will commence at Total Performance and acceptance.

E23.2 Method of Measurement and Basis of Payment

E23.2.1 Method of Measurement shall be as follows:

- (a) Soil and Sod will be measured on a square metre basis for: "Topsoil and Sod" on Form B: Prices.

E23.2.2 Basis of Payment shall be as follows:

- (a) Soil and Sod will be paid for at the Contract Unit Prices. The amount to be paid for shall be the total number of units, as indicated on Form B: Prices. This price shall be full payment for supplying all labour, equipment and materials, and performing all operations herein described and all other items incidental to the Work and as accepted by the Contract Administrator.

## **PLAY EQUIPMENT**

## **E24. PLAY EQUIPMENT**

- E24.1 This specification shall cover the supply and installation of the Play Equipment as listed below and specified herein.
- E24.2 The Contractor shall furnish all labour, materials, equipment and services necessary to complete the Work according to the drawings and specifications.
- E24.3 The Contractor shall obtain all approvals including permit if required.
- E24.4 **Play Area:**
- (a) Play area to be designed for children aged 2-12 with a minimum of one playstructure along with independent components that are geared towards these ages. **The playstructure must have a ramp that leads to the Playground Entry Platform. The ramp shall start at a height of 0.3m above grade.**
  - (b) **The site is an area with high vandalism and thus plastic, glass components, and moving parts must be minimized, and only steel slides will be allowed.**
  - (c) Play equipment shall allow for visibility through the play area as much as possible.
  - (d) **Play equipment should follow a Firehall/ Firefighter theme in tribute to the old firehall located next to it.**
  - (e) Play equipment must provide the following play activities:
    - (i) Sensory & Imaginative Play;
    - (ii) Climbing;
    - (iii) Balancing;
    - (iv) Motion; and
    - (v) Sliding.
  - (f) The design submission shall be evaluated as per B21.
- E24.5 If colour is a feature of posts, top caps and panels, the Contract Administrator shall have the ability to modify specified colours from the proposed design after Contract Award. If the price of the equipment in the Bid Submission is subject to the colours of the proposed design, this must be indicated in the Bid Submission.
- E24.6 Components which are **unacceptable** are the following:
- (a) Wooden structures;
  - (b) Tube (enclosed) slides and enclosed crawl tubes;
  - (c) Play panels with many small moving parts;
  - (d) Talk Tubes;
  - (e) Glass Components;
  - (f) Barrel rollers; and
  - (g) Large number of plastic components.
- E24.7 Components which are generally **not accepted but may be considered** are the following:
- (a) Cable rides;
  - (b) Sand diggers;
  - (c) Merry-go-rounds; and
  - (d) Tire Swings.
- E24.8 Playstructures
- E24.8.1 General Description

- (a) If a Playstructure is specified, this specification shall cover the supply and installation of it.
- (b) Play equipment shall be installed in the play areas as shown on the attached Drawing. The play equipment and their safety zones should fit into the proposed play areas. Efficiency and good use of space will be considered in the evaluation of submissions.

#### E24.8.2 Materials

- (a) Posts / Caps
  - (i) All posts shall be a minimum 5" O.D. round or 4" square tubing for a post and deck structure.
  - (ii) 3.5 " O.D. round or 3.0" square tubing will be permitted in circumstances where a multi-deck structure has decks of varied heights which are all under 4', or for structures with 2 decks or less.
  - (iii) All posts shall be fabricated from either aluminium (0.125" (11ga) min. wall thickness) or galvanized steel (0.120" (11 ga) min. wall thickness) tubing. All fabrication cuts, drill holes and weld joints shall be sprayed with a corrosion resistant coating. The bottom end of the posts is to be sealed with a moisture barrier.
  - (iv) In the case of a deckless structure, a minimum size of 2 3/8" O.D. round posts fabricated out of steel or aluminum is acceptable.
  - (v) Top caps shall be made of steel construction and shall be factory installed and secured in place with tamper proof, self-sealing rivets. Plastic top caps will be accepted if made of solid construction (hollow caps not accepted).
  - (vi) If painted colour is a feature of posts and top caps, it shall be a baked-on polyester powder coating. The powder coating finish shall meet or exceed ASTM standards for hardness, adhesion, impact and salt spray resistance.
- (b) Decks (if applicable)
  - (i) All decks shall be manufactured from vinyl-coated perforated steel or a steel core composite. Deck heights may vary to a maximum height of 6'.
- (c) Clamping System
  - (i) All deck, rail and play component clamping systems shall be fabricated from zinc plated, galvanized steel, stainless steel or aluminum. Tamper proof, corrosion resistant fasteners shall be used to retain clamping systems.
- (d) Handrails, Safety Rails and Handloops (if applicable)
  - (i) All handrails, safety rails and handloops shall be fabricated using a minimum of 15/16" (24mm) O.D. with a 120" wall thickness steel tubing. After all fabrication activities have occurred including end cuts, drill holes, bends and weld joints, all components shall be hot dipped galvanized.
  - (ii) Smooth all cut edges and weld joints prior to hot dip galvanizing and ensure that all tubing is free from burrs, cracks, defects and other imperfections.
- (e) Hardware
  - (i) All fasteners shall be socketed and tamper proof in design, and either carbon steel plated with zinc/nickel and iridescent chromate finish or stainless steel.
  - (ii) All necessary hardware shall be provided.
- (f) Poly Components
  - (i) Poly components such as slides and hoods shall be fabricated from U.V. stabilized, rotationally molded linear low-density polyethylene.
  - (ii) Poly components such as play panels shall be fabricated from compression molded solid colour, U.V. stabilized, high-density polyethylene.
- (g) Slides (if applicable)

- (i) **Only stainless steel slides are acceptable with North or east orientation.**
- (h) Each playstructure shall have kick plates and hand loops as required to meet the most recent Canadian Standards Association Standards.
- (b) Installation
  - (a) Play equipment shall be installed as per manufacturer's specifications and in accordance with the most recent Canadian Standards Association Standards.
  - (b) One play equipment installer on site, at minimum, must be a valid Canadian Certified Playground Inspector.**
  - (c) All posts and other vertical items shall be plumb and true to vertical, if so designed.
  - (d) All decks shall be level, if so designed.

#### E24.9 Independent Components

##### E24.9.1 General Description

- (a) The Contractor shall furnish all labour, materials, equipment and services necessary to complete the Work according to the specifications.
- (b) This specification shall cover the supply and installation of Independent Components as specified herein.
- (c) Independent Components shall be installed as per the proposed design, as the proposed budget will allow.
- (d) Independent Components shall be installed in the available areas as shown on Drawings. The Components and their safety zones must fit into the proposed play area.

##### E24.9.2 Materials

- (a) All materials shall be structurally sound and suitable for safe play. Durability shall be ensured on all parts and materials.
- (b) There shall be a minimum (or no) amount of hollow plastic components. Solid plastic is acceptable.
- (c) There shall be a minimum amount of solid elements which limit visibility through the Site.
- (d) Fasteners
  - (i) All hardware shall be tamper-proof in design and requiring special tools. It shall be either carbon steel plated with zinc/nickel and iridescent chromate finish or stainless steel. All necessary hardware and tools shall be provided.
- (e) Finishes
  - (i) Finishes shall meet or exceed ASTM standards for hardness, adhesion, impact and salt spray resistance. All fabrication cuts, drill holes and weld joints shall be sprayed with a corrosion resistant coating.
- (f) Slides
  - (i) If an independent slide is proposed, stainless steel is preferred. If other slides are proposed on the Site one may be plastic. North or east orientation preferred. If independent slide over 4' high is proposed, support posts must be minimum 5"O.D.
  - (ii) Tube (enclosed) slides and plastic spiral slides will not be accepted.
- (g) Foundations
  - (i) Shall be as per E27.

#### E24.10 Method of Measurement and Basis of Payment

E24.10.1 Method of Measurement shall be as follows:

- (a) Play Equipment shall be measured on a lump sum basis for:
  - (i) "Play Equipment" on Form B: Prices

E24.10.2 Basis of Payment shall be as follows:

- (a) Play Equipment will be paid for at the Contract Unit Prices. The amount to be paid for shall be the total number of units, as indicated on Form B: Prices. This price shall be full payment for supplying all labour, equipment and materials, and performing all operations herein described and all other items incidental to the Work and as accepted by the Contract Administrator.

## **E25. SWING SET**

E25.1 General Description

E25.1.1 The Contractor shall furnish all labour, materials, equipment and services necessary to complete the Work according to the specifications.

E25.1.2 This specification shall cover the supply and installation of one (1) complete swing standard as specified herein:

- (a) Three Leg Heavy Duty Swing Frame, 2.4m ( 8ft.) high, 2-Bay, complete with two (2) slash-proof rubber, enclosed infant seats, and two (2) slash-proof rubber belt seat, heavy-duty chain, swing hangers and hammer locks / bolt links.

E25.2 Materials

E25.2.1 Topbeam

- (a) All topbeams shall be fabricated from **3 1/2" O.D. 8 gauge (minimum), RS40 galvanized steel pipe with anti-wrap**. All fabrication cuts, drill holes and weld joints shall be sprayed with a corrosion resistant coating.

E25.2.2 Legs

- (a) All legs shall be fabricated from 2 3/8" O.D. 10 gauge, RS40 galvanized steel pipe. All fabrication cuts, drill holes and weld joints shall be sprayed with a corrosion resistant coating. The bottom end of the posts is to be sealed with a moisture barrier.

E25.2.3 Yoke Clamps

- (a) All yoke clamps shall be either one piece construction and fabricated from 8 gauge, RS40 galvanized steel pipe or two piece, compression clamping cast aluminum or galvanized metal complete with tamper-proof hardware.

E25.2.4 Swing Hangers

- (a) All swing hangers shall be fabricated from galvanized malleable iron and have oil impregnated bearings pressed in.

E25.2.5 Swing Chain

- (a) All swing chain shall be 4/0 straight link, galvanized steel.

E25.2.6 Enclosed Infant (Bucket) Seats

- (a) All enclosed infant seats shall be moulded of U.V. stabilized, high quality, rubber with a tempered stainless steel reinforcement plate insert moulded inside, rendering the seats slashproof. Infant seats shall be fully enclosed to prevent slipping out and provide extra lower back support.

E25.2.7 Belt Seats

- (a) All belt seats shall be moulded of U.V. stabilized, high quality, rubber with a tempered stainless steel reinforcement plate insert moulded inside, rendering the

seats slashproof. The perimeter shall be moulded to form a blunt, impact absorbing edge.

E25.2.8 Hardware

- (a) All fasteners shall be tamper proof in design, requiring special tools. The fasteners shall be either carbon steel plated with zinc/nickel and iridescent chromate finish or stainless steel.

E25.2.9 Concrete Foundations

- (a) Post shall be installed into a concrete footing the composition of which is detailed in E27.

E25.3 Installation

E25.3.1 Installation shall be in accordance with Manufacturers specifications.

E25.3.2 Top rail is to be level and posts securing anchored in concrete.

E25.3.3 Swing seats shall not be installed until the protective surfacing (in accordance with E16) has been installed

E25.4 Method of Measurement and Basis of Payment

E25.4.1 Method of Measurement shall be as follows:

- (a) Swing Set will be measured on a per unit basis for: "Swing Set" on Form B: Prices.

E25.4.2 Basis of Payment shall be as follows:

- (a) Swing Set will be paid for at the Contract Unit Prices. The amount to be paid for shall be the total number of units, as indicated on Form B: Prices. This price shall be full payment for supplying all labour, equipment and materials, and performing all operations herein described and all other items incidental to the Work and as accepted by the Contract Administrator.

**E26. BOWL SWING**

E26.1 General Description

E26.1.1 The Contractor shall furnish all labour, materials, equipment and services necessary to complete the Work according to the specifications.

E26.1.2 This specification shall cover the supply and installation of one (1) bowl swing.

- (a) Bowl Swing's that shall be acceptable include either Landscape Structure's "Oodle Swing" or Burke's "Volito", or approved equal as per B10.

E26.2 Installation

E26.2.1 Installation shall be in accordance with Manufacturers specifications.

E26.2.2 Top rail is to be level and posts securing anchored in concrete.

E26.2.3 Swing seat shall not be installed until the protective surfacing (in accordance with E16) has been installed.

E26.3 Method of Measurement and Basis of Payment

E26.3.1 Method of Measurement shall be as follows:

- (a) Bowl Swing will be measured on a per unit basis for: "Bowl Swing" on Form B: Prices.

E26.3.2 Basis of Payment shall be as follows:

- (a) Bowl Swing will be paid for at the Contract Unit Prices. The amount to be paid for shall be the total number of units, as indicated on Form B: Prices. This price shall be full payment for supplying all labour, equipment and materials, and performing all

operations herein described and all other items incidental to the Work and as accepted by the Contract Administrator.

## **E27. FOUNDATIONS**

### **E27.1 General Description**

E27.1.1 All playground equipment posts, bases and anchors are to be set in concrete footings or piles to ensure stability and prevent frost heaving. An alternative to concrete footings or piles that may be approved includes a welded and secured rail mounting system. The current Standard Construction Specifications of the City of Winnipeg, CW 2160 –latest revision - Concrete to be used in Underground Works, is to be utilized in the installation of the concrete works for all below ground components.

### **E27.2 Materials**

E27.2.1 The specific concrete requirements shall be:

- (a) Sulfate resistant, Type 50 Cement;
- (b) 28 day compressive strength of 30 Mpa;
- (c) maximum aggregate size of 20mm, nominal;
- (d) slump 80 +/- 20mm;
- (e) maximum water/cement ratio 0.49.

### **E27.3 Installation**

E27.3.1 All posts and supports shall be centred in the concrete footing such that there is a complete collar of concrete around each post and support. Where posts are not perfectly centred there should be a minimum of 2" concrete at any point around the post.

E27.3.2 All concrete footings for play equipment shall be a **minimum of 3' depth**, or in accordance with Manufacturer's specifications, whichever is greater.

### **E27.4 Method of Measurement and Basis of Payment**

E27.4.1 Method of Measurement shall be as follows:

- (a) Foundations shall be incidental to the measurement of Play Equipment, Swing Set and Bowl Swing listed above and as shown on Form B: Prices.

E27.4.2 Basis of Payment shall be as follows:

- (a) No separate payment shall be made for play equipment foundations.

## **E28. MAINTENANCE KITS**

E28.1 All play equipment shall include the supply of maintenance kits. Maintenance kits shall include maintenance manuals, complete manufacturer's parts lists, touch-up paint, PVC repair paint, 10% extra of each bolt, washer and any other hardware utilized on the play equipment, and all special tools necessary for assembly and maintenance.

E28.2 There shall be no payment for the maintenance kits.