

## GENERAL NOTES:

1. PROVIDE SEPARATE PRICE FOR PRODUCTS AND INSTALLATION DETAILED ON THIS DRAWING.

## NOTES:

K.E.

- 1. PROVIDE WEATHERPROOF, STEEL, HINGED JB, PENTAIR CAT. NO. A12108CNHF C/W LOCKABLE DOOR. JB SHALL HAVE BACKBOARD FOR SCREW-MOUNTING AUXILIARY EQUIPMENT WITHIN ENCLOSURE. MOUNT JB TO INTERIOR FLANGE ON SURFACE OF STEEL I-BEAM.
- PROVIDE 100W ELECTRIC HEATER, PENTAIR HOFFMAN CAT. NO. DAH1001A. HEATER SHALL BE MOUNTED TO BACKBOARD WITHIN UNIT. WIRE AND CONNECT TO CIRCUIT D-5.
- 3. PROVIDE LUMENPULSE LUMENTOUCH 2.0 DMX LIGHTING CONTROLLER C/W 6V DC POWER SUPPLY. MOUNT TO STANDARD SINGLE-GANG JUNCTION BOX ON BACKBOARD WITHIN ENCLOSURE. 120/6V POWER SUPPLY SHALL BE MOUNTED IN JB, OR ON BACKBOARD.
- PROVIDE LUMENPULSE CBX-DS LINE-VOLTAGE CONTROL BOX. MOUNT CONTROL BOX TO INTERIOR FLANGE ON SURFACE OF STEEL I-BEAM.

- 5. UTILIZE LUMENPULSE LOGLC-UL-STD-X-BK LEADER CABLE FROM CBX-DS TO FIRST LUMINAIRE. ELECTRICAL SUBCONTRACTOR SHALL DETERMINE LENGTH OF CABLE PRIOR TO ORDERING.
- 6. DMX CONTROL WIRING SHALL BE RUN IN 1/2" (16mm) EMT CONDUIT FROM LUMENTOUCH 2.0 TO CBX-DS.
- 7. RUN SEPARATE POWER SUPPLY FOR EACH ENCLOSURE. ALL POWER FOR DMX CONTROL SYSTEM AND ASSOCIATED LUMINAIRES SHALL CONNECT TO CIRCUIT D-5.
- 8. PROVIDE 13" (41mm) CONDUIT FROM CBX-DS BOX TO LUMINAÎRES. DMX COLOUR CHANGING LUMINAIRES SHALL BE LUMENPULSE CAT. NO. LOG-HO-120-48-30K-10X60 XPE2-NO\_R&D. PROVIDE LUMENPULSE LOGJC-UL-STD-1-BK JUMPER CABLES BETWEEN LUMINAIRES.
- CONTRACTOR SHALL INCLUDE PROGRAMMING OF LUMENTOUCH 2.0 IN CONTRACT. COORDINATE TIMES OF OPERATION WITH CITY OF WINNIPEG PRIOR TO START OF DEVICE PROGRAMMING.

