

654-2017 ADDENDUM 1

SUPPLY, DELIVERY AND MAINTENANCE OF RADIO SERVICE MONITORS

URGENT

PLEASE FORWARD THIS DOCUMENT TO WHOEVER IS IN POSSESSION OF THE REQUEST FOR PROPOSAL

ISSUED: November 8, 2017
BY: Olawale D. Jegede
TELEPHONE NO. (204) 986-8363

THIS ADDENDUM SHALL BE INCORPORATED INTO THE REQUEST FOR PROPOSAL AND SHALL FORM A PART OF THE CONTRACT DOCUMENTS

Template Version: Ar20120228

Please note the following and attached changes, corrections, additions, deletions, information and/or instructions in connection with the Request for Proposal, and be governed accordingly. Failure to acknowledge receipt of this Addendum in Paragraph 9 of Form A: Proposal may render your Proposal non-responsive.

PART E – SPECIFICATIONS

Revise: E2.2.1 (d) (iv) to read:

E2.2.1 (d) (iv) **Sensitivity of < - 113 dBm** (for 10 dB SINAD, FM, 25 kHz, 1kHz rate, 6kHz FM Deviation, 300 Hz to 3.4 kHz AF Filter, Pre-amp ON).

Revise: E2.2.1(i) to read:

E2.2.1(i) Environmental/Safety: Shall

- ◆ **Have operating temperature 0 to 50° C and Storage temperature of -40 to +71° C**, shock and vibrations of 30G Shock at 5-500 Hz random vibrations.
- ◆ Comply with the safety standards UL 61010B-1, EN 61010-1, and CSA C22.2 No. 61010-1.
- ◆ Maximum warm-up time of 15 minutes for every measurement to be within specifications.

Delete E2.4(a)(vi)

Revise: E2.4(a)(viii) to read:

E2.4(a)(viii) Environmental/Safety: Shall

- ◆ **have operating temperature of 0°C to 50°C and storage temperature of -30°C to 80°C.**
- ◆ **have a battery that complies** with the safety standards CE/ UL2054 / UL1642 / FCC IEC 62133 / EN6095 / ROHS UN 38.3 / PSE / RCM.
- ◆ have a maximum warm-up time of 15 minutes for every measurement to be within specifications.