

EXTERIOR WALL TYPES

- EW1** METAL CLADDING ON WOOD STUD FRAMING
- 22MM PREFINISHED 22 GA. CORRUGATED METAL CLADDING (1 COLOUR)
 - 16x38MM VERTICAL FURRING STRIPS @ 406 MM O.C.
 - SPUN POLYOLEFIN AIR/WATER RESISTIVE BARRIER MEMBRANE
 - 16MM CONSTRUCTION GRADE PLYWOOD EXTERIOR SHEATHING
 - 140MM WOOD STUD FRAMING @ 406MM O.C.
 - 16MM G1S PLYWOOD INTERIOR SHEATHING TO FULL WALL HEIGHT; CLEAR SEALED

- EW2** CLADDING ON WOOD STUD FRAMING
- 152MM HORIZONTAL TONGUE & GROOVE DOUGLAS FIR SIDING; CLEAR SEALED
 - 16x38MM VERTICAL FURRING STRIPS @ 406 MM O.C.
 - SPUN POLYOLEFIN AIR/WATER RESISTIVE BARRIER MEMBRANE
 - 16MM CONSTRUCTION GRADE PLYWOOD EXTERIOR SHEATHING
 - 140MM WOOD STUD FRAMING @ 406MM O.C.
 - 16MM G1S PLYWOOD INTERIOR SHEATHING TO FULL WALL HEIGHT; CLEAR SEALED

- EW2b** CLADDING ON WOOD STUD FRAMING (INSULATED)
- 152MM HORIZONTAL TONGUE & GROOVE DOUGLAS FIR SIDING; CLEAR SEALED
 - 16x38MM VERTICAL FURRING STRIPS @ 406 MM O.C.
 - SPUN POLYOLEFIN AIR/WATER RESISTIVE BARRIER MEMBRANE
 - 16MM CONSTRUCTION GRADE PLYWOOD EXTERIOR SHEATHING
 - 140MM WOOD STUD FRAMING @ 406MM O.C. (FILL CAVITY W/ 140mm MINERAL WOOL BATT INSULATION)
 - 6 MIL POLYETHYLENE VAPOUR BARRIER MEMBRANE
 - 16MM G1S PLYWOOD INTERIOR SHEATHING TO FULL WALL HEIGHT; CLEAR SEALED

- EW3** POLYCARBONATE CLADDING ON WOOD STUD FRAMING
- 22MM CORRUGATED POLYCARBONATE CLADDING
 - 16MM X 38MM (OR AS NOTED) PT WD FURRING
 - WOOD TRUSS FRAMING

- EW4** SLAB ON GRADE CURB
- CEMENT PARGING ON GALVANIZED METAL LATH
 - BITUMINOUS DAMPROOFING
 - REINFORCED CONCRETE SLAB ON GRADE (REFER TO STRUCTURAL)

INTERIOR WALL TYPES

- IW1** G1S PLYWD ON WOOD STUD FRAMING
- 16MM G1S PLYWOOD INTERIOR SHEATHING TO FULL WALL HEIGHT; CLEAR SEALED
 - 140MM WOOD FRAMING @ 406MM O.C.
 - 16MM G1S PLYWOOD INTERIOR SHEATHING TO FULL WALL HEIGHT; CLEAR SEALED

- IW2** G1S PLYWD ON WOOD STUD FRAMING (INSULATED)
- 16MM G1S PLYWOOD INTERIOR SHEATHING TO FULL WALL HEIGHT; CLEAR SEALED
 - 140MM WOOD FRAMING @ 406MM O.C. (FILL CAVITY W/ 140mm MINERAL WOOL BATT INSULATION)
 - 6 MIL POLYETHYLENE VAPOUR BARRIER MEMBRANE
 - 16MM G1S PLYWOOD INTERIOR SHEATHING TO FULL WALL HEIGHT; CLEAR SEALED

ROOF TYPES

- R1** METAL ROOFING ON WOOD STUD FRAMING
- 22MM PREFINISHED 22 GA. STANDING SEAM METAL ROOFING
 - ADHERED WATERPROOF MEMBRANE
 - 16MM PLYWOOD SHEATHING
 - WOOD TRUSS FRAMING

FLOOR TYPES

- F1** SLAB ON GRADE
- REINFORCED CONCRETE SLAB ON GRADE (REFER TO STRUCTURAL)
 - UNDERSLAB VAPOUR BARRIER MEMBRANE
 - COMPACTED SAND
 - COMPACTED BASE (REFER TO STRUCTURAL)
 - COMPACTED SUB-BASE (REFER TO STRUCTURAL)

FLOOR FINISH NOTE:

NEW CONCRETE FLOOR TO HAVE PIGMENTED POLYURETHANE (ON EPOXY BASE) FINISH. REFER TO SPECIFICATION SECTION 09 91 13 INTERIOR PAINTING; SUBSECTION 2.5.4 - INTERIOR PAINTING SYSTEMS FOR DETAILS

SYMBOL LEGEND

	SECTION DETAILS & BUILDING SECTION TAG
	CALLOUT TAG
	ELEVATION TAG
	GLAZING ELEVATION TAG
	LEVEL TAG
	SPOT ELEVATION
	WALL TAG
	FLOOR TAG
	ROOF TAG
	DOOR TAG
	GRID LINE
	ROOM TAG
	INDICATES GLAZING
	BREAK LINE
	ACTUATOR
	CENTRE LINE
	NORTH ARROW

