Base course timber :

- Base course timbers shall be pinned with a minimum of two (2) 19mm dia.
 by 900mm rebar at maximum 1200mm o.c.
- All rows of timber above base course shall be securely spiked with a minimum of two (2 x12mm dia. by 250mm spikes at maximum 1200mm o.c.
- Preservative must be applied to all end cuts.

Drawing Title:

Drawing No:

Double Timber Edging with Cap

SCD-651A

25 x 140mm (1"-5/4" x 6") Pedra or Composite Cap. (actual size of composite board must be - shall be pre-drilled and screwed down using screws treated for ACQ use and sized to suit. Screws to extend into timber equal or wider than board below) Joints to be base at min. 50mm and to be countersunk into cap. Two parallel lapped with Timber below. Grain of Wood Curved screws every 600mm O.C. along length and at ends. Only use Down as Shown. butt joints for straight sections of pedra. Min. length of timbers to be 1200mm. Install longest lengths possible. 140 x 140mm (6" x 6") S4S (smooth four sides) Pressure Treated Timber. Joints to be butt joints. Joints in straight runs are to be lapped over timber below by a minimum of 600mm. 12mm dia. x 250mm Spikes @ max. 1200mm O.C. 8mm Chamfer Safety Surfacing Topsoil and Sod/Seed Repairs. Ensure positive Top Edges drainage away from play area - min. 1%, max. 10% slope. (If sod is specified, use one full width of sod) 600 mm **Existing Grade** Non-Woven Geotextile Fabric between subgrade and safety surfacing 75mm Depth (min.) x 300mm Width - 19mm Existing Subgrade down crushed granular base 19mm dia. x 500mm Rebar @ max. 1200mm O.C. and at all max. 1200 o.c. joints. 12mm dia. x 250mm Spikes @ max. 1200mm O.C. 19mm dia. x 500mm Rebar @ max. 1200mm O.C. and at all joints max. 1200 o.c

REVISION: 2

DATE: June 25, 2015

SCALE: NTS DRAWN BY: SP

The City of Winnipeg Planning, Property and Development Department Planning and Land Use Division Unit 15 - 30 Fort Street, Winnipeg, MB, R3C 4X5

DIMENSIONS SHOWN ARE IN MILLIMETRES UNLESS OTHERWISE SPECIFIED

