

CRAWLSPACE GENERAL NOTES:

1. SLOPE ALL WEEPING TILE MINIMUM 1% TO SUMP PITS.

LEGEND:

DIRECTION OF WEEPING TILE DOWNWARD SLOPE AT MINIMUM 1% TO SUMP PUMP PIT

100 mm PERFORATED WEEPING TILE IN TRENCH. REFER TO TYPICAL DETAILS & SECTIONS.

PERFORATED WEEPING TILE

NON-PERFORATED WEEPING TILE

WEEPING TILE CLEAN OUT

— - — WEEPING TILE HIGH POINT

- - - - - SUMP PUMP PIT DISCHARGE LINE

DRAWING REFERENCE NOTES:

REFERENCE NOTE TAG DESCRIPTION

1.01 FLOOR ACCESS DOOR A C/W VERTICAL LADDER ABOVE, REFER TO DETAIL 9 ON A5.3.

1.02 FLOOR ACCESS DOOR B C/W STEEL GRATE STAIR
ASSEMBLY, REFER TO SECTION DETAILS 10 AND 11 ON

1.03 WEEPING TILE SUMP PIT, REFER TO DETAILS AP2.02 AND AP2.03.

1.04 CONTINUOUS CONCRETE PAVER WALKWAY.

1.05 FIRESTOP WALL CONSTRUCTION, REFER TO TYPICAL DETAIL AP2.04.

1.06 CONCRETE ENTRANCE SLAB ABOVE, REFER TO STRUCTURAL.

1.07 EXTENT OF WOOD PORCH ABOVE, REFER TO LANDSCAPE & STRUCTURAL.

