



## 542-2020 ADDENDUM 1

### ASSINIBOIA WEST COMMUNITY CENTRE WADING POOL UPGRADES

#### **URGENT**

**PLEASE FORWARD THIS DOCUMENT TO  
WHOEVER IS IN POSSESSION OF THE  
TENDER**

ISSUED: August 26, 2020  
BY: Dean Spearman  
TELEPHONE NO. 204 261-4137

**THIS ADDENDUM SHALL BE INCORPORATED  
INTO THE TENDER AND SHALL FORM A PART  
OF THE CONTRACT DOCUMENTS**

Template Version: A20190115

---

**Please note the following and attached changes, corrections, additions, deletions, information and/or instructions in connection with the Tender, and be governed accordingly. Failure to acknowledge receipt of this Addendum in Paragraph 10 of Form A: Bid may render your Bid non-responsive.**

---

#### **PART B – BIDDING PROCEDURES**

Revise B2.1 to read: The Submission Deadline is 12:00 noon Winnipeg time, **August 31, 2020.**

#### **PART E – SPECIFICATIONS**

Revise: E20.4 to read: Deck shall have an Water Flecks warning strip at the edge of the deck.

- (a) Thickness of Flecks shall be 9.5 mm.
- (b) Top surface of Flecks shall be flush with the adjacent concrete surface.
- (c) Exposed edge of Flecks shall be formed rounded w. approx. 9 mm radius.

REVISE: E23 TO READ:

#### **E23 BASIN SURFACING**

E23.1 This section shall cover the construction of a resilient overlay surfacing in the existing pool basin.

E23.2 Material to be Water Flecks surfacing or equal approved in accordance with B7.

- (a) Colour Type A to be Light Blue in basin and on covers (182.0 sq. m.).
- (b) Colour Type B to be Tan on accessible entry (5.75 sq. m.).
- (c) Colour Type C to be Dark Blue in warning strip (7.7 sq. m.).

E23.3 Water Flecks is distributed by Prairie Surfaces, contact Dave Jones (204)295-5520, [djones@prairiesurfaces.ca](mailto:djones@prairiesurfaces.ca).

E23.4 Installation

- (a) Surfacing shall be installed by a qualified installer.
- (b) Ensure any new concrete has cured for a minimum of 30 days.
- (c) Power wash deck surface.
- (d) Install keyways in the existing spray heads, drain and the inside of the pool as per manufacturers recommendations
- (e) Install Flecks surfacing according to Manufacturers recommendations.

- (f) The depth of Water Flecks is nominally 9.5 mm. Within the basin itself adjust depth of flecks to accommodate fluctuations in the concrete surface as necessary to produce a smooth finished product.
- (g) Temperature must remain above 10 degrees C throughout the installation and curing process
- (h) Do not begin installation until it is not raining and there is no rain in the immediate forecast or within 72 hours
- (i) Protect the installed surface for a minimum of 72 hours following installation.
- (j) Payment shall be as per Form B:Prices at the price for the item "Basin Surfacing".

## **DRAWINGS**

Replace: 542-2020 \_Drawing\_ L-2-RC with 542-2020 \_Addendum\_1 Drawing L-2-RD

542-2020 \_Drawing\_ L-6-RC with 542-2020 \_Addendum\_1 Drawing L-6-RD