



- CONSTRUCTION NOTES**
- INSTALL DETECTABLE WARNING SURFACE TILE AT CURB RAMP AS PER SD-228AA (TYP.)
 - REMOVE EXISTING CONCRETE SIDEWALK AND CURB AND CONSTRUCT NEW MONOLITHIC CURB AND SIDEWALK WITH BLOCKOUTS (SEE DETAIL)
 - REMOVE EXISTING INTERLOCKING PAVING STONE SIDEWALK AND CURB AND CONSTRUCT NEW MONOLITHIC CURB AND SIDEWALK WITH BLOCKOUTS (SEE SE-22-124)
 - REGRADE EXISTING PAVING STONES
 - CONSTRUCT 12.75 m² SILVA CELL WITH A SUMP PIT, TREE WELL CURBING, ADA COMPLIANT - 8709-A 48"x48" GRATE AND FRAME; NEW TREE TO BE SUPPLIED AND PLANTED BY OTHERS (SEE SE-22-125)
 - CONSTRUCT 25.5 m² SILVA CELL WITH DRAINAGE CONNECTED TO EXISTING CB, AND ADA COMPLIANT GRATES AND FRAMES; NEW TREES TO BE SUPPLIED AND PLANTED BY OTHERS (SEE SE-22-125)
 - TREE REMOVAL AS PER CW 3010-R4
 - REMOVE TREE WELL CURBING AND SOIL AND CONSTRUCT NEW MONOLITHIC CURB AND SIDEWALK (SD-228B)

- GENERAL NOTES**
- UTILITY DIMENSIONS ARE TO BACK OF CURB
 - ALL CURB RADII UNDER 15.0m SHALL BE MODIFIED
 - PAVING BAND ALIGNMENT TO BE DIRECTED BY CONTRACT ADMINISTRATOR
 - CURB REPLACEMENT AS DIRECTED BY CONTRACT ADMINISTRATOR
 - CONTRACTOR TO CONFIRM THE LOCATION OF ALL UTILITIES/SERVICES IN THE FIELD PRIOR TO CONSTRUCTION
 - USE EXTREME CAUTION WHEN WORKING ABOVE UTILITY VAULTS
 - CONTRACTOR TO TAKE PRECAUTIONARY STEPS TO PROTECT EXISTING TREES WITHIN THE CONSTRUCTION LIMITS AS PER CW 1140
 - CURB REPLACEMENT AS DIRECTED BY CONTRACT ADMINISTRATOR
 - PAVING STONE INSTALLATION AS DIRECTED BY CONTRACT ADMINISTRATOR
 - NEW TREES SUPPLIED AND PLANTED BY OTHERS, MIN. 1500 FROM BACK OF CURB
 - ADJUST ALL CURB STOPS AND WATER VALVES TO GRADE

PRELIMINARY
NOT TO BE USED FOR
CONSTRUCTION

METRIC
WHOLE NUMBERS INDICATE MILLIMETERS
DECIMALIZED NUMBERS INDICATE METERS

TENDER NO. 333-2022

EXISTING	LEGEND - PLAN	PROPOSED	EXISTING	LEGEND - PLAN	PROPOSED
⊕	HYDRANT	⊕	---	LDS/WWS	---
⊗	VALVE	⊗	---	WATERMAIN	---
⊙	CURB STOP	⊙	---	GAS	---
○	MANHOLE	●	---	TRAFFIC SIGNALS	⊠
□	CATCH BASIN	■	---	HYDRO/STREET LIGHT	⊞
△	CURB INLET	▲	---	MTS/SHAW	---
○	HYDRO POLE	●	---	CURB RENEWAL	---
○	LIGHT STANDARD	●	---	PROPERTY LINE	---
○	TRAFFIC SIGNAL POLE	●	---	RAMP CURB	---
+	SURVEY BAR	+	---	ELEVATIONS	③1.000
⊕	GEODETIC BENCH MARK	⊕	---	TREE	⊕

CONCRETE	LOCATION APPROVED
▨	IB @ NW CORNER ELLICE AVE & KENNEDY ST
▨	ELEV. 232.359
▨	CONCRETE SIDEWALK
▨	UNDERGROUND STRUCTURES
▨	ASPHALT
▨	UTILITY BOX
▨	BRICK

NOTE:
LOCATION OF UNDERGROUND STRUCTURES AS SHOWN ARE BASED ON THE BEST INFORMATION AVAILABLE. BUT NO GUARANTEE IS GIVEN THAT ALL EXISTING UTILITIES ARE SHOWN OR THAT THE GIVEN LOCATIONS ARE EXACT. CONFIRMATION OF EXISTENCE AND EXACT LOCATION OF ALL SERVICES MUST BE OBTAINED FROM THE INDIVIDUAL UTILITIES BEFORE PROCEEDING WITH CONSTRUCTION.

DESIGNED BY	C.W.	CHECKED BY	R.W.
DRAWN BY	C.W.	APPROVED BY	
HOR. SCALE:	1 : 250	DATE	2022/06/09
VERTICAL:	1 : 10		



THE CITY OF WINNIPEG
PUBLIC WORKS DEPARTMENT

ELLICE AVENUE
FROM COLONY STREET TO KENNEDY STREET
SIDEWALK RENEWAL & SILVA CELL INSTALLATION
FROM STA. 1+00 TO STA. 3+00

CITY DRAWING NUMBER
SE-22-123
SHEET 1 OF 3
1