



NOTE:

1. REFER SHEET 2215 FOR BEARING REPLACEMENT SEQUENCE FOR ABUTMENT AND PEDESTAL CONSTRUCTION STAGING.
2. ALL EXPOSED EDGES TO BE CHAMFERED 20mm UNLESS NOTED OTHERWISE.
2. ROUGHEN EXISTING ABUTMENT SURFACES IN CONTACT WITH WINGWALL EXTENSION, WINGWALL CAP AND ABUTMENT BEARING PEDESTAL AS PER ICRI GUIDELINE No. 310.2R (MEDIUM SCARIFICATION) TO 6mm AMPLITUDE.



Certificate of Authorization
Tetra Tech Canada Inc.
No. 6499



TETRA TECH

DESIGNED BY:

| | |
|--|----------|
| | REVIEWED |
|--|----------|

| | |
|-------|----|
| DRAWN | EV |
|-------|----|

| |
|----------|
| APPROVED |
|----------|

SCALE:

| | |
|-------------|------|
| ACCEPTED BY | DATE |
|-------------|------|

CAM WARD P ENG 25.08.07

ORIGINAL DRAWING
REVISION " 0 " SEALED BY
S.Y.I. AWAD
25.08.07

| |
|------------------------|
| CONSULTANT DRAWING NO. |
|------------------------|



THE CITY OF WINNIPEG
PUBLIC WORKS DEPARTMENT
ENGINEERING DIVISION

LAGIMODIERE TWIN OVERPASSES
OVER CPKC KEEWATIN
REHABILITATION AND RELATED WORKS

NORTHBOUND STRUCTURE
SOUTH ABUTMENT N-0 - CONCRETE DETAILS

CITY DRAWING NUMBER

CITY DRAWING NUMBER
B123-25-2204

| | |
|--------------|----|
| D125-25-2204 | |
| SHEET | OF |

SHEET 4 OF 48

2204