


METRIC					
WHOLE NUMBERS INDICATE MILLIMETRES					
DECIMALIZED NUMBERS INDICATE METRES					
EXISTING	LEGEND - PLAN	PROPOSED	EXISTING	LEGEND - PLAN	PROPOSED
⬮	HYDRANT	⬮	---	LDS / WWS	---
⬮	VALVE	⬮	---	WATER MAIN	---
⬮	CURB STOP	⬮	---	GAS	---
⬮	MANHOLE	⬮	---	TRAFFIC SIGNALS	---
⬮	CATCH BASIN / CATCH PIT	⬮	---	HYDRO / STREET LIGHT	---
⬮	CURB INLET	⬮	---	COMMUNICATIONS	---
⬮	POLE	⬮	---	CURB RENEWAL	---
⬮	LIGHT STANDARD	⬮	---	PROPERTY LINE	---
⬮	TRAFFIC SIGNAL POLE	⬮	---	RAMP CURB	---
⬮	SURVEY BAR	⬮	---	ELEVATIONS	---
⬮	GEODETIC BENCH MARK	⬮	---	TREE / TREELINE	---


EXISTING	LEGEND - PLAN	PROPOSED
---	CONCRETE	---
---	CONC SIDEWALK / MEDIAN	---
---	ASPHALT	---
---	PAVING STONE	---
---	GRAVEL	---
---	PLANING / REMOVAL	---
---	DITCH FLOW	---
---	TOP OF SLOPE	---
---	CULVERT	---
---	SEWER FLOW DIRECTION	---
---	TEST HOLE / CORE HOLE	---

LOCATION APPROVED		UNDERGROUND STRUCTURES	
BM 40-003	ELEV 237.231 m	Tbt: in 6.1 m Conc. pile, 3.8 m S. of N.L. of Portage Ave., 30.5 m E. of line of E.L. of Seaton St. S. of Portage Ave.	
DESIGNED BY	GFC	CHECKED BY	JGK
DRAWN BY	KMB	APPROVED BY	RPB
HOR SCALE	1:250	RELEASED FOR CONSTRUCTION	
VERT SCALE	1:10		
DATE	May 5, 2025	DATE	

**Stantec**
500 - 311 Portage Avenue, Winnipeg MB Canada R3B 2B7
Tel. 204.489.5900 Fax 204.453.9012 www.stantec.com

0	ISSUED FOR TENDER	25/05/05	GFC
No.	REVISIONS	YY/MM/DD	BY

PROFESSIONAL'S SEAL



CONSULTANT FILE NAME
08661c-201-01.dwg

**THE CITY OF WINNIPEG**
PUBLIC WORKS DEPARTMENT
ENGINEERING DIVISION

2025 REGIONAL STREET RENEWALS
PORTAGE AVENUE
DAVID ST TO CAVALIER DR
ASPHALT REHABILITATION
PAVING AND GRADING
STA 0+200 TO STA 0+340

CITY DRAWING NUMBER	P-3588-3
SHEET	3 OF 14
DRAWING NUMBER	3

- NOTES
- ADJUST MH AND CB RIMS TO NEW GRADES.
 - LAMP STANDARDS, HYDRO POLES, AND ANCHORS THAT REQUIRE TEMPORARY SUPPORT, REMOVAL OR REPLACEMENT, TO BE DONE SO AT THE EXPENSE OF THE CONTRACTOR AS NECESSARY.
 - CONTRACTOR TO REGRADE/RENEW EXISTING PRIVATE SIDEWALKS TO LIMITS AS SHOWN. SIDEWALKS TO BE RENEWED WITH CONCRETE UNLESS NOTED OTHERWISE.
 - CONTRACTOR TO TAKE PRECAUTIONARY STEPS TO PROTECT EXISTING TREES WITHIN THE LIMITS OF CONSTRUCTION FROM DAMAGE FROM CONSTRUCTION ACTIVITIES AS OUTLINED IN THE SPECIFICATIONS.
 - CONTRACTOR TO CONFIRM THE LOCATION OF ALL UTILITIES/SERVICES IN THE FIELD PRIOR TO CONSTRUCTION.
 - MODIFIED BARRIER CURB TO BE USED AT ALL INTERSECTION RADII, BACK LANE RADII AND BULLNOSES.
 - CONTRACTOR TO OVERLAY DRIVEWAYS TO ENSURE POSITIVE DRAINAGE TO NEW STREET GRADES. FINAL LIMITS TO BE DETERMINED IN THE FIELD BY CONTRACT ADMINISTRATOR.
 - CB SD-023 & SD-024 OFFSETS ARE DIMENSIONED TO BOC. CB SD-025 OFFSETS ARE DIMENSIONED O/C.
 - REFER TO TENDER FOR DETAILS REGARDING TRAFFIC MANAGEMENT.
 - MATCH EXISTING GRADES AT DOOR SILLS.
 - ADJUST EXISTING WATER VALVES AND WATER SERVICE CURB STOPS TO GRADE.
 - ADD 200.000 m TO ABBREVIATED ELEVATIONS TO OBTAIN GEODETIC ELEVATIONS.
 - SEE SHEET 14 FOR TYPICAL CROSS SECTIONS
- AC WATERMAIN NOTES
- USE OF VIBRATORY HEAVY EQUIPMENT WITHIN 3.0 METERS HORIZONTALLY OF THE ASBESTOS-CONCRETE WATER MAIN CENTERLINE IS PROHIBITED. THIS RESTRICTION DOES NOT APPLY TO THE USE OF VIBRATORY ROLLERS ON THE PAVEMENT SURFACE LAYER.
 - CONCRETE DEMOLITION AND REMOVAL WITHIN 3.0 METERS HORIZONTALLY OF THE ASBESTOS-CONCRETE WATER MAIN SHALL BE COMPLETED BY SAW CUTTING OR USE OF HAND-HELD JACKHAMMERS. USE OF MACHINE MOUNTED CONCRETE BREAKERS ABOVE ASBESTOS-CONCRETE WATER MAINS IS PROHIBITED.