

## <u>NOTES</u>

- 1. ADJUST MH AND CB RIMS TO NEW GRADES.
- 2. LAMP STANDARDS, HYDRO POLES, AND ANCHORS THAT REQUIRE TEMPORARY SUPPORT, REMOVAL OR REPLACEMENT, TO BE DONE SO AT THE EXPENSE OF THE CONTRACTOR AS NECESSARY.
- CONTRACTOR TO TAKE PRECAUTIONARY STEPS TO PROTECT EXISTING TREES WITHIN THE LIMITS OF CONSTRUCTION FROM DAMAGE FROM CONSTRUCTION ACTIVITIES AS OUTLINED IN THE SPECIFICATIONS.
- CONTRACTOR TO CONFIRM THE LOCATION OF ALL UTILITIES/SERVICES IN THE FIELD PRIOR TO CONSTRUCTION.
- 5. CB SD-023 & SD-024 OFFSETS ARE DIMENSIONED TO BOC. CB SD-025 OFFSETS ARE DIMENSIONED O/C. TF-100 OFFSETS ARE DIMENSIONED TO FACE OF CURB.
- 6. REFER TO TENDER FOR DETAILS REGARDING TRAFFIC MANAGEMENT.
- 7. REFER TO TENDER SPECIFICATIONS FOR CONSTRUCTION REQUIREMENTS NEAR EXISTING GAS MAINS OR SERVICES.
- 8. ADD 200.000 m TO ABBREVIATED ELEVATIONS TO OBTAIN GEODETIC ELEVATIONS.
- BULLNOSES SHALL BE MONOLITHIC CONCRETE AS PER SD-227C, TRANSITION FROM 100mm MOUNTABLE CURB OVER 3.0m.
- 10. PRIVATE APPROACHES SHALL BE FINISHED WITH A MINIMUM 300mm GRANULAR A BASE COURSE AND 60mm SP 1 TO BACK OF RADII.

EXISTING PAVEMENT

- THE CONTRACTOR SHALL BE AWARE THAT SOME OF THE EXISTING PAVEMENT WAS LEFT IN PLACE DURING THE PREVIOUS RECONSTRUCTION OF SOUTHBOUND PEMBINA HIGHWAY.
- THE DEPTH OF THE PAVEMENT IS BETWEEN 450mm AND 600mm BELOW EXISTING GRADE.
- EXISTING PAVEMENT WITHIN THE PROPOSED PAVEMENT STRUCTURE SHALL BE REMOVED AND PAID AS CONCRETE PAVEMENT REMOVAL AND SHALL BE BACKFILLED WITH SUITABLE SITE FILL.

		ENGINEERS GEOSCIENTISTS MANITOBA Certificate of Authorization Stantec Consulting Ltd. No. 1301 TENDER No. 45-2025
Winnipeg THE CITY OF WINNIPEG PUBLIC WORKS DEPARTMENT ENGINEERING DIVISION		
	2025 REGIONAL STREET RENEWALS SOUTHBOUND PEMBINA HIGHWAY RECONSTRUCTION AND RESURFACING LA SALLE RIVER TO PERREAULT AVE	CITY DRAWING NUMBER P-3589-15 SHEET OF 15 24
AME	SOUTHBOUND PEMBINA HIGHWAY STA 1+190 TO STA 1+320	15